KERN FFN 15K2IPN



All-round bench scale, protected by stainless steel and IP65 rating



| Category | |
|------------------|--|
| Brand | KERN |
| Product category | Industrial scales |
| Product group | Food (kitchen/stainless steel/IP6568 protection) |

| Measuring System | |
|--------------------------------|--------------------------------|
| Readability [d] | 2 g |
| Weighing capacity [Max] | 15 kg |
| Number of weighing ranges | 1 |
| Eccentric loading at 1/3 [Max] | 0,01 kg |
| Reproducibility | 0,002 kg |
| Linearity | ± 0,004 kg |
| Weighing system | Strain gauge |
| Resolution | 7.500 |
| Tare range | -15 kg |
| Units | kg lb |
| Default unit | kg |
| Stabilization time | 2 s |
| Warm-up time | 30 min |
| Adjustment options | Adjusting with external weight |
| Recommended adjusting weight | 15 kg (M3) |
| Possible calibration points | 10 kg; 15 kg |

| Approval | | |
|------------------------------|-------|--|
| CE mark | ✓ | |
| | | |
| Display | | |
| Display Display digit height | 25 mm | |

| Construction | |
|---------------------------------------|--------------------------|
| Dimension housing (W×D×H) | 243×300×127 mm |
| Dimensions completely mounted (W×D×H) | 243×300×127 mm |
| Dimensions weighing surface (W×D) | 233×193 mm |
| Material housing | stainless steel, plastic |
| Material weighing plate | stainless steel |
| Levelling feet adjustable | ✓ |
| Load cells - number | 1 |

| Functions | |
|---------------------------------|----------------|
| Number of keys for operation | 3 |
| Tare function | manual (multi) |
| Underfloor weighing | None |
| IP protection - complete device | IP65 |

| Power Supplay | |
|---|------------------------|
| Input voltage power supply / power [Max] | 110 V - 230 V AC |
| Input voltage device / power [Max] | 12 V, 500 mA |
| Plug-in power supply type | Power adapter |
| Supplied plug-in power supply | Battery & Power supply |
| Plug-in power supply / adapter for countries - included with the delivery | EURO UK US CH |
| Plug-in power supply / adapter for countries - optional | EURO AUS UK US CH |
| Rechargeable battery | WTB-A01N |
| Rechargeable battery charging time | 12 h |
| Rechargeable battery operating time - backlight on | 30 h |
| Rechargeable battery operating time - backlight off | 50 h |
| Battery | no battery |

| Environmental conditions | |
|-----------------------------|--------|
| Humity of environment [Min] | 25 % |
| Humity of environment [Max] | 95 % |
| Ambient temperature [Min] | -10 °C |
| Ambient temperature [Max] | 40 °C |

| Packing & Shipping | |
|------------------------------|----------------|
| Readability force [d] (N) | 1 d |
| Shipping method | Parcel service |
| Dimensions packaging (W×D×H) | 380×403×206 mm |
| Net weight approx. | 4,0 kg |

KERN FFN 15K2IPN



All-round bench scale, protected by stainless steel and IP65 rating

Gross weight approx. 4,6 kg
UN number (hazardous goods) 2800

Services (optional)

Article number for adjustment at the location of installation

Article number for DAkkS calibration

Article number for certificate of

Article number for certificate of conformity (verification) 969-517

Piktogramme

STANDARD



OPTION

