

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: **0338**
Version: **4.0 en**
Replaces version of: 2021-09-30
Version: (3)

date of compilation: 2016-06-15
Revision: 2021-10-15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance	Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS
Article number	0338
Registration number (REACH)	01-2119473980-30-xxxx
Index number in CLP Annex VI	606-004-00-4
EC number	203-550-1
CAS number	108-10-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Laboratory chemical Laboratory and analytical use
Uses advised against:	Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone: +49 (0) 721 - 56 06 0
Telefax: +49 (0) 721 - 56 06 149
e-mail: sicherheit@carlroth.de
Website: www.carlroth.de

Competent person responsible for the safety data sheet: :Department Health, Safety and Environment

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: 0338

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.1I	Acute toxicity (inhal.)	4	Acute Tox. 4	H332
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.6	Carcinogenicity	2	Carc. 2	H351
3.8R	Specific target organ toxicity - single exposure (respiratory tract irritation)	3	STOT SE 3	H335
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

Supplemental hazard information

Code	Supplemental hazard information
EUH066	repeated exposure may cause skin dryness or cracking

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word

Danger

Pictograms

GHS02, GHS07,
GHS08



Hazard statements

H225 Highly flammable liquid and vapour
H319 Causes serious eye irritation
H332 Harmful if inhaled
H335 May cause respiratory irritation
H336 May cause drowsiness or dizziness
H351 Suspected of causing cancer

Precautionary statements

Precautionary statements - prevention

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: 0338

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P261	Avoid breathing mist/vapours
P280	Wear protective gloves/protective clothing/eye protection/face protection

Precautionary statements - response

P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

For professional users only

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

Labelling of packages where the contents do not exceed 125 ml

Signal word: **Danger**

Symbol(s)



H351	Suspected of causing cancer.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
EUH066	Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	Isobutyl methylketone
Molecular formula	C ₆ H ₁₂ O
Molar mass	100,2 g/mol
REACH Reg. No	01-2119473980-30-xxxx
CAS No	108-10-1
EC No	203-550-1
Index No	606-004-00-4

Substance, Specific Conc. Limits, M-factors, ATE			
Specific Conc. Limits	M-Factors	ATE	Exposure route
-	-	11 mg/l/4h	inhalation: vapour

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: **0338**

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

Following ingestion

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

4.2 Most important symptoms and effects, both acute and delayed

Irritation, Cough, Dyspnoea, Dizziness, Drowsiness, Narcosis

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings
water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: **0338**

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: 0338

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed. May cause decomposition by long-term light influence.

Incompatible substances or mixtures

Observe hints for combined storage.

Protect against external exposure, such as

direct light irradiation, contact with air/oxygen

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted. Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
EU	4-methylpentan-2-one	108-10-1	IOELV	20	83	50	208				2000/39/EC
GB	4-methylpentan-2-one	108-10-1	WEL	50	208	100	416				EH40/2005

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Biological limit values

Country	Name of agent	CAS No	Parameter	Notation	Identifier	Value	Material	Source
GB	4-methylpentan-2-one	108-10-1	4-methylpentan-2-one		BMGV	20 µmol/l	urine	EH40/2005

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: 0338

Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	83 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	208 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
DNEL	83 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
DNEL	208 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
DNEL	11,8 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Environmental values

Relevant PNECs and other threshold levels				
End-point	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	0,6 mg/l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0,06 mg/l	aquatic organisms	marine water	short-term (single instance)
PNEC	27,5 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	8,27 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	0,83 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
PNEC	1,3 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 °C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: 0338

only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

PE: polyethylene, Butyl caoutchouc (butyl rubber)

• material thickness

0,7mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• Splash protection - Protective gloves

• type of material: Butyl caoutchouc (butyl rubber)

• material thickness: 0,7mm


• breakthrough times of the glove material: >240 minutes (permeation: level 5)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic
Odour threshold	0,04 – 0,08 ppm
Melting point/freezing point	-84 °C
Boiling point or initial boiling point and boiling range	114 – 118 °C at 1.013 hPa
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	1,2 vol% (LEL) - 8 vol% (UEL)
Flash point	14 °C (c.c.)
Auto-ignition temperature	460 °C (DIN 51794)
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	0,7375 mm ² /s at 20 °C

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: 0338

Solubility(ies)

Water solubility 14,1 g/l at 20 °C (ECHA)

Partition coefficient

Partition coefficient n-octanol/water (log value): 1,9 (pH value: 6,7, 20 °C) (ECHA) (OECD Prüfrichtlinie 117)

Soil organic carbon/water (log KOC) 2,008 (ECHA)

Vapour pressure 20 hPa at 20 °C

Density 0,8 g/cm³ at 20 °C

Relative vapour density 3,46 (air = 1)

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard classes: There is no additional information.

Other safety characteristics:

Temperature class (EU, acc. to ATEX) T1
Maximum permissible surface temperature on the equipment: 450°C

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air. May form explosive peroxides.

If heated

Risk of ignition.

10.2 Chemical stability

May cause decomposition by long-term light influence.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Aldehydes, Nitric acid

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Direct light irradiation. Peroxide formation possible with air oxygen.

10.5 Incompatible materials

There is no additional information.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: **0338**

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5. Peroxides.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Harmful if inhaled.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	2.080 mg/kg	rat		TOXNET
dermal	LD50	3.000 mg/kg	rabbit		TOXNET
inhalation: vapour	LC50	11,6 mg/l/4h	rat		ECHA

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

vomiting, nausea, gastrointestinal complaints

• If in eyes

Causes serious eye irritation

• If inhaled

Irritation to respiratory tract, fatigue, narcosis, cough, Dyspnoea

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: 0338

- **If on skin**

repeated exposure may cause skin dryness or cracking

- **Other information**

Liver and kidney damage, Headache, Narcosis, Nausea, Vertigo, Inebriation

11.2 Endocrine disrupting properties

Not listed.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
LC50	>179 mg/l	fish	ECHA	96 h
EC50	>200 mg/l	aquatic invertebrates	ECHA	48 h

Aquatic toxicity (chronic)				
Endpoint	Value	Species	Source	Exposure time
EC50	3.623 mg/l	aquatic invertebrates	ECHA	24 h

Biodegradation

The substance is readily biodegradable.

12.2 Process of degradability

Theoretical Oxygen Demand: 2,715 mg/mg
Theoretical Carbon Dioxide: 2,636 mg/mg

Process of degradability		
Process	Degradation rate	Time
biotic/abiotic	83 %	28 d
oxygen depletion	83 %	28 d

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	1,9 (pH value: 6,7, 20 °C) (ECHA) (OECD Prüfrichtlinie 117)
---------------------------	---

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: 0338

12.4 Mobility in soil

Henry's law constant	18,75 Pa m ³ /mol at 20 °C (ECHA)
The Organic Carbon normalised adsorption coefficient	2,008 (ECHA)

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Not listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste catalogue ordinance (Germany).

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN UN 1245

IMDG-Code UN 1245

ICAO-TI UN 1245

14.2 UN proper shipping name

ADR/RID/ADN METHYL ISOBUTYL KETONE

IMDG-Code METHYL ISOBUTYL KETONE

ICAO-TI Methyl isobutyl ketone

14.3 Transport hazard class(es)



Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: 0338

ADR/RID/ADN	3
IMDG-Code	3
ICAO-TI	3
14.4 Packing group	
ADR/RID/ADN	II
IMDG-Code	II
ICAO-TI	II
14.5 Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6 Special precautions for user	
Provisions for dangerous goods (ADR) should be complied within the premises.	
14.7 Maritime transport in bulk according to IMO instruments	
The cargo is not intended to be carried in bulk.	
14.8 Information for each of the UN Model Regulations	
Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information	
Proper shipping name	METHYL ISOBUTYL KETONE
Particulars in the transport document	UN1245, METHYL ISOBUTYL KETONE, 3, II, (D/E)
Classification code	F1
Danger label(s)	3
	
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D/E
Hazard identification No	33
Emergency Action Code	3YE
International Maritime Dangerous Goods Code (IMDG) - Additional information	
Proper shipping name	METHYL ISOBUTYL KETONE
Particulars in the shipper's declaration	UN1245, METHYL ISOBUTYL KETONE, 3, II, 14°C C.C.
Marine pollutant	-
Danger label(s)	3
	
Special provisions (SP)	-

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: 0338

Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-E, S-D
Stowage category	B

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name	Methyl isobutyl ketone
Particulars in the shipper's declaration	UN1245, Methyl isobutyl ketone, 3, II
Danger label(s)	3



Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)				
Name of substance	Name acc. to inventory	CAS No	Restriction	No
Isobutyl methylketone	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3
Isobutyl methylketone	flammable / pyrophoric		R40	40
Isobutyl methylketone	substances in tattoo inks and permanent make-up		R75	75

Legend

- R3
- Shall not be used in:
 - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
 - tricks and jokes,
 - games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
 - Articles not complying with paragraph 1 shall not be placed on the market.
 - Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
 - can be used as fuel in decorative oil lamps for supply to the general public, and
 - present an aspiration hazard and are labelled with H304.
 - Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
 - Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
 - (a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps – may lead to life-threatening lung damage";
 - (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter fluid may lead to life threatening lung damage";
 - (c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.;

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: **0338**

Legend

- R40
1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:
 - metallic glitter intended mainly for decoration,
 - artificial snow and frost,
 - 'whoopee' cushions,
 - silly string aerosols,
 - imitation excrement,
 - horns for parties,
 - decorative flakes and foams,
 - artificial cobwebs,
 - stink bombs.
 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:
'For professional users only'.
 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).
 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: **0338**

Legend

- R75
1. Shall not be placed on the market in mixtures for use for tattooing purposes, and mixtures containing any such substances shall not be used for tattooing purposes, after 4 January 2022 if the substance or substances in question is or are present in the following circumstances:
 - (a) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight;
 - (b) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as reproductive toxicant category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;
 - (c) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin sensitiser category 1, 1A or 1B, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;
 - (d) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2, or as serious eye damage category 1 or eye irritant category 2, the substance is present in the mixture in a concentration equal to or greater than:
 - (i) 0,1 % by weight, if the substance is used solely as a pH regulator;
 - (ii) 0,01 % by weight, in all other cases;
 - (e) in the case of a substance listed in Annex II to Regulation (EC) No 1223/2009 (*1), the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight;
 - (f) in the case of a substance for which a condition of one or more of the following kinds is specified in column g (Product type, Body parts) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight:
 - (i) "Rinse-off products";
 - (ii) "Not to be used in products applied on mucous membranes";
 - (iii) "Not to be used in eye products";
 - (g) in the case of a substance for which a condition is specified in column h (Maximum concentration in ready for use preparation) or column i (Other) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration, or in some other way, that does not accord with the condition specified in that column;
 - (h) in the case of a substance listed in Appendix 13 to this Annex, the substance is present in the mixture in a concentration equal to or greater than the concentration limit specified for that substance in that Appendix.
 2. For the purposes of this entry use of a mixture "for tattooing purposes" means injection or introduction of the mixture into a person's skin, mucous membrane or eyeball, by any process or procedure (including procedures commonly referred to as permanent make-up, cosmetic tattooing, micro-blading and micro-pigmentation), with the aim of making a mark or design on his or her body.
 3. If a substance not listed in Appendix 13 falls within more than one of points (a) to (g) of paragraph 1, the strictest concentration limit laid down in the points in question shall apply to that substance. If a substance listed in Appendix 13 also falls within one or more of points (a) to (g) of paragraph 1, the concentration limit laid down in point (h) of paragraph 1 shall apply to that substance.
 4. By way of derogation, paragraph 1 shall not apply to the following substances until 4 January 2023:
 - (a) Pigment Blue 15:3 (CI 74160, EC No 205-685-1, CAS No 147-14-8);
 - (b) Pigment Green 7 (CI 74260, EC No 215-524-7, CAS No 1328-53-6).
 5. If Part 3 of Annex VI to Regulation (EC) No 1272/2008 is amended after 4 January 2021 to classify or re-classify a substance such that the substance then becomes caught by point (a), (b), (c) or (d) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the date of application of that new or revised classification is after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect on the date of application of that new or revised classification.
 6. If Annex II or Annex IV to Regulation (EC) No 1223/2009 is amended after 4 January 2021 to list or change the listing of a substance such that the substance then becomes caught by point (e), (f) or (g) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the amendment takes effect after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect from the date falling 18 months after entry into force of the act by which that amendment was made.
 7. Suppliers placing a mixture on the market for use for tattooing purposes shall ensure that, after 4 January 2022, the mixture is marked with the following information:
 - (a) the statement "Mixture for use in tattoos or permanent make-up";
 - (b) a reference number to uniquely identify the batch;
 - (c) the list of ingredients in accordance with the nomenclature established in the glossary of common ingredient names pursuant to Article 33 of Regulation (EC) No 1223/2009, or in the absence of a common ingredient name, the IUPAC name. In the absence of a common ingredient name or IUPAC name, the CAS and EC number. Ingredients shall be listed in descending order by weight or volume of the ingredients at the time of formulation. "Ingredient" means any substance added during the process of formulation and present in the mixture for use for tattooing purposes. Impurities shall not be regarded as ingredients. If the name of a substance, used as ingredient within the meaning of this entry, is already required to be stated on the label in accordance with Regulation (EC) No 1272/2008, that ingredient does not need to be marked in accordance with this Regulation;
 - (d) the additional statement "pH regulator" for substances falling under point (d)(i) of paragraph 1;
 - (e) the statement "Contains nickel. Can cause allergic reactions." if the mixture contains nickel below the concentration limit specified in Appendix 13;
 - (f) the statement "Contains chromium (VI). Can cause allergic reactions." if the mixture contains chromium (VI) below the concentration limit specified in Appendix 13;
 - (g) safety instructions for use insofar as they are not already required to be stated on the label by Regulation (EC) No 1272/2008.The information shall be clearly visible, easily legible and marked in a way that is indelible. The information shall be written in the official language(s) of the Member State(s) where the mixture is placed on the market, unless the Member State(s) concerned provide(s) otherwise. Where necessary because of the size of the package, the information listed in the first subparagraph, except for point (a), shall be included instead in the instructions for use. Before using a mixture for tattooing purposes, the person using the mixture shall provide the person undergoing the procedure with the information marked on the package or included in the instructions for use pursuant to this paragraph.
 8. Mixtures that do not contain the statement "Mixture for use in tattoos or permanent make-up" shall not be used for tattooing purposes.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: 0338

Legend

9. This entry does not apply to substances that are gases at temperature of 20 °C and pressure of 101,3 kPa, or generate a vapour pressure of more than 300 kPa at temperature of 50 °C, with the exception of formaldehyde (CAS No 50-00-0, EC No 200-001-8).

10. This entry does not apply to the placing on the market of a mixture for use for tattooing purposes, or to the use of a mixture for tattooing purposes, when placed on the market exclusively as a medical device or an accessory to a medical device, within the meaning of Regulation (EU) 2017/745, or when used exclusively as a medical device or an accessory to a medical device, within the same meaning. Where the placing on the market or use may not be exclusively as a medical device or an accessory to a medical device, the requirements of Regulation (EU) 2017/745 and of this Regulation shall apply cumulatively.

List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

Not listed.

Seveso Directive

2012/18/EU (Seveso III)				
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements		Notes
P5c	flammable liquids (cat. 2, 3)	5.000	50.000	51)

Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

Deco-Paint Directive

VOC content	100 % , 800 g/l
-------------	--------------------

Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	800 g/l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Isobutyl methylketone	Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-related functions in or via the aquatic environment		A)	

Legend

A) Indicative list of the main pollutants

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: 0338

Regulation on the marketing and use of explosives precursors

not listed

Regulation on drug precursors

not listed

Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AICS	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed

Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: **0338**

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification according to Regulation (EC) No 1272/2008 (CLP): change in the listing (table)	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Hazard statements: change in the listing (table)	yes
2.2		Precautionary statements - response: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
ADR/RID/ADN	Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN)
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: 0338

Abbr.	Descriptions of used abbreviations
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
SVHC	Substance of Very High Concern
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.
Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Isobutyl methylketone ROTIPURAN® ≥99 %, p.a., ACS

article number: **0338**

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.