acc. to Regulation (EC) No. 1907/2006 (REACH)

Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

Replaces version of: 2017-08-28

Version: (1)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance Nickel-aluminium alloy 50/50% Ni/Al, for syn-

thesis, powder

Article number 0663

CAS number 12635-29-9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes

(household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

Tor the surety data ... Department reducir, surety and Environmen

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.12	Substance and mixture which, in contact with water, emits flammable gas	3	Water-react. 3	H261
3.45	Skin sensitisation	1	Skin Sens. 1	H317
3.6	Carcinogenicity	2	Carc. 2	H351

United Kingdom (en) Page 1 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)



Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

article number: 0663

Section	Hazard class		Hazard class and category	Hazard statement
3.9	Specific target organ toxicity - repeated exposure	1	STOT RE 1	H372
4.1C	Hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. In contact with water releases flammable gases which may ignite spontaneously. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS02, GHS07, GHS08







Hazard statements

H261	In contact with water releases flammable gases
H317	May cause an allergic skin reaction
H351	Suspected of causing cancer
H372	Causes damage to organs (respiratory system, skin) through prolonged or re-
	peated exposure
H412	Harmful to aquatic life with long lasting effects

Precautionary statements

Precautionary statements - prevention

P223 Do not allow contact with water

P260 Do not breathe dust

P280 Wear protective gloves/eye protection

Precautionary statements - response

P308+P313 IF exposed or concerned: Get medical advice/attention

For professional users only

Hazardous ingredients for labelling: Nickel powder

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

United Kingdom (en) Page 2 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

article number: 0663

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Aluminium powder (pyrophoric)	CAS No 7429-90-5 EC No 231-072-3	50	Pyr. Sol. 1 / H250 Water-react. 2 / H261		GHS-HC T(a)
Nickel powder	CAS No 7440-02-0 EC No 231-111-4	50	Skin Sens. 1 / H317 Carc. 2 / H351 STOT RE 1 / H372 Aquatic Chronic 3 / H412	<u>(1)</u>	GHS-HC IARC: 2B

Notes

GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/

2008/EC, Annex VI)
IARC: IARC group 2B: possibly carcinogenic to humans (International Agency for Research on Cancer)

2B: T(a): This substance is marketed in a form which has the physical properties as indicated

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. After contact with skin, wash immediately with plenty of water. In case of skin reactions, consult a physician.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

United Kingdom (en) Page 3 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

article number: 0663

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings dry extinguishing powder, D-powder, dry sand

Unsuitable extinguishing media

water

5.2 Special hazards arising from the substance or mixture

Product may release hydrogen gas. Increased storage temperatures will accelerate this process. Water-reactive (in contact with water releases flammable gases).

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe dust.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains. Take up mechanically.

Advice on how to clean up a spill

Take up mechanically. Control of dust. Take up carefully when dry.

Other information relating to spills and releases

Place in appropriate containers for disposal.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

United Kingdom (en) Page 4 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

article number: 0663



SECTION 7: Handling and storage

Precautions for safe handling

Avoid exposure. Avoid dust formation.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Store in a dry place.

Incompatible substances or mixtures

Observe hints for combined storage. Do not allow contact with water.

Evaporative conditions

Keep container tightly closed and in a well-ventilated place.

Consideration of other advice:

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Coun	Name of agent	CAS No	Identifi- er	TWA [mg/ m³]	STEL [mg/ m³]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
GB	aluminium	7429-90-5	WEL	10			i	EH40/2005
GB	aluminium	7429-90-5	WEL	4			r	EH40/2005
GB	nickel	7440-02-0	WEL	0,1				EH40/2005

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur

Inhalable fraction Respirable fraction

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified) **TWA**

Relevant DNELs of components of the mixture							
Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time	
Nickel powder	7440-02-0	DNEL	0,05 mg/ m³	human, inhalat- ory	worker (industry)	chronic - systemic effects	

United Kingdom (en) Page 5 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

Relevant PNECs of components of the mixture

7440-02-0

7440-02-0

article number: 0663



Relevant DNELs of components of the mixture								
Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time		
Nickel powder	7440-02-0	DNEL	0,05 mg/ m³	human, inhalat- ory	worker (industry)	chronic - local ef- fects		
Nickel powder	7440-02-0	DNEL	11,9 mg/ m³	human, inhalat- ory	worker (industry)	acute - local ef- fects		

Name of sub-**CAS No** Threshol **Exposure time** End-Organism **Environmental** stance point d level compartment Nickel powder 7440-02-0 **PNEC** $7,1 \,^{\mu g}/_{l}$ aquatic organfreshwater short-term (single isms instance) Nickel powder 7440-02-0 **PNEC** $8,6 \, \mu g/I$ marine water aquatic organshort-term (single instance) isms aquatic organ-Nickel powder 7440-02-0 **PNEC** $0,33 \, \text{mg/}_{1}$ sewage treatment short-term (single isms plant (STP) instance) 109 mg/kg short-term (single Nickel powder 7440-02-0 **PNEC** aquatic organfreshwater sediisms ment instance)

aquatic organ-

isms

terrestrial organ-

isms

marine sediment

soil

short-term (single instance)

short-term (single

instance)

109 mg/kg

29,9 ^{mg}/_{kg}

8.2 Exposure controls

Individual protection measures (personal protective equipment)

PNEC

PNEC

Eye/face protection

Nickel powder

Nickel powder





Use safety goggle with side protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

United Kingdom (en) Page 6 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

ROTH

Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

article number: 0663

type of material

NBR (Nitrile rubber)

material thickness

>0,11 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection





Respiratory protection necessary at: Dust formation. Particulate filter device (EN 143). P2 (filters at least 94 % of airborne particles, colour code: White).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state solid

Form powder, crystalline

Colour grey - black
Odour odourless
Melting point/freezing point 1.460 °C

Boiling point or initial boiling point and boiling not de

range

not determined

Flammability mixture which, in contact with water, emits flam-

mable gases (in accordance with GHS criteria)

Lower and upper explosion limit 0 vol% (LEL) - 0 vol% (UEL)

Flash point not applicable
Auto-ignition temperature not determined
Decomposition temperature not relevant
pH (value) not applicable
Kinematic viscosity not relevant

Solubility(ies)

Water solubility not determined

Partition coefficient

United Kingdom (en) Page 7 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

article number: 0663

Partition coefficient n-octanol/water (log value): this information is not available

Vapour pressure not determined

Density and/or relative density

Density $4,3 \, {}^{9}/_{cm^{3}}$ at 20 °C

Relative vapour density information on this property is not available

~2.850 kg/_{m³} **Bulk density**

Particle characteristics No data available.

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

Pyrophoric solids

9.2.1.1 Risk of ignition Stable at room temperature for prolonged peri-0.1

ods of time (days)

There is no additional information. Other safety characteristics:

SECTION 10: Stability and reactivity

Reactivity

The mixture contains reactive substance(s). Reactivity with water.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Water, Alkali hydroxide (caustic alkali), Acids

10.4 Conditions to avoid

Protect from moisture.

10.5 Incompatible materials

There is no additional information.

Release of flammable materials with

Water

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

United Kingdom (en) Page 8 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

article number: 0663



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Aluminium powder (pyrophoric)	7429-90-5	oral	LD50	>15.900 ^{mg} / _{kg}	rat
Aluminium powder (pyrophoric)	7429-90-5	inhalation: dust/mist	LC50	>0,888 ^{mg} / _l / 4h	rat
Nickel powder	7440-02-0	oral	LD50	>9.000 ^{mg} / _{kg}	rat

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Causes damage to organs (respiratory system, skin) through prolonged or repeated exposure.

Hazard category	Target organ	Exposure route	
1	respiratory system	if exposed	
1	skin	if exposed	

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

United Kingdom (en) Page 9 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

article number: 0663



Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

Data are not available.

• If in eyes

Data are not available.

If inhaled

Data are not available.

• If on skin

May produce an allergic reaction, pruritis, localised redness

Other information

none

11.2 Endocrine disrupting properties

None of the ingredients are listed.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture							
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time		
Nickel powder	7440-02-0	LC50	15,3 ^{mg} / _l	fish	96 h		

Aquatic toxicity (chronic) of components of the mixture							
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time		
Nickel powder	7440-02-0	EC50	≤108 ^{µg} / _I	aquatic invertebrates	21 d		

Biodegradation

Data are not available.

12.2 Process of degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential	of componen	ts of the mixt	ure	
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Nickel powder	7440-02-0	45		

United Kingdom (en) Page 10 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

ROTH

Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

article number: 0663

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste catalogue ordinance (Germany).

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number or ID number

ADRRID UN 1396 IMDG-Code UN 1396 ICAO-TI UN 1396

14.2 UN proper shipping name

ADRRID ALUMINIUM POWDER, UNCOATED IMDG-Code ALUMINIUM POWDER, UNCOATED ICAO-TI Aluminium powder, uncoated

14.3 Transport hazard class(es)

ADRRID 4.3 IMDG-Code 4.3

United Kingdom (en) Page 11 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

article number: 0663

4.3
4.

14.4 Packing group

ADRRID III
IMDG-Code III
ICAO-TI III

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Proper shipping name ALUMINIUM POWDER, UNCOATED

Particulars in the transport document UN1396, ALUMINIUM POWDER, UNCOATED, 4.3,

III, (E)

Classification code W2
Danger label(s) 4.3



Excepted quantities (EQ)

Limited quantities (LQ)

Transport category (TC)

Tunnel restriction code (TRC)

Hazard identification No

423

Emergency Action Code

4W

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional information

Classification code 4.3

Danger label(s) 4.3



Excepted quantities (EQ) E1
Limited quantities (LQ) 1 kg
Transport category (TC) 3
Hazard identification No 423

United Kingdom (en) Page 12 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

article number: 0663

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name ALUMINIUM POWDER, UNCOATED

Particulars in the shipper's declaration UN1396, ALUMINIUM POWDER, UNCOATED, 4.3,

III

Marine pollutant

Danger label(s) 4.3

Special provisions (SP) 223

Excepted quantities (EQ) E1

Limited quantities (LQ) 1 kg

EmS F-G, S-O

Stowage category A

Segregation group 15 - Powdered metals

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Aluminium powder, uncoated

Particulars in the shipper's declaration UN1396, Aluminium powder, uncoated, 4.3, III

Danger label(s) 4.3



Special provisions (SP)

Excepted quantities (EQ)

Limited quantities (LQ)

A3

E1

10 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Seveso Directive

2012/	2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes	
	not assigned			

Deco-Paint Directive

VOC content	0 % 0 ⁹ / ₁
	0 3/

United Kingdom (en) Page 13 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

article number: 0663

Industrial Emissions Directive (IED)

VOC content	0 %
VOC content	0 ^g / _l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

Pollutant release and transfer registers (PRTR)

Name of substance	CAS No	Remarks	Threshold for releases to air (kg/year)
Nickel powder	7440-02-0	(8)	50

Legend

Water Framework Directive (WFD)

List of pollutants (WFD)

Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Aluminium powder (pyrophoric)	Metals and their compounds		a)	
Nickel powder	nickel	7440-02-0	b)	
Nickel powder	nickel compounds		b)	
Nickel powder	nickel compounds	7440-02-0	c)	
Nickel powder	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)	
Nickel powder	Metals and their compounds		a)	

Legend

A) B) C) Indicative list of the main pollutants

List of priority substances in the field of water policy Environmental Quality Standards for Priority Substances and certain other pollutants

Regulation on the marketing and use of explosives precursors

United Kingdom (en) Page 14 / 19

All metals shall be reported as the total mass of the element in all chemical forms present in the release

acc. to Regulation (EC) No. 1907/2006 (REACH)



Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

article number: 0663

Explosives precursors which are subject to restrictions					
Name of substance	CAS No	Type of registration	Remarks	Limit value	Upper limit value for the pur- pose of licensing under Article 5(3)
Aluminium powder (pyrophoric)	7429-90-5	Annex II	powd d < 200 µm > 70%		

Legend

> 70%

As a substance or in mixtures containing 70 % or more, by weight, of aluminium and/or magnesium. Substances on their own or in mixtures or in substances for which suspicious transactions shall be reported With a particle size less than 200 μ m. annex II

d < 200 µm

Powder powd

Additional statements

If the product is passed on to third parties, in accordance with Article 7 "Notification of the supply chain" of Regulation EU 2019/1148, the information obligation is subject to the entire supply chain and all other provisions mentioned in Article 7 on restricted and regulated raw materials.

Regulation on drug precursors

none of the ingredients are listed

Regulation on substances that deplete the ozone layer (ODS)

none of the ingredients are listed

Regulation concerning the export and import of hazardous chemicals (PIC)

none of the ingredients are listed

Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

National regulations(GB)

Restrictions according to GB REACH, Annex 17

none of the ingredients are listed

Name of substance	Name acc. to inventory	CAS No	No
Nickel-aluminium alloy	flammable / pyrophoric		40

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

United Kingdom (en) Page 15 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

article number: 0663

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

Australian Inventory of Industrial Chemicals
Chemical Inventory and Control Regulation
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances
Koroa Existing Chemical Inventory AIIC CICR

DSL ECSI

IECSC INSQ

KECI Korea Existing Chemicals Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances

Taiwan Chemical Substance Inventory

Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation:

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1		The most important adverse physicochemical, human health and environmental effects: Delayed or immediate effects can be expected after short or long-term exposure. In contact with water releases flammable gases which may ignite spontaneously. Spillage and fire water can cause pollution of watercourses.	yes
2.2		Pictograms: change in the listing (table)	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Danger		yes

United Kingdom (en) Page 16 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

article number: 0663

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2	contains: Nickel powder		yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations	
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de naviga- tion intérieures (European Agreement concerning the International Carriage of Dangerous Goods by In- land Waterways)	
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)	
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard	
BCF	Bioconcentration factor	
BOD	Biochemical Oxygen Demand	
Carc.	Carcinogenicity	
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)	
Ceiling-C	Ceiling value	
COD	Chemical oxygen demand	
DGR	Dangerous Goods Regulations (see IATA/DGR)	
DNEL	Derived No-Effect Level	
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval	
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)	
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)	
EINECS	European Inventory of Existing Commercial Chemical Substances	
ELINCS	European List of Notified Chemical Substances	
EmS	Emergency Schedule	
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)	

United Kingdom (en) Page 17 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

article number: 0663

Abbr.	Descriptions of used abbreviations	
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)	
ICAO	International Civil Aviation Organization	
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air	
IMDG	International Maritime Dangerous Goods Code	
IMDG-Code	International Maritime Dangerous Goods Code	
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval	
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval	
LEL	Lower explosion limit (LEL)	
log KOW	n-Octanol/water	
NLP	No-Longer Polymer	
PBT	Persistent, Bioaccumulative and Toxic	
PNEC	Predicted No-Effect Concentration	
Pyr. Sol.	Pyrophoric solid	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals	
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)	
Skin Sens.	Skin sensitisation	
STEL	Short-term exposure limit	
STOT RE	Specific target organ toxicity - repeated exposure	
TWA	Time-weighted average	
UEL	Upper explosion limit (UEL)	
VOC	Volatile Organic Compounds	
vPvB	Very Persistent and very Bioaccumulative	
Water-react.	Material which, in contact with water, emits flammable gases	
WEL	Workplace exposure limit	

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

United Kingdom (en) Page 18 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



Nickel-aluminium alloy 50/50% Ni/Al, for synthesis, powder

article number: 0663

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text	
H250	Catches fire spontaneously if exposed to air.	
H261	In contact with water releases flammable gases.	
H317	May cause an allergic skin reaction.	
H351	Suspected of causing cancer.	
H372	Causes damage to organs (respiratory system, skin) through prolonged or repeated exposure.	
H412	Harmful to aquatic life with long lasting effects.	

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United Kingdom (en) Page 19 / 19