according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: **1774**Version: **2.0 en**date of compilation: 2016-01-12
Revision: 2021-11-16

Replaces version of: 2016-01-12

Version: (1)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance Standard mixture of mineral oils 500 mg/l min-

eral oil and diesel in acetone

Article number 1774

Registration number (REACH)

It is not required to list the identified uses be-

cause the substance is not subject to registration

according to REACH (< 1 t/a).

Index number in CLP Annex VI 606-001-00-8

EC number 200-662-2

CAS number 67-64-1

Alternative name(s) Acetone

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes

(household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

United Kingdom (en) Page 1 / 22

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	n Hazard class		Hazard class and category	Hazard statement
2.6	2.6 Flammable liquid		Flam. Liq. 2	H225
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

Supplemental hazard information

Code	Supplemental hazard information
EUH066	repeated exposure may cause skin dryness or cracking

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

|--|

Pictograms

GHS02, GHS07



Hazard statements

H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat, sparks, open flames, hot surfaces. No smoking

Precautionary statements - response

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

Precautionary statements - storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

United Kingdom (en) Page 2 / 22

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Symbol(s)





EUH066

Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 **Substances**

Standard mixture of mineral oils Name of substance

Molecular formula C_3H_6O

Molar mass 58,08 ^g/_{mol}

CAS No 67-64-1

EC No 200-662-2

Index No 606-001-00-8

Impurities/additives/constituents:

Name of substance	Wt%
Fuels, diesel	< 0,1
Mineral oil	< 0,1

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 **Description of first aid measures**



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

United Kingdom (en) Page 3 / 22

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Irritation, Nausea, Vomiting, Gastrointestinal complaints, Headache, Vertigo, Dizziness, Drowsiness, Narcosis

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

6.3 Methods and material for containment and cleaning up

United Kingdom (en) Page 4 / 22

according to Regulation (EC) No. 1907/2006 (REACH)

ROTH

Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. When not in use, keep containers tightly closed.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

United Kingdom (en) Page 5 / 22

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

SECTION 8: Exposure controls/personal protection

Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
EU	acetone	67-64-1	IOELV	500	1.210						2000/39/ EC
GB	acetone	67-64-1	WEL	500	1.210	1.50 0	3.620				EH40/ 2005

Notation

Ceiling-C

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) STEL

TWA

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8

hours time-weighted average (unless otherwise specified)

Human health values

Relevant DNELs and other threshold levels

Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time			
DNEL	1.210 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects			
DNEL	2.420 mg/m ³	human, inhalatory	worker (industry)	acute - local effects			
DNEL	186 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic effects			

Environmental values

Relevant PNECs and other threshold levels

End- point	Threshold level	Organism	Environmental com- partment	Exposure time		
PNEC	10,6 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)		
PNEC	1,06 ^{mg} / _l	1,06 ^{mg} / _I aquatic organisms marine water		short-term (single instance)		
PNEC	100 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)		
PNEC	30,4 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)		
PNEC	3,04 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)		
PNEC	29,5 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)		

United Kingdom (en) Page 6 / 22

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

Butyl caoutchouc (butyl rubber)

material thickness

0,7mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: AX (gas filters and combined filters against low-boiling point organic compounds, colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

United Kingdom (en) Page 7 / 22

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour colourless

Odour characteristic

Melting point/freezing point -94,8 °C (ECHA)

Boiling point or initial boiling point and boiling 56,05 °C (ECHA)

range

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 60 g/m³ (LEL) - 345 g/m³ (UEL) /

2,6 vol% (LEL) - 12,8 vol% (UEL)

Flash point -17 °C (ECHA)

Auto-ignition temperature 465 °C (ECHA) (auto-ignition temperature (liquids

and gases))

Decomposition temperature not relevant

pH (value) 5 – 6 (20 °C) (ECHA)

Kinematic viscosity not determined

Solubility(ies)

Water solubility miscible in any proportion

Partition coefficient

Partition coefficient n-octanol/water (log value): -0,23 (ECHA)

Vapour pressure 240 hPa at 20 °C

Density $0.79 \, {}^{9}/_{cm^3}$ at 20 ${}^{\circ}\text{C}$

Relative vapour density 2,01 (air = 1)

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard There is no additional information.

classes:

Other safety characteristics:

Miscibility completely miscible with water

Maximum explosion pressure 8,9 bar

United Kingdom (en) Page 8 / 22

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

Surface tension 38,1 $^{\rm mN}$ / $_{\rm m}$ (-91,09 $^{\rm o}$ C) (ECHA)

Refractive index 1,359

Temperature class (EU, acc. to ATEX)

Maximum permissible surface temperature on

the equipment: 450°C

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Risk of ignition: strong oxidiser, Reducing agents, Nitric acid, Chromium(VI) oxide,

Exothermic reaction with: Alkali metals, Alkali hydroxide (caustic alkali), Bromine, Halogenated hydroxybons

drocarbons,

Danger of explosion: Chloroform, Hydrogen peroxide

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Rubber articles, different plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Δcut	a ta	xicity
\neg cut		AICILY

Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	5.800 ^{mg} / _{kg}	rat		ECHA

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Fuels, diesel	68334-30-5	inhalation: va- pour	LC50	3,6 ^{mg} / _l /4h	rat

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

United Kingdom (en) Page 9 / 22

according to Regulation (EC) No. 1907/2006 (REACH)

ROTH

Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

vomiting, nausea, gastrointestinal complaints

• If in eyes

Causes serious eye irritation, corneal opacity

• If inhaled

irritant effects, headache, vertigo, fatigue, dizziness, narcosis

• If on skin

repeated exposure may cause skin dryness or cracking

Other information

none

11.2 Endocrine disrupting properties

Not listed.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

United Kingdom (en) Page 10 / 22

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

Αd	uatic	toxicity ((acute)
ΛЧ	uutit	CONICILY	ucucc <i>j</i>

Endpoint	Value	Species	Source	Exposure time
LC50	8.120 ^{mg} / _l	fish	ECHA	96 h

Aquatic toxicity (acute) of components of the mixture

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Fuels, diesel 68334-30-5		LL50	28 ^{mg} / _l	fish	48 h
Fuels, diesel	68334-30-5	EL50	210 ^{mg} / _l	aquatic invertebrates	48 h

Aquatic toxicity (chronic)

Endpoint	Value	Species	Source	Exposure time
EC50	61,15 ^g / _l	microorganisms	ECHA	30 min

Aquatic toxicity (chronic) of components of the mixture

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Fuels, diesel	68334-30-5	LL50	>100 ^{mg} / _l	fish	24 h
Fuels, diesel	68334-30-5	EL50	>1.000 ^{mg} / _l	aquatic invertebrates	24 h

Biodegradation

The substance is readily biodegradable.

12.2 Process of degradability

Theoretical Oxygen Demand: 2,204 $^{\rm mg}/_{\rm mg}$ Theoretical Carbon Dioxide: 2,273 $^{\rm mg}/_{\rm mg}$ Biochemical Oxygen Demand: 1,85 $^{\rm g}/_{\rm g}$ at 5 d

Process of degradability

Process	Degradation rate	Time
biotic/abiotic	91 %	28 d
carbon dioxide generation	90,9 %	28 d

Degradability of components of the mixture

Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source
Fuels, diesel	68334-30-5	oxygen deple- tion	57,5 %	28 d		ECHA

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

United Kingdom (en) Page 11 / 22

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

n-octanol/water (log KOW)	-0,23 (ECHA)
BOD5/COD	963,54166667

12.4 Mobility in soil

Henry's law constant 2,929 Pa m³/ _{mol} at 25 °C (ECHA)
--

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Not listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste catalogue ordinance (Germany).

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN	UN 1090
IMDG-Code	UN 1090
ICAO-TI	UN 1090

14.2 UN proper shipping name

ADR/RID/ADN	ACETONE
IMDG-Code	ACETONE
ICAO-TI	Acetone

United Kingdom (en) Page 12 / 22

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

14.3	Transport hazard class(es)	
	ADR/RID/ADN	3
	IMDG-Code	3
	ICAO-TI	3
14.4	Packing group	
	ADR/RID/ADN	II
	IMDG-Code	II
	ICAO-TI	II
14.5	Environmental hazards	non-environmentally hazardous acc. to the dan- gerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Information	
Proper shipping name	ACETONE
Particulars in the transport document	UN1090, ACETONE, 3, II, (D/E)
Classification code	F1
Danger label(s)	3
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

Limited quantities (LQ) 1 L

Transport category (TC) 2

Tunnel restriction code (TRC) D/E

Hazard identification No 33

Emergency Action Code 2YE

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name	ACETONE
Particulars in the shipper's declaration	UN1090, ACETONE, 3, II, -17°C c.c.
Marine pollutant	-
Danger label(s)	3



Special provisions (SP)

United Kingdom (en) Page 13 / 22

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

Excepted quantities (EQ) E2 Limited quantities (LQ) 1 L

EmS F-E, S-D

Stowage category

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Acetone

Particulars in the shipper's declaration UN1090, Acetone, 3, II

Danger label(s) 3



Excepted quantities (EQ) E2 Limited quantities (LQ) 1 L

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)

Name of substance	Name acc. to inventory	CAS No	Restriction	No
Standard mixture of mineral oils	this product meets the criteria for classification in accordance with Reg- ulation No 1272/2008/EC		R3	3
Standard mixture of mineral oils	flammable / pyrophoric		R40	40
Standard mixture of mineral oils	substances in tattoo inks and permanent make-up		R75	75

Legend

1. Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

- tricks and jokes,

games for one or more participants, or any article intended to be used as such, even with ornamental aspects,

2. Articles not complying with paragraph 1 shall not be placed on the market.

3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume,

can be used as fuel in decorative oil lamps for supply to the general public, and present an aspiration hazard and are labelled with H304.

- 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation
- (CEN).
 5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
- (a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil
- or even sucking the wick of lamps may lead to life-threatening lung damage";

 (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage';

 (c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.';

United Kingdom (en) Page 14 / 22

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

Legend

R40

- 1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

 metallic glitter intended mainly for decoration,
- artificial snow and frost,
- 'whoopee' cushions,

- wildopee cashins,
 silly string aerosols,
 imitation excrement,
 horns for parties,
 decorative flakes and foams,
- artificial cobwebs,
- stink bombs.
- 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

 "For professional users only."
- 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).
- 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

United Kingdom (en) Page 15 / 22

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

Legend

R75

1. Shall not be placed on the market in mixtures for use for tattooing purposes, and mixtures containing any such substances shall not be used for tattooing purposes, after 4 January 2022 if the substance or substances in question is or are present in the following circumstances:

(a) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as carcinogen category

1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight; (b) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as reproductive toxicant category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by

(c) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin sensitiser category 1, 1A or 1B, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;

(d) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2, or as serious eye damage category 1 or eye irritant category 2, the substance is present in the mixture in a concentration equal to or greater than:

(i) 0,1 % by weight, if the substance is used solely as a pH regulator

(ií) 0,01 % by weight, in all other cases;

(e) in the case of a substance listed in Annex II to Regulation (EC) No 1223/2009 (*1), the substance is present in the

mixture in a concentration equal to or greater than 0,00005 % by weight;

(f) in the case of a substance for which a condition of one or more of the following kinds is specified in column g (Product type, Body parts) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight:

(i) "Rinse-off products";
(ii) "Not to be used in products applied on mucous membranes";
(iii) "Not to be used in eye products";

(g) in the case of a substance for which a condition is specified in column h (Maximum concentration in ready for use preparation) or column i (Other) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration, or in some other way, that does not accord with the condition specified in that column; (h) in the case of a substance listed in Appendix 13 to this Annex, the substance is present in the mixture in a concen-

(n) in the case of a substance listed in Appendix 13 to this Annex, the substance is present in the mixture in a concentration equal to or greater than the concentration limit specified for that substance in that Appendix.

2. For the purposes of this entry use of a mixture "for tattooing purposes" means injection or introduction of the mixture into a person's skin, mucous membrane or eyeball, by any process or procedure (including procedures commonly referred to as permanent make-up, cosmetic tattooing, micro-blading and micro-pigmentation), with the aim of making a mark or design on his or her body.

3. If a substance not listed in Appendix 13 falls within more than one of points (a) to (g) of paragraph 1, the strictest concentration limit laid down in the points in question shall apply to that substance. If a substance listed in Appendix 13 also falls within one or more of points (a) to (g) of paragraph 1, the concentration limit laid down in point (h) of paragraph 1 shall apply to that substance.

as also falls within one of more of points (a) to (g) of paragraph 1, the concentration limit faid down in point (ii) of paragraph 1 shall apply to that substance.

4. By way of derogation, paragraph 1 shall not apply to the following substances until 4 January 2023:
(a) Pigment Blue 15:3 (CI 74160, EC No 205-685-1, CAS No 147-14-8);
(b) Pigment Green 7 (CI 74260, EC No 215-524-7, CAS No 1328-53-6).

5. If Part 3 of Annex VI to Regulation (EC) No 1272/2008 is amended after 4 January 2021 to classify or re-classify a substance such that the substance then becomes caught by point (a), (b), (c) or (d) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the date of application of that now or revised classification in fifty the date referred to in paragraph 1 or as the case may be paragraph. plication of that new or revised classification is after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect on the date of application of that new or revised classification.

6. If Annex II or Annex IV to Regulation (EC) No 1223/2009 is amended after 4 January 2021 to list or change the listing of a substance such that the substance then becomes caught by point (e), (f) or (g) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the

amendment takes effect after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect from the date falling 18 months after entry into force of the act by which that amendment was made.

7. Suppliers placing a mixture on the market for use for tattooing purposes shall ensure that, after 4 January 2022, the mixture is marked with the following information:

(a) the statement "Mixture for use in tattoos or permanent make-up";

(a) the statement "Mixture for use in tattoos or permanent make-up";
(b) a reference number to uniquely identify the batch;
(c) the list of ingredients in accordance with the nomenclature established in the glossary of common ingredient names pursuant to Article 33 of Regulation (EC) No 1223/2009, or in the absence of a common ingredient name, the IUPAC name. In the absence of a common ingredient name or IUPAC name, the CAS and EC number. Ingredients shall be listed in descending order by weight or volume of the ingredients at the time of formulation. "Ingredient" means any substance added during the process of formulation and present in the mixture for use for tattooing purposes. Impurities shall not be regarded as ingredients. If the name of a substance, used as ingredient within the meaning of this entry, is already required to be stated on the label in accordance with Regulation (EC) No 1272/2008, that ingredient does not need to be marked in accordance with this Regulation;
(d) the additional statement "pH regulator" for substances falling under point (d)(i) of paragraph 1;
(e) the statement "Contains nickel. Can cause allergic reactions." if the mixture contains nickel below the concentration limit specified in Appendix 13;

tion limit specified in Appendix 13

(f) the statement "Contains chromium (VI). Can cause allergic reactions." if the mixture contains chromium (VI) below

the concentration limit specified in Appendix 13; (g) safety instructions for use insofar as they are not already required to be stated on the label by Regulation (EC) No 1272/2008.

The information shall be clearly visible, easily legible and marked in a way that is indelible.

The information shall be written in the official language(s) of the Member State(s) where the mixture is placed on the market, unless the Member State(s) concerned provide(s) otherwise.

Where necessary because of the size of the package, the information listed in the first subparagraph, except for point (a), shall be included instead in the instructions for use.

Before using a mixture for tattooing purposes, the person using the mixture shall provide the person undergoing the procedure with the information marked on the package or included in the instructions for use pursuant to this paragraph. 8. Mixtures that do not contain the statement "Mixture for use in tattoos or permanent make-up" shall not be used for

tattooing purposes.

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

Legend

9. This entry does not apply to substances that are gases at temperature of 20 $^{\circ}$ C and pressure of 101,3 kPa, or generate a vapour pressure of more than 300 kPa at temperature of 50 $^{\circ}$ C, with the exception of formaldehyde (CAS No 50-00-0, EC No 200-001-8).

10. This entry does not apply to the placing on the market of a mixture for use for tattooing purposes, or to the use of a mixture for tattooing purposes, when placed on the market exclusively as a medical device or an accessory to a medical device, within the meaning of Regulation (EU) 2017/745, or when used exclusively as a medical device or an accessory to a medical device, within the same meaning. Where the placing on the market or use may not be exclusively as a medical device or an accessory to a medical device, the requirements of Regulation (EU) 2017/745 and of this Regulation shall apply cumulatively.

List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

Not listed.

Seveso Directive

2012/	18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity plication of lower a quiren		Notes
P5c	flammable liquids (cat. 2, 3)	5.000	50.000	51)

Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

Deco-Paint Directive

VOC content	100 % , 790 ⁹ / _I

Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	790 ^g / _l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Standard mixture of mineral oils	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		A)	

Legend

A) Indicative list of the main pollutants

United Kingdom (en) Page 17 / 22

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

Regulation on the marketing and use of explosives precursors

Explosives precursors which are subject to restrictions					
Name of substance	CAS No	Type of registration	Remarks	Limit value	Upper limit value for the pur- pose of licensing under Article 5(3)
Standard mixture of mineral oils	67-64-1	Annex II			

Legend

annex II Substances on their own or in mixtures or in substances for which suspicious transactions shall be reported

Additional statements

If the product is passed on to third parties, in accordance with Article 7 "Notification of the supply chain" of Regulation EU 2019/1148, the information obligation is subject to the entire supply chain and all other provisions mentioned in Article 7 on restricted and regulated raw materials.

Regulation on drug precursors

Name of substance	CAS No	Classification	CN Code	Threshold level
Standard mixture of mineral oils	67-64-1	Category 3	2914 11 00	

Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

UN Convention against Illicit Traffic in Narcotic Drugs and Psychotropic Substances

Name of substance	CAS No	Listed in	HS code
Standard mixture of mineral oils	67-64-1	Table II	2914.11

National inventories

Country	Inventory	Status
AU	AICS	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed

United Kingdom (en) Page 18 / 22

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

Country	Inventory	Status
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed

Legend

AICS Australian Inventory of Chemical Substances

CICR CSCL-ENCS DSL

ECSI IECSC

Chemical Inventory of Chemical Substances
Chemical Inventory and Control Regulation
List of Existing and New Chemical Substances (CSCL-ENCS)
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances

Vorce Spiriting Chemicals Inventory

KECI Korea Existing Chemicals Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances

Taiwan Chemical Substance Inventory **Toxic Substance Control Act**

15.2 **Chemical Safety Assessment**

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification according to Regulation (EC) No 1272/2008 (CLP): change in the listing (table)	yes
2.1		Supplemental hazard information: change in the listing (table)	yes
2.1	Remarks: For full text of Hazard- and EU Hazard-state- ments: see SECTION 16.		yes
2.1	The most important adverse physicochemical, human health and environmental effects: Narcotic effects.	The most important adverse physicochemical, human health and environmental effects: The product is combustible and can be ignited by potential ignition sources.	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Precautionary statements - prevention: change in the listing (table)	yes

United Kingdom (en) Page 19 / 22

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de naviga- tion intérieures (European Agreement concerning the International Carriage of Dangerous Goods by In- land Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
ADR/RID/ADN	Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN)
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
CN Code	Combined Nomenclature
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)

United Kingdom (en) Page 20 / 22

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

Abbr.	Descriptions of used abbreviations	
ICAO	International Civil Aviation Organization	
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air	
IMDG	International Maritime Dangerous Goods Code	
IMDG-Code	International Maritime Dangerous Goods Code	
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008	
IOELV	Indicative occupational exposure limit value	
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval	
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval	
LEL	Lower explosion limit (LEL)	
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality	
NLP	No-Longer Polymer	
PBT	Persistent, Bioaccumulative and Toxic	
PNEC	Predicted No-Effect Concentration	
ppm	Parts per million	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals	
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)	
STEL	Short-term exposure limit	
SVHC	Substance of Very High Concern	
TWA	Time-weighted average	
UEL	Upper explosion limit (UEL)	
VOC	Volatile Organic Compounds	
vPvB	Very Persistent and very Bioaccumulative	
WEL	Workplace exposure limit	

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

United Kingdom (en) Page 21 / 22

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 500 mg/l mineral oil and diesel in acetone

article number: 1774

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United Kingdom (en) Page 22 / 22