according to Regulation (EC) No. 1907/2006 (REACH)



Karl-Fischer-ROTIBydroquant waterstandard 5.0 , 5 mg H₂O/g

article number: **1KPX** Version: **1.0 en**

date of compilation: 2021-06-15

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Identification of the substance

Article number

Registration number (REACH)

1KPX

not relevant (mixture)

ard 5.0 , 5 mg $H_{\rm 2}O/g$

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Uses advised against:

Laboratory chemical Laboratory and analytical use

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

Karl-Fischer-ROTI®Hydroquant waterstand-

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment sheet:

e-mail (competent person):

sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class		Hazard class and category	Hazard statement
2.6	Flammable liquid	3	Flam. Liq. 3	H226
3.10	Acute toxicity (oral)	4	Acute Tox. 4	H302
3.1D	Acute toxicity (dermal)	4	Acute Tox. 4	H312
3.1I	Acute toxicity (inhal.)	4	Acute Tox. 4	H332
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315

according to Regulation (EC) No. 1907/2006 (REACH)



Karl-Fischer-ROTI®Hydroquant waterstandard 5.0 , 5 mg $\rm H_2O/g$

article number: **1KPX**

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318
3.8R	Specific target organ toxicity - single exposure (respirat- ory tract irritation)	3	STOT SE 3	H335
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
3.9	Specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
3.10	Aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word Danger

Pictograms



Hazard statements

H226 H302+H312+H332	Flammable liquid and vapour Harmful if swallowed, in contact with skin or if inhaled
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H318	Causes serious eye damage
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs (kidney, liver, central nervous system) through prolonged or repeated exposure

Precautionary statements

Precautionary statements - prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking
P261	Avoid breathing mist/vapours/spray

P280 Wear protective gloves/eye protection

Precautionary statements - response

P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin
	with water [or shower]
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing
P312	Call a POISON CENTRE/doctor if you feel unwell

according to Regulation (EC) No. 1907/2006 (REACH)



Karl-Fischer-ROTI®Hydroquant waterstandard 5.0, 5 mg H₂O/g

article number: 1KPX

Hazardous ingredients for labelling:

1-Butanol, Xylene (isomers)

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Symbol(s)



H304 H318	May be fatal if swallowed and enters airways. Causes serious eye damage.
P280 P305+P351+P338	Wear protective gloves/eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
contains:	1-Butanol, Xylene (isomers)

2.3 **Other hazards**

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 **Substances**

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Xylene (isomers)	CAS No 1330-20-7 EC No 215-535-7 Index No 601-022-00-9 REACH Reg. No 01-2119488216- 32-xxxx	≥ 50	Flam. Liq. 3 / H226 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 STOT RE 2 / H373 Asp. Tox. 1 / H304		C(a) GHS-HC IOELV
1-Butanol	CAS No 71-36-3 EC No 200-751-6 Index No 603-004-00-6 REACH Reg. No 01-2119484630- 38-xxxx	25 - 50	Flam. Liq. 3 / H226 Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 STOT SE 3 / H335 STOT SE 3 / H336		GHS-HC

Notes

C(a): Mixture of isomers
 GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/ 2008/EC, Annex VI)
 IOELV: Substance with a community indicative occupational exposure limit value

according to Regulation (EC) No. 1907/2006 (REACH)



Karl-Fischer-ROTI®Hydroquant waterstandard 5.0 , 5 mg $\rm H_2O/g$

article number: **1KPX**

Name of sub- stance	Identifier	Specific Conc. Limits	M-Factors	ΑΤΕ	Exposure route
Xylene (isomers)	CAS No 1330-20-7	-	-	1.100 ^{mg} / _{kg} 11 ^{mg} / _l /4h	dermal inhalation: va-
	EC No 215-535-7				pour
	Index No 601-022-00-9				
1-Butanol	CAS No 71-36-3	-	-	500 ^{mg} / _{kg}	oral
	EC No 200-751-6				
	Index No 603-004-00-6				

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion

Rinse mouth with water (only if the person is conscious). Call a physician immediately. Call a doctor. Observe aspiration hazard if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Irritation, Vomiting, Aspiration hazard, Risk of serious damage to eyes, Risk of blindness, Dizziness, Drowsiness, Narcosis, Cough, Dyspnoea

4.3 Indication of any immediate medical attention and special treatment needed

none

according to Regulation (EC) No. 1907/2006 (REACH)



Karl-Fischer-ROTI®Hydroquant waterstandard 5.0, 5 mg H₂O/g

article number: **1KPX**

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapourair mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂), May produce toxic fumes of carbon monoxide if burning.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

according to Regulation (EC) No. 1907/2006 (REACH)



Karl-Fischer-ROTI®Hydroquant waterstandard 5.0 , 5 mg H₂O/g

article number: 1KPX

6.4 Reference to other sections


Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Take precautionary measures against static discharge.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted. Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
EU	xylene	1330-20- 7	IOELV	50	221	100	442				2000/39/ EC

according to Regulation (EC) No. 1907/2006 (REACH)



Karl-Fischer-ROTI®Hydroquant waterstandard 5.0, 5 mg H₂O/g

article number: 1KPX

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
GB	xylene, mixture of isomers	1330-20- 7	WEL	50	220	100	441				EH40/ 2005
GB	butan-1-ol	71-36-3	WEL			50	154				EH40/ 2005

Notation

Ceiling-C STEL

TWA

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-

minute period (unless otherwise specified) Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Biological limit values

Coun try	Name of agent	CAS No	Parameter	Nota tion	Identi- fier	Value	Material	Source
GB	xylene, mixture of isomers	1330-20- 7	methylhippuric acids	crea	BMGV	650 mmol/ mol	urine	EH40/ 2005

Notation

Creatinine crea

Relevant DNELs of components of the mixture								
Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time		
Xylene (isomers)	1330-20-7	DNEL	221 mg/m ³	human, inhalat- ory	worker (industry)	chronic - systemic effects		
Xylene (isomers)	1330-20-7	DNEL	442 mg/m ³	human, inhalat- ory	worker (industry)	acute - systemic effects		
Xylene (isomers)	1330-20-7	DNEL	221 mg/m ³	human, inhalat- ory	worker (industry)	chronic - local ef- fects		
Xylene (isomers)	1330-20-7	DNEL	442 mg/m ³	human, inhalat- ory	worker (industry)	acute - local ef- fects		
Xylene (isomers)	1330-20-7	DNEL	212 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects		
1-Butanol	71-36-3	DNEL	310 mg/m ³	human, inhalat- ory	worker (industry)	chronic - local ef- fects		

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
Xylene (isomers)	1330-20-7	PNEC	0,327 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
Xylene (isomers)	1330-20-7	PNEC	0,327 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
Xylene (isomers)	1330-20-7	PNEC	6,58 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)

according to Regulation (EC) No. 1907/2006 (REACH)



Karl-Fischer-ROTIBydroquant waterstandard 5.0 , 5 mg H₂O/g

article number: 1KPX

Relevant PNECs of components of the mixture								
Name of sub- stance	CAS No	End- point	Threshol Organism Environmental compartment		Exposure time			
Xylene (isomers)	1330-20-7	PNEC	12,46 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)		
Xylene (isomers)	1330-20-7	PNEC	12,46 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)		
Xylene (isomers)	1330-20-7	PNEC	2,31 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)		
1-Butanol	71-36-3	PNEC	0,082 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)		
1-Butanol	71-36-3	PNEC	0,008 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)		
1-Butanol	71-36-3	PNEC	2.476 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)		
1-Butanol	71-36-3	PNEC	0,324 ^{mg} / ^{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)		
1-Butanol	71-36-3	PNEC	0,032 ^{mg} / kg	aquatic organ- isms	marine sediment	short-term (single instance)		
1-Butanol	71-36-3	PNEC	0,017 ^{mg} / kg	terrestrial organ- isms	soil	short-term (single instance)		

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

Butyl caoutchouc (butyl rubber)

according to Regulation (EC) No. 1907/2006 (REACH)

Karl-Fischer-ROTIBydroquant waterstandard 5.0 , 5 mg H₂O/g

article number: **1KPX**

material thickness

0,7mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 $^{\circ}$ C, colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

.,	•
Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	not determined
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	1,2 vol% - 9,4 vol%
Flash point	21 °C
Auto-ignition temperature	340 °C
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not determined
Solubility(ies)	
Water solubility	(partially soluble)
Partition coefficient	
Partition coefficient n-octanol/water (log value):	this information is not available
Vapour pressure	6,7 hPa at 20 °C

Karl-Fischer-ROTI ${
m B}$ Hydroquant waterstandard 5.0 , 5 mg H $_2$ O/g

article number: **1KPX**

	Density Relative vapour density	0,8527 ^g / _{cm³} at 20 °C information on this property is not available
	Particle characteristics	not relevant (liquid)
	Other safety parameters	
	Oxidising properties	none
2	Other information	
	Information with regard to physical hazard classes:	There is no additional information.
	Other safety characteristics:	
	Temperature class (EU, acc. to ATEX)	T2 Maximum permissible surface temperature on the equipment: 300°C

SECTION 10: Stability and reactivity

10.1 Reactivity

9.2

The mixture contains reactive substance(s). Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Nitric acid, Sulphur, Sulphuric acid

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Rubber articles, different plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.



according to Regulation (EC) No. 1907/2006 (REACH)

Karl-Fischer-ROTIBydroquant waterstandard 5.0 , 5 mg H₂O/g

article number: **1KPX**

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.

Acute toxicity estimate (ATE) of components of the mixture							
Name of substance CAS No Exposure route ATE							
Xylene (isomers)	1330-20-7	dermal	1.100 ^{mg} / _{kg}				
Xylene (isomers)	1330-20-7	inhalation: vapour	11 ^{mg} / _l /4h				
1-Butanol	71-36-3	oral	500 ^{mg} / _{kg}				

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Xylene (isomers)	1330-20-7	inhalation: va- pour	LC50	29 ^{mg} / _l /4h	rat
Xylene (isomers)	1330-20-7	oral	LD50	3.523 ^{mg} / _{kg}	rat
1-Butanol	71-36-3	oral	LD50	2.292 ^{mg} / _{kg}	rat
1-Butanol	71-36-3	dermal	LD50	3.430 ^{mg} / _{kg}	rabbit

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.



according to Regulation (EC) No. 1907/2006 (REACH)



Karl-Fischer-ROTIBydroquant waterstandard 5.0 , 5 mg H₂O/g

article number: 1KPX

Specific target organ toxicity - repeated exposure

May cause damage to organs (kidney, liver, central nervous system) through prolonged or repeated exposure.

Hazard category	Target organ	Exposure route
2	kidney	if exposed
2	liver	if exposed
2	central nervous system	if exposed

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

aspiration hazard

• If in eyes

Causes serious eye damage, risk of blindness

• If inhaled

Irritation to respiratory tract, fatigue, narcosis, cough, Dyspnoea

• If on skin

causes skin irritation

• Other information

Other adverse effects: Liver and kidney damage

11.2 Endocrine disrupting properties

None of the ingredients are listed.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

quatic toxicity (acute) of components of the mixture							
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time		
Xylene (isomers)	1330-20-7	LC50	2,6 ^{mg} / _l	rainbow trout	96 h		
Xylene (isomers)	1330-20-7	ErC50	4,7 ^{mg} / _l	algae	72 h		
1-Butanol	71-36-3	LC50	1.376 ^{mg} / _l	fish	96 h		
1-Butanol	71-36-3	EC50	1.328 ^{mg} / _l	aquatic invertebrates	48 h		
1-Butanol	71-36-3	ErC50	225 ^{mg} / _l	algae	96 h		

according to Regulation (EC) No. 1907/2006 (REACH)



Karl-Fischer-ROTI®Hydroquant waterstandard 5.0 , 5 mg H_2O/g

article number: **1KPX**

Aquatic toxicity (chronic) of components of the mixture							
Name of sub- stance	CAS No Endpoint Value Species Expe						
Xylene (isomers)	1330-20-7	EC50	2,2 ^{mg} / _l	algae	73 h		
1-Butanol	71-36-3	EC50	18 ^{mg} / _l	aquatic invertebrates	21 d		

Biodegradation

The relevant substances of the mixture are readily biodegradable.

12.2 Process of degradability

Degradability of components of the mixture							
Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source	
Xylene (iso- mers)	1330-20-7	oxygen deple- tion	98 %	28 d		ECHA	
1-Butanol	71-36-3	biotic/abiotic	98 %	28 d			
1-Butanol	71-36-3	oxygen deple- tion	68 %	5 d		ECHA	

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture							
Name of substance CAS No BCF Log KOW BOD5/COD							
Xylene (isomers)	1330-20-7	>5,5 - <12,2	3,15 (pH value: 7, 20 °C)				
1-Butanol	71-36-3		1 (pH value: 7, 25 °C)				

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Karl-Fischer-ROTI®Hydroquant waterstandard 5.0 , 5 mg H₂O/g



article number: **1KPX**

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste catalogue ordinance (Germany).

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1	UN number or ID number	
	ADR/RID/ADN	UN 1993
	IMDG-Code	UN 1993
	ICAO-TI	UN 1993
14.2	UN proper shipping name	
	ADR/RID/ADN	FLAMMABLE LIQUID, N.O.S.
	IMDG-Code	FLAMMABLE LIQUID, N.O.S.
	ICAO-TI	Flammable liquid, n.o.s.
	Technical name (hazardous ingredients)	Xylene (isomers), 1-Butanol
14.3	Transport hazard class(es)	
	ADR/RID/ADN	3
	IMDG-Code	3
	ICAO-TI	3
14.4	Packing group	
	ADR/RID/ADN	III
	IMDG-Code	III
	ICAO-TI	III
14.5	Environmental hazards	non-environmentally hazardous acc. to the dan- gerous goods regulations
14 6	Special precautions for user	

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations



Karl-Fischer-ROTIBydroquant waterstandard 5.0 , 5 mg H $_2$ O/g

article number: **1KPX**

Transport of dangerous goods by road, rail a information	and inland waterway (ADR/RID/ADN) - Additional
Proper shipping name	FLAMMABLE LIQUID, N.O.S.
Particulars in the transport document	UN1993, FLAMMABLE LIQUID, N.O.S., (contains: Xylene (isomers), 1-Butanol), 3, III, (D/E)
Classification code	F1
Danger label(s)	3
Special provisions (SP)	274, 601
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	3
Tunnel restriction code (TRC)	D/E
Hazard identification No	30
Emergency Action Code	3Y
International Maritime Dangerous Goods Co	ode (IMDG) - Additional information
Proper shipping name	FLAMMABLE LIQUID, N.O.S.
Particulars in the shipper's declaration	UN1993, FLAMMABLE LIQUID, N.O.S., (contains: Xylene (isomers), 1-Butanol), 3, III, 21°C c.c.
Marine pollutant	-
Danger label(s)	3
Special provisions (SP)	223, 274, 955
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, <u>S-E</u>
Stowage category	A
International Civil Aviation Organization (IC	AO-IATA/DGR) - Additional information
Proper shipping name	Flammable liquid, n.o.s.
Particulars in the shipper's declaration	UN1993, Flammable liquid, n.o.s., (contains: Xy- lene (isomers), 1-Butanol), 3, III
Danger label(s)	3
Special provisions (SP)	A3
Excepted quantities (EQ)	E1

according to Regulation (EC) No. 1907/2006 (REACH)



Karl-Fischer-ROTI®Hydroquant waterstandard 5.0, 5 mg H₂O/g

article number: 1KPX

Limited quantities (LQ)

10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)				
Name of substance	Name acc. to inventory	CAS No	Restriction	Νο
Karl-Fischer-ROTI®Hydroquant water- standard 5.0	this product meets the criteria for classification in accordance with Reg- ulation No 1272/2008/EC		R3	3
Xylene (isomers)	flammable / pyrophoric		R40	40
1-Butanol	flammable / pyrophoric		R40	40
1-Butanol	substances in tattoo inks and perman- ent make-up		R75	75

Legend

R3

R40

1. Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

- tricks and jokes,

- games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
 2. Articles not complying with paragraph 1 shall not be placed on the market.
 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume,

or both, if they — can be used as fuel in decorative oil lamps for supply to the general public, and

present an aspiration hazard and are labelled with H304.
 Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation

(CEN). 5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:

ments are met: (a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with His liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps – may lead to life-threatening lung damage"; (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage'; (c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.'; 1. Shall not be used, as substance or as mixtures in aerosol dispensers where these perced dispensers are intended

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: - metallic glitter intended mainly for decoration,

artificial snow and frost,
'whoopee' cushions,

- silly string aerosols

- imitation excrement,

horns for parties,
decorative flakes and foams,

- artificial cobwebs,

stink bombs.

2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of to above is marked visibly, legibly and indelibly with: 'For professional users only'.

3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).

4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.



Karl-Fischer-ROTI®Hydroquant waterstandard 5.0 , 5 mg H₂O/g

article number: **1KPX**



8. Mixtures that do not contain the statement "Mixture for use in tattoos or permanent make-up" shall not be used for tattooing purposes.

® §ROTH

Karl-Fischer-ROTIBydroquant waterstandard 5.0 , 5 mg H₂O/g

article number: **1KPX**

Legend

9. This entry does not apply to substances that are gases at temperature of 20 °C and pressure of 101,3 kPa, or generate a vapour pressure of more than 300 kPa at temperature of 50 °C, with the exception of formaldehyde (CAS No 50-00-0, EC No 200-001-8).

10. This entry does not apply to the placing on the market of a mixture for use for tattooing purposes, or to the use of a mixture for tattooing purposes, when placed on the market exclusively as a medical device or an accessory to a medical device, within the meaning of Regulation (EU) 2017/745, or when used exclusively as a medical device or an accessory to a medical device, within the same meaning. Where the placing on the market or use may not be exclusively as a medical device or an accessory to a medical device or an accessory to a medical device, the requirements of Regulation (EU) 2017/745 and of this Regulation shall apply cumulatively.

List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

None of the ingredients are listed. (Or Concentration of the substance in a mixture: <0.1 % Mass concentration)

Seveso Directive

2012/	18/EU (Seveso III)			
Νο	Dangerous substance/hazard categories	Qualifying quantity plication of lower a quiren		Notes
P5c	flammable liquids (cat. 2, 3)	5.000	50.000	51)

Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

Deco-Paint Directive

VOC content	100 % 1.025 ^g / _l
	1.025 97

Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	1.025 ^g / _l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

Pollutant release and transfer registers (PRTR)			
Name of substance	CAS No	Remarks	Threshold for releases to air (kg/year)
Xylene (isomers)	1330-20-7	(17) (11)	

Legend

(11) Single pollutants are to be reported if the threshold for BTEX (the sum parameter of benzene, toluene, ethyl benzene, xylenes) is exceeded

(17) Total mass of xylene (ortho-xylene, meta-xylene, para-xylene)

according to Regulation (EC) No. 1907/2006 (REACH)



Karl-Fischer-ROTIBydroquant waterstandard 5.0 , 5 mg H₂O/g

article number: 1KPX

ist of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Xylene (isomers)	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		A)	

Legend

A) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

none of the ingredients are listed

Regulation on drug precursors

none of the ingredients are listed

Regulation on substances that deplete the ozone layer (ODS)

none of the ingredients are listed

Regulation concerning the export and import of hazardous chemicals (PIC)

none of the ingredients are listed

Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

National inventories

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AICS CICR

Australian Inventory of Chemical Substances Chemical Inventory and Control Regulation according to Regulation (EC) No. 1907/2006 (REACH)



Karl-Fischer-ROTIBydroquant waterstandard 5.0 , 5 mg H₂O/g

article number: **1KPX**

DSL ECSI IECSC INSQ ISHA-ENCS KECI NZIoC PICCS	List of Existing and New Chemical Substances (CSCL-ENCS) Domestic Substances List (DSL) EC Substance Inventory (EINECS, ELINCS, NLP) Inventory of Existing Chemical Substances Produced or Imported in China National Inventory of Chemical Substances Inventory of Existing and New Chemical Substances (ISHA-ENCS) Korea Existing Chemicals Inventory New Zealand Inventory of Chemicals Philippine Inventory of Chemicals and Chemical Substances (PICCS) REACH registered substances Taiwan Chemical Substance Inventory Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in imple- mentation of Council Directive 98/24/EC
Acute Tox.	Acute toxicity
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de naviga- tion intérieures (European Agreement concerning the International Carriage of Dangerous Goods by In- land Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
ADR/RID/ADN	European Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN)
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identi- fier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances

according to Regulation (EC) No. 1907/2006 (REACH)



Karl-Fischer-ROTI®Hydroquant waterstandard 5.0 , 5 mg H₂O/g

article number: **1KPX**

Abbr.	Descriptions of used abbreviations	
EmS	Emergency Schedule	
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in eithe growth (EbC50) or growth rate (ErC50) relative to the control	
Eye Dam.	Seriously damaging to the eye	
Eye Irrit.	Irritant to the eye	
Flam. Liq.	Flammable liquid	
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions	
IATA	International Air Transport Association	
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)	
ICAO	International Civil Aviation Organization	
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air	
IMDG	International Maritime Dangerous Goods Code	
IMDG-Code	International Maritime Dangerous Goods Code	
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008	
IOELV	Indicative occupational exposure limit value	
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 9 lethality during a specified time interval	
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during specified time interval	
log KOW	n-Octanol/water	
NLP	No-Longer Polymer	
PBT	Persistent, Bioaccumulative and Toxic	
PNEC	Predicted No-Effect Concentration	
ppm	Parts per million	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals	
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)	
Skin Corr.	Corrosive to skin	
Skin Irrit.	Irritant to skin	
STEL	Short-term exposure limit	
STOT RE	Specific target organ toxicity - repeated exposure	
STOT SE	Specific target organ toxicity - single exposure	
SVHC	Substance of Very High Concern	
TWA	Time-weighted average	
VOC	Volatile Organic Compounds	
	Very Persistent and very Bioaccumulative	

according to Regulation (EC) No. 1907/2006 (REACH)



Karl-Fischer-ROTIBydroquant waterstandard 5.0 , 5 mg H₂O/g

article number: **1KPX**

Abbr.	Descriptions of used abbreviations
WEL	Workplace exposure limit

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs (kidney, liver, central nervous system) through prolonged or repeated expos- ure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.