

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: **1PKH**
Version: **1.0 en**

date of compilation: 2022-06-01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance

FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

Article number

1PKH

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Laboratory and analytical use
Laboratory chemical

Uses advised against:

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone:+49 (0) 721 - 56 06 0

Telefax: +49 (0) 721 - 56 06 149

e-mail: sicherheit@carlroth.de

Website: www.carlroth.de

Competent person responsible for the safety data sheet: Department Health, Safety and Environment

e-mail (competent person):

sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.10	Acute toxicity (oral)	4	Acute Tox. 4	H302
3.1D	Acute toxicity (dermal)	4	Acute Tox. 4	H312
3.1I	Acute toxicity (inhal.)	4	Acute Tox. 4	H332
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: 1PKH

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
3.7	Reproductive toxicity	2	Repr. 2	H361d
3.8	Specific target organ toxicity - single exposure	1	STOT SE 1	H370
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
3.9	Specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
3.10	Aspiration hazard	1	Asp. Tox. 1	H304
4.1A	Hazardous to the aquatic environment - acute hazard	1	Aquatic Acute 1	H400
4.1C	Hazardous to the aquatic environment - chronic hazard	2	Aquatic Chronic 2	H411

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling

Signal word

Danger

Pictograms

GHS02, GHS07,
GHS08, GHS09



Hazard statements

H225	Highly flammable liquid and vapour
H302+H312+H332	Harmful if swallowed, in contact with skin or if inhaled
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361d	Suspected of damaging the unborn child
H370	Causes damage to organs (eye)
H373	May cause damage to organs through prolonged or repeated exposure
H410	Very toxic to aquatic life with long lasting effects

Precautionary statements

Precautionary statements - prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P260	Do not breathe dust/fume/gas/mist/vapours/spray
P280	Wear protective gloves/protective clothing/eye protection/face protection

Precautionary statements - response

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: **1PKH**

P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor
P331 Do NOT induce vomiting

Precautionary statements - storage

P403+P235 Store in a well-ventilated place. Keep cool

For professional users only

Hazardous ingredients for labelling:

Toluene, Methanol, Isooctane, 2,4,4-Trimethylpentene

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Toluene	CAS No 108-88-3 EC No 203-625-9	45 – < 50	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 Repr. 2 / H361d STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304		GHS-HC IOELV
Isooctane	CAS No 540-84-1 EC No 208-759-1	20 – < 25	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410		C(a) GHS-HC
Methanol	CAS No 67-56-1 EC No 200-659-6	15 – < 20	Flam. Liq. 2 / H225 Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 3 / H331 STOT SE 1 / H370		GHS-HC IOELV
2,4,4-Trimethylpentene	CAS No 25167-70-8 EC No 246-690-9	10 – < 15	Flam. Liq. 2 / H225 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410		D GHS-HC
Ethanol	CAS No 64-17-5 EC No 200-578-6	1 – < 5	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319		GHS-HC IARC: 1

Notes

C(a): Mixture of isomers

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: **1PKH**

Notes

- D: Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.
- GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC, Annex VI)
- IARC: 1: IARC group 1: carcinogenic to humans (International Agency for Research on Cancer)
- IOELV: Substance with a community indicative occupational exposure limit value

Name of substance	Identifier	Specific Conc. Limits	M-Factors	ATE	Exposure route
Methanol	CAS No 67-56-1 EC No 200-659-6	STOT SE 1; H370: C \geq 10 % STOT SE 2; H371: 3 % \leq C < 10 %	-	100 mg/kg 300 mg/kg 3 mg/l/4h	oral dermal inhalation: vapour

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Rinse mouth with water (only if the person is conscious). Call a physician immediately. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Call a doctor. Observe aspiration hazard if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Following inhalation: Cough, Headache, Vertigo, Dizziness, Drowsiness, Narcosis,
Following skin contact: Irritation, Has degreasing effect on the skin,
After eye contact: Conjunctival redness of the eyes, Conjunctivitis (pink eye),
Following ingestion: Abdominal pain, Malaise, Vomiting, Aspiration hazard, Poisoning effect on central nervous system can cause convulsions, laboured breathing and loss of consciousness, Loss of righting reflex, and ataxia, Serious physical decay of vision, Risk of blindness, Large doses may result in coma and death

4.3 Indication of any immediate medical attention and special treatment needed

none

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: **1PKH**

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings
water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂), May produce toxic fumes of carbon monoxide if burning.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: **1PKH**

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Measures to protect the environment

Avoid release to the environment.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted. Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: **1PKH**

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
EU	toluene	108-88-3	IOELV	50	192	100	384			H	2006/15/EC
EU	methanol	67-56-1	IOELV	200	260					H	2006/15/EC
GB	toluene	108-88-3	WEL	50	191	100	384				EH40/2005
GB	ethanol	64-17-5	WEL	1.000	1.920						EH40/2005
GB	methanol	67-56-1	WEL	200	266	250	333				EH40/2005

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur

H Absorbed through the skin

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Toluene	108-88-3	DNEL	192 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Toluene	108-88-3	DNEL	384 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
Toluene	108-88-3	DNEL	192 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
Toluene	108-88-3	DNEL	384 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
Toluene	108-88-3	DNEL	384 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Isooctane	540-84-1	DNEL	2.035 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Isooctane	540-84-1	DNEL	773 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Methanol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Methanol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: 1PKH

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Methanol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
Methanol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
Methanol	67-56-1	DNEL	20 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Methanol	67-56-1	DNEL	20 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
2,4,4-Trimethylpentene	25167-70-8	DNEL	14,7 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2,4,4-Trimethylpentene	25167-70-8	DNEL	2,1 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Ethanol	64-17-5	DNEL	1.900 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
Ethanol	64-17-5	DNEL	343 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
Ethanol	64-17-5	DNEL	950 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Toluene	108-88-3	PNEC	0,68 mg/l	aquatic organisms	freshwater	short-term (single instance)
Toluene	108-88-3	PNEC	0,68 mg/l	aquatic organisms	marine water	short-term (single instance)
Toluene	108-88-3	PNEC	13,61 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Toluene	108-88-3	PNEC	16,39 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Toluene	108-88-3	PNEC	16,39 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Toluene	108-88-3	PNEC	2,89 mg/kg	terrestrial organisms	soil	short-term (single instance)
Methanol	67-56-1	PNEC	20,8 mg/l	aquatic organisms	freshwater	short-term (single instance)
Methanol	67-56-1	PNEC	2,08 mg/l	aquatic organisms	marine water	short-term (single instance)
Methanol	67-56-1	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Methanol	67-56-1	PNEC	77 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: 1PKH

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Methanol	67-56-1	PNEC	7,7 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Methanol	67-56-1	PNEC	100 mg/kg	terrestrial organisms	soil	short-term (single instance)
2,4,4-Trimethylpentene	25167-70-8	PNEC	14,9 µg/l	aquatic organisms	freshwater	short-term (single instance)
2,4,4-Trimethylpentene	25167-70-8	PNEC	1,49 µg/l	aquatic organisms	marine water	short-term (single instance)
2,4,4-Trimethylpentene	25167-70-8	PNEC	0,233 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2,4,4-Trimethylpentene	25167-70-8	PNEC	0,891 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2,4,4-Trimethylpentene	25167-70-8	PNEC	89,1 µg/kg	aquatic organisms	marine sediment	short-term (single instance)
2,4,4-Trimethylpentene	25167-70-8	PNEC	0,397 mg/kg	terrestrial organisms	soil	short-term (single instance)
Ethanol	64-17-5	PNEC	0,79 mg/cm ³	unknown	marine water	intermittent release
Ethanol	64-17-5	PNEC	2,75 mg/cm ³	unknown	air	intermittent release
Ethanol	64-17-5	PNEC	3,6 mg/cm ³	unknown	freshwater sediment	intermittent release
Ethanol	64-17-5	PNEC	580 mg/cm ³	unknown	sewage treatment plant (STP)	intermittent release
Ethanol	64-17-5	PNEC	0,63 mg/cm ³	unknown	soil	intermittent release
Ethanol	64-17-5	PNEC	0,96 mg/cm ³	unknown	freshwater	intermittent release

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: **1PKH**

• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

Butyl caoutchouc (butyl rubber)

• material thickness

0,7mm

• breakthrough times of the glove material


>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: AX (gas filters and combined filters against low-boiling point organic compounds, colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	clear
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	~64 °C at 1.013 hPa
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	not determined
Flash point	-12 °C
Auto-ignition temperature	not determined
Decomposition temperature	not relevant

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: **1PKH**

pH (value)	not determined
Kinematic viscosity	not determined
<u>Solubility(ies)</u>	
Water solubility	not determined
<u>Partition coefficient</u>	
Partition coefficient n-octanol/water (log value):	this information is not available
Vapour pressure	not determined
<u>Density and/or relative density</u>	
Density	0,7864 g/cm ³ at 20 °C
Relative vapour density	information on this property is not available
Particle characteristics	not relevant (liquid)
<u>Other safety parameters</u>	
Oxidising properties	none

9.2 Other information

Information with regard to physical hazard classes:	There is no additional information.
Other safety characteristics:	There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

The mixture contains reactive substance(s). Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Danger of explosion: Oxidisers, Perchlorates, Nitrogen oxides (NO_x), Chlorates, Halogenated hydrocarbons, Hydrogen peroxide, Nitric acid, Sulphuric acid,

Exothermic reaction with: Reducing agents, Acids, Chlorine, Chloroform, Acid chlorides, inorganic,

Dangerous/dangerous reactions with: Fluorine, Alkali metals, Alkaline earth metal, strong oxidiser

10.4 Conditions to avoid

UV-radiation/sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: 1PKH

10.5 Incompatible materials

aluminium, iron, zinc, different plastics, Rubber articles

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Methanol	67-56-1	oral	100 mg/kg
Methanol	67-56-1	dermal	300 mg/kg
Methanol	67-56-1	inhalation: vapour	3 mg/l/4h

Acute toxicity of components of the mixture					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Toluene	108-88-3	oral	LD50	5.580 mg/kg	rat
Toluene	108-88-3	inhalation: vapour	LC50	28,1 mg/l/4h	rat
Toluene	108-88-3	dermal	LD50	>5.000 mg/kg	rabbit
Isooctane	540-84-1	oral	LD50	>5.000 mg/kg	rat
Isooctane	540-84-1	inhalation: vapour	LC50	>33,52 mg/l/4h	rat
Isooctane	540-84-1	dermal	LD50	>2.000 mg/kg	rabbit
Methanol	67-56-1	inhalation: vapour	LC50	131 mg/l/4h	rat
Methanol	67-56-1	oral	LD50	5.628 mg/kg	rat
Methanol	67-56-1	oral	LDLo	143 mg/kg	human
Methanol	67-56-1	dermal	LD50	15.800 mg/kg	rabbit
2,4,4-Trimethylpentene	25167-70-8	oral	LD50	>2.000 mg/kg	rat
2,4,4-Trimethylpentene	25167-70-8	dermal	LD50	>2.000 mg/kg	rat

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: 1PKH

Acute toxicity of components of the mixture					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Ethanol	64-17-5	inhalation: vapour	LC50	95,6 mg/l/4h	rat
Ethanol	64-17-5	oral	LD50	7.060 mg/kg	rat

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

Causes damage to organs (eye). May cause drowsiness or dizziness.

Hazard category	Target organ	Exposure route
1	eye	if exposed

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

abdominal pain, vomiting, aspiration hazard, loss of righting reflex, and ataxia, poisoning effect on central nervous system can cause convulsions, laboured breathing and loss of consciousness, risk of blindness, large doses may result in coma and death

• If in eyes

conjunctivitis (pink eye)

• If inhaled

vertigo, cough, headache, fatigue, narcosis

• If on skin

has degreasing effect on the skin, causes skin irritation

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: 1PKH

• Other information

none

11.2 Endocrine disrupting properties

None of the ingredients are listed.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Toluene	108-88-3	LC50	5,5 mg/l	fish	96 h
Toluene	108-88-3	EC50	84 mg/l	microorganisms	24 h
Isooctane	540-84-1	LL50	18,4 mg/l	fish	96 h
Isooctane	540-84-1	LC50	0,11 mg/l	fish	96 h
Isooctane	540-84-1	EC50	0,4 mg/l	aquatic invertebrates	48 h
Isooctane	540-84-1	EL50	2,4 mg/l	aquatic invertebrates	48 h
Methanol	67-56-1	LC50	15.400 mg/l	fish	96 h
Methanol	67-56-1	ErC50	22.000 mg/l	algae	96 h
2,4,4-Trimethylpentene	25167-70-8	LC50	0,58 mg/l	fish	96 h
2,4,4-Trimethylpentene	25167-70-8	EC50	1,2 mg/l	aquatic invertebrates	48 h
2,4,4-Trimethylpentene	25167-70-8	ErC50	1,5 mg/l	algae	72 h
Ethanol	64-17-5	LC50	8.140 mg/l	orfe (Leuciscus idus)	96 h
Ethanol	64-17-5	EC50	9.000 - 14.000 mg/l	daphnia magna	48 h

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Toluene	108-88-3	LC50	3,78 mg/l	aquatic invertebrates	2 d
Toluene	108-88-3	EC50	3,23 mg/l	aquatic invertebrates	7 d
Isooctane	540-84-1	EL50	1,6 mg/l	aquatic invertebrates	21 d
Isooctane	540-84-1	EC50	0,23 mg/l	aquatic invertebrates	21 d

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: 1PKH

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
2,4,4-Trimethylpentene	25167-70-8	EC50	0,33 mg/l	aquatic invertebrates	21 d

Biodegradation

Data are not available.

12.2 Process of degradability

Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
Isooctane	540-84-1	oxygen depletion	61,81 %	70 d		ECHA
Methanol	67-56-1	biotic/abiotic	99 %	30 d		
Methanol	67-56-1	oxygen depletion	69 %	5 d		ECHA
Ethanol	64-17-5	biotic/abiotic	94 %	d		

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Toluene	108-88-3	90	2,73 (pH value: 7, 20 °C)	
Isooctane	540-84-1	231	4,08	
Methanol	67-56-1		-0,77	
2,4,4-Trimethylpentene	25167-70-8	466,8	4,9 - 5 (pH value: 7, 25 °C)	
Ethanol	64-17-5		-0,31	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: 1PKH

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste catalogue ordinance (Germany).

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number or ID number

ADRRID	UN 1992
IMDG-Code	UN 1992
ICAO-TI	UN 1992

14.2 UN proper shipping name

ADRRID	FLAMMABLE LIQUID, TOXIC, N.O.S.
IMDG-Code	FLAMMABLE LIQUID, TOXIC, N.O.S.
ICAO-TI	Flammable liquid, toxic, n.o.s.
Technical name (hazardous ingredients)	Methanol, Toluene

14.3 Transport hazard class(es)

ADRRID	3 (6.1)
IMDG-Code	3 (6.1)
ICAO-TI	3 (6.1)

14.4 Packing group

ADRRID	II
IMDG-Code	II
ICAO-TI	II

14.5 Environmental hazards

hazardous to the aquatic environment

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: **1PKH**

Environmentally hazardous substance (aquatic environment): Isooctane

14.6 Special precautions for user


Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments


The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Proper shipping name	FLAMMABLE LIQUID, TOXIC, N.O.S.
Particulars in the transport document	UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S., (contains: Methanol, Toluene), 3 (6.1), II, (D/E), environmentally hazardous
Classification code	FT1
Danger label(s)	3+6.1, "Fish and tree"
	
Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	274, 802(ADN)
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D/E
Hazard identification No	336
Emergency Action Code	3WE

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID) Additional information

Classification code	FT1
Danger label(s)	3+6.1 Fish and tree
	
Environmental hazards	Yes Hazardous to water
Special provisions (SP)	274, 802(ADN)
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
Transport category (TC)	2
Hazard identification No	336

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: 1PKH

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name	FLAMMABLE LIQUID, TOXIC, N.O.S.
Particulars in the shipper's declaration	UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S., (contains: Methanol, Toluene, Isooctane), 3 (6.1), II, -12°C c.c., MARINE POLLUTANT
Marine pollutant	YES (hazardous to the aquatic environment), (Isooctane)
Danger label(s)	3+6.1, "Fish and tree"
Special provisions (SP)	274
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-E, S-D
Stowage category	B

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name	Flammable liquid, toxic, n.o.s.
Particulars in the shipper's declaration	UN1992, Flammable liquid, toxic, n.o.s., (contains: Methanol, Toluene), 3 (6.1), II
Environmental hazards	YES (hazardous to the aquatic environment)
Danger label(s)	3+6.1
Special provisions (SP)	A3
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
E1	environmental hazards (hazardous to the aquatic environment, cat. 1)	100 200	56)

Notation

56) Hazardous to the Aquatic Environment in category Acute 1 or Chronic 1

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: 1PKH

Deco-Paint Directive

VOC content	100 % 786,4 g/l
-------------	--------------------

Industrial Emissions Directive (IED)

VOC content	100 %
VOC content (Water content was discounted)	786,4 g/l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

Pollutant release and transfer registers (PRTR)			
Name of substance	CAS No	Remarks	Threshold for releases to air (kg/year)
Toluene	108-88-3	(11)	

Legend

(11) Single pollutants are to be reported if the threshold for BTEX (the sum parameter of benzene, toluene, ethyl benzene, xylenes) is exceeded

Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Toluene	Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-related functions in or via the aquatic environment		a)	
Ethanol	Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-related functions in or via the aquatic environment		a)	
Methanol	Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-related functions in or via the aquatic environment		a)	

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: 1PKH

Legend

A) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

none of the ingredients are listed

Regulation on drug precursors

Name of substance	CAS No	Classification	CN Code	Threshold level
Toluene	108-88-3	Category 3	2902 30 00	

Regulation on substances that deplete the ozone layer (ODS)

none of the ingredients are listed

Regulation concerning the export and import of hazardous chemicals (PIC)

none of the ingredients are listed

Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list

none of the ingredients are listed

Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)			
Name of substance	Name acc. to inventory	CAS No	No
FAM test liquid B	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		3
2,4,4-Trimethylpentene	flammable / pyrophoric		40
Toluene	Toluene	108-88-3	48
Toluene	flammable / pyrophoric		40
Isooctane	flammable / pyrophoric		40

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

UN Convention against Illicit Traffic in Narcotic Drugs and Psychotropic Substances

Name of substance	CAS No	Listed in	HS code
Toluene	108-88-3	Table II	2902.30

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: 1PKH

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
Acute Tox.	Acute toxicity
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: **1PKH**

Abbr.	Descriptions of used abbreviations
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CN Code	Combined Nomenclature
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: **1PKH**

Abbr.	Descriptions of used abbreviations
IMDG-Code	International Maritime Dangerous Goods Code
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
Repr.	Reproductive toxicity
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



FAM test liquid B , contains methanol, for polymer materials, acc. to DIN 51604-2

article number: 1PKH

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs (eye).
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.