acc. to Regulation (EC) No. 1907/2006 (REACH)

PCB 15 ROTI®Star 100 μg/ml in isooctane

date of compilation: 2022-09-22 article number: 1X14 Version: 1.0 en

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance **PCB 15** ROTI®Star 100 μg/ml in isooctane

Article number 1X14

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory and analytical use

Laboratory chemical

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes

(household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr, 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

sicherheit@carlroth.de e-mail (competent person):

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
3.9	Specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
3.10	10 Aspiration hazard		Asp. Tox. 1	H304
4.1A	Hazardous to the aquatic environment - acute hazard	1	Aquatic Acute 1	H400

United Kingdom (en) Page 1 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



article number: 1X14



Section	Section Hazard class		Hazard class and category	Hazard statement
4.1C	Hazardous to the aquatic environment - chronic hazard	1	Aquatic Chronic 1	H410

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS02, GHS07, GHS08, GHS09









Hazard statements

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure
H410	Very toxic to aquatic life with long lasting effects

Precautionary statements

Precautionary statements - prevention

P280 Wear protective gloves/protective clothing/eye protection/face protection

Hazardous ingredients for labelling: PCB 15, Isooctane

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

United Kingdom (en) Page 2 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCB 15 ROTI®Star 100 μg/ml in isooctane

article number: 1X14



Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Isooctane	CAS No 540-84-1 EC No 208-759-1 Index No 601-009-00-8	90 - < 100	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410		C(a) GHS-HC
PCB 15	CAS No 2050-68-2 EC No 218-095-4 Index No 602-039-00-4	< 0,1	STOT RE 2 / H373 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	\$ \P	C GHS-HC

Notes

C(a): Mixture of isomers

C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC, Annex VI)

Name of sub- stance	Identifier	Specific Conc. Limits	M-Factors	ATE	Exposure route
PCB 15	CAS No 2050-68-2	STOT RE 2; H373: C ≥ 0,005 %	-	-	
	EC No 218-095-4				

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Call a physician immediately. Observe aspiration hazard if vomiting occurs.

United Kingdom (en) Page 3 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCB 15 ROTI®Star 100 μg/ml in isooctane

article number: 1X14



4.2 Most important symptoms and effects, both acute and delayed

Following inhalation: Drowsiness, Dizziness, Narcosis,

Following skin contact: Irritation, After eye contact: Irritant effects, Following ingestion: Aspiration hazard

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂), May produce toxic fumes of carbon monoxide if burning.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. Danger of explosion.

United Kingdom (en) Page 4 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCB 15 ROTI®Star 100 μg/ml in isooctane

article number: 1X14



6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Measures to protect the environment

Avoid release to the environment.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep in a cool place.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 2 - 8 °C

7.3 Specific end use(s)

No information available.

United Kingdom (en) Page 5 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCB 15 ROTI®Star 100 µg/ml in isooctane

article number: 1X14



SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE [PP]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source	
GB	polychlorinated bi- phenyls (PCB)	1336-36- 3	WEL		0,1						EH40/ 2005	

Notation

Ceiling-C

Ceiling value is a limit value above which exposure should not occur

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) STFI

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified) **TWA**

Relevant DNELs of components of the mixture Name of sub-**CAS No** End-**Threshol Protection Used in Exposure time** stance point d level goal, route of exposure Isooctane 540-84-1 DNEL 2.035 mg/ human, inhalatworker (industry) chronic - systemic effects m³ orv Isooctane 540-84-1 DNFI 773 mg/kg human, dermal chronic - systemic worker (industry) bw/day effects

8.2 **Exposure controls**

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection.

Skin protection





hand protection


Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

Page 6 / 19 United Kingdom (en)

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCB 15 ROTI®Star 100 μg/ml in isooctane

article number: 1X14



NBR (Nitrile rubber)

material thickness

>0,3 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour colourless

Odour like: Gasoline

Melting point/freezing point -107 °C

Boiling point or initial boiling point and boiling

range

99,2 °C at 1.013 hPa

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 45 g/m³ (LEL) - 290 g/m³ (UEL) /

1 vol% (LEL) - 6 vol% (UEL)

Flash point not determined

Auto-ignition temperature 418 °C (auto-ignition temperature (liquids and

gases))

Decomposition temperature not relevant pH (value) (neutral)

Kinematic viscosity not determined

Solubility(ies)

Water solubility (poorly soluble (1 till < 10 mg/l))

Partition coefficient

United Kingdom (en) Page 7 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

PCB 15 ROTI®Star 100 µg/ml in isooctane

Partition coefficient n-octanol/water (log value): this information is not available

Vapour pressure 28 hPa at 20 °C

Density and/or relative density

0,69 ^g/_{cm³} at 15 °C Density

Relative vapour density information on this property is not available

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

Other safety characteristics: There is no additional information.

SECTION 10: Stability and reactivity

Reactivity

The mixture contains reactive substance(s). Risk of ignition.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

There is no additional information.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

UV-radiation/sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

different plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

United Kingdom (en) Page 8 / 19



article number: 1X14

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCB 15 ROTI®Star 100 μg/ml in isooctane

article number: 1X14



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Isooctane	540-84-1	oral	LD50	>5.000 ^{mg} / _{kg}	rat
Isooctane	540-84-1	inhalation: va- pour	LC50	>33,52 ^{mg} / _l / 4h	rat
Isooctane	540-84-1	dermal	LD50	>2.000 ^{mg} / _{kg}	rabbit

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

vomiting, aspiration hazard

United Kingdom (en) Page 9 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCB 15 ROTI®Star 100 μg/ml in isooctane

article number: 1X14

• If in eyes

causes slight to moderate irritation

If inhaled

drowsiness, dizziness, fatigue, narcosis

• If on skin

causes skin irritation

Other information

none

11.2 Endocrine disrupting properties

None of the ingredients are listed.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of sub- stance	CAS No	Endpoint	Value	Value Species	
Isooctane	540-84-1	LL50	18,4 ^{mg} / _l	fish	96 h
Isooctane	540-84-1	LC50	0,11 ^{mg} / _l	fish	96 h
Isooctane	540-84-1	EC50	0,4 ^{mg} / _l	aquatic invertebrates	48 h
Isooctane	540-84-1	EL50	2,4 ^{mg} / _l	aquatic invertebrates	48 h

Aquatic toxicity (chronic) of components of the mixture

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Isooctane	540-84-1	EL50	1,6 ^{mg} / _l	aquatic invertebrates	21 d
Isooctane	540-84-1	EC50	0,23 ^{mg} / _l	aquatic invertebrates	21 d

Biodegradation

Data are not available.

12.2 Process of degradability

Degradability	v of com	ponents	of the	mixture
Degradabilit	, 0. 00	ponents	01 1110	IIIIXCUIC

Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source
Isooctane	540-84-1	oxygen deple- tion	61,81 %	70 d		ECHA

United Kingdom (en) Page 10 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

PCB 15 ROTI®Star 100 μg/ml in isooctane

article number: 1X14



Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Isooctane	540-84-1	231	4,08	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Properties of waste which render it hazardous

HP 3 flammable

HP 5 specific target organ toxicity (STOT)/aspiration toxicity

HP 14 ecotoxic

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

United Kingdom (en) Page 11 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

PCB 15 ROTI®Star 100 μg/ml in isooctane

article number: 1X14



SECTION 14: Transport information

14.1 UN number or ID number

ADRRID UN 1262 IMDG-Code UN 1262 ICAO-TI UN 1262

14.2 UN proper shipping name

ADRRID OCTANES
IMDG-Code OCTANES
ICAO-TI Octanes

14.3 Transport hazard class(es)

ADRRID 3
IMDG-Code 3
ICAO-TI 3

14.4 Packing group

ADRRID II
IMDG-Code II
ICAO-TI II

14.5 Environmental hazards hazardous to the aquatic environment

Environmentally hazardous substance (aquatic environment):

Isooctane

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Proper shipping name OCTANES

Particulars in the transport document UN1262, OCTANES, 3, II, (D/E), environmentally

hazardous

Classification code F

Danger label(s) 3, "Fish and tree"





Environmental hazards yes (hazardous to the aquatic environment)

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

United Kingdom (en) Page 12 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCB 15 ROTI®Star 100 μg/ml in isooctane

article number: 1X14

Transport category (TC) 2
Tunnel restriction code (TRC) D/E

Hazard identification No 33

Emergency Action Code 3YE

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional

information

Classification code F1

Danger label(s)

Fish and tree

Environmental hazards Yes

Hazardous to water

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
Transport category (TC) 2
Hazard identification No 33

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name OCTANES

Particulars in the shipper's declaration UN1262, OCTANES, 3, II, <23°C c.c., MARINE POL-

LUTANT

Marine pollutant yes (P) (hazardous to the aquatic environment)

Danger label(s) 3, "Fish and tree"

3



Special provisions (SP)

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

EmS F-E, S-E

Stowage category B

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Octanes

Particulars in the shipper's declaration UN1262, Octanes, 3, II

Environmental hazards yes (hazardous to the aquatic environment)

Danger label(s) 3

Excepted quantities (EQ) E2

United Kingdom (en) Page 13 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCB 15 ROTI®Star 100 μg/ml in isooctane

article number: 1X14

Limited quantities (LQ)



SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Seveso Directive

2012/	2012/18/EU (Seveso III)				
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes		
E1	environmental hazards (hazardous to the aquatic environment, cat. 1)	100 200	56)		

1 L

Notation

56) Hazardous to the Aquatic Environment in category Acute 1 or Chronic 1

Deco-Paint Directive

VOC content	99,95 % 689,7 ⁹ / _I
-------------	--

Industrial Emissions Directive (IED)

VOC content	99,95 %
VOC content	689,7 ^g / _l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

Pollutant release and transfer registers (PRTR) Name of substance CAS No Remarks Threshold for releases to air (kg/year) PCB 15 1336-36-3 0,1

Water Framework Directive (WFD)

List of pollutants (WFD)

Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
PCB 15	Dioxins and dioxin-like com- pounds		b)	HAZ (9)
PCB 15	Dioxins and dioxin-like com- pounds		c)	
PCB 15	Organohalogen compounds and substances which may form such compounds in the aquatic envir- onment		a)	

United Kingdom (en) Page 14 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCB 15 ROTI®Star 100 µg/ml in isooctane

article number: 1X14



List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
PCB 15	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)	
PCB 15	Persistent hydrocarbons and per- sistent and bioaccumulable or- ganic toxic substances		a)	

Legend

This refers to the following compounds: (9)

7 polychlorinated dibenzo-p-dioxins (PCDDs): 2,3,7,8-T4CDD (CAS 1746-01-6), 1,2,3,7,8-P5CDD (CAS 40321-76-4), 1,2,3,4,7,8-H6CDD (CAS 39227-28-6), 1,2,3,6,7,8-H6CDD (CAS 57653-85-7), 1,2,3,7,8,9-H6CDD (CAS 19408-74-3), 1,2,3,4,6,7,8-H7CDD (CAS 35822-46-9), 1,2,3,4,6,7,8,9-O8CDD (CAS 3268-87-9)

10 polychlorinated dibenzofurans (PCDFs): 2,3,7,8-T4CDF (CAS 51207-31-9), 1,2,3,7,8-P5CDF (CAS 57117-41-6), 2,3,4,7,8-P5CDF (CAS 57117-31-4), 1,2,3,4,7,8-H6CDF (CAS 70648-26-9), 1,2,3,6,7,8-H6CDF (CAS 57117-44-9), 1,2,3,7,8,9-H6CDF (CAS 72918-21-9), 2,3,4,6,7,8-H6CDF (CAS 60851-34-5), 1,2,3,4,6,7,8-H7CDF (CAS 67562-39-4), 1,2,3,4,7,8,9-H7CDF (CAS 55673-89-7), 1,2,3,4,6,7,8,9-O8CDF (CAS 39001-02-0)

12 dioxin-like polychlorinated biphenyls (PCB-DL): 3,3',4,4'-T4CB (PCB 77, CAS 32598-13-3), 3,3',4',5-T4CB (PCB 81, CAS 70362-50-4), 2,3,3',4,4'-P5CB (PCB 105, CAS 32598-14-4), 2,3,4,4',5-P5CB (PCB 114, CAS 74472-37-0), 2,3',4,4',5-P5CB (PCB 118, CAS 31508-00-6), 2,3',4,4',5'-P5CB (PCB 123, CAS 65510-44-3), 3,3',4,4',5-P5CB (PCB 126, CAS 57465-28-8), 2,3,3',4,4',5-H6CB (PCB 156, CAS 38380-08-4), 2,3,3',4,4',5'-H6CB (PCB 157, CAS 69782-90-7), 2,3',4,4',5,5'-H6CB (PCB 167, CAS 52663-72-6), 3,3',4,4',5,5'-H6CB (PCB 169, CAS 32774-16-6), 2,3,3',4,4',5,5'-H7CB (PCB 189, CAS 39635-31-9).

Indicative list of the main pollutants

List of priority substances in the field of water policy
Environmental Quality Standards for Priority Substances and certain other pollutants

A) B) C) HAZ Identified as priority hazardous substance

Regulation on the marketing and use of explosives precursors

none of the ingredients are listed

Regulation on drug precursors

none of the ingredients are listed

Regulation on substances that deplete the ozone layer (ODS)

none of the ingredients are listed

Regulation concerning the export and import of hazardous chemicals (PIC)

chemicals subject to the international prior informed consent (PIC) procedure (the 'PIC procedure').

Name of substance	Name acc. to inventory	CAS No	Wt%	Category / subcat- egory	Use limita- tion
PCB 15	polychlorinated biphenyls (PCB)	1336-36- 3	0,05	i	
PCB 15	polychlorinated biphenyls (PCB)	1336-36- 3	0,05		

Legend

Category: i - industrial chemical

United Kingdom (en) Page 15 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCB 15 ROTI®Star 100 µg/ml in isooctane

article number: 1X14



Regulation on persistent organic pollutants (POP)

Name of substance	CAS No	Wt%	Type of registra- tion	Re- marks	Exemp- tions	Concentration limit
PCB 15	1336-36-3	0,05	Annex I - A		A1-ex-08	
PCB 15	1336-36-3	0,05	Annex III - A			
PCB 15	1336-36-3	0,05	Annex IV			50 mg/kg

Legend

Without prejudice to Directive 96/59/EC, articles already in use at the time of the entry into force of this Regulation are allowed to be used. A1-ex-08

Member States shall identify and remove from use equipment (e.g. transformers, capacitors or other receptacles containing liquid stocks) containing more than 0,005 % PCBs and volumes greater than 0,05 dm3, as soon as possible but no later than 31 December 2025.

annex I - A Part A - Substances listed in the Convention and in the Protocol as well as substances listed only in the Convention annex III - A List of substances subject to release reduction provisions annex IV List of substances subject to waste management provisions set out in Article 7

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list none of the ingredients are listed

Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)				
Name of substance	Name acc. to inventory	CAS No	No	
PCB 15	this product meets the criteria for classi- fication in accordance with Regulation No 1272/2008/EC		3	
Isooctane	flammable / pyrophoric		40	

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status		
AU	AIIC	all ingredients are listed		
CA	DSL	all ingredients are listed		
CN	IECSC	all ingredients are listed		
EU	ECSI	all ingredients are listed		
EU	REACH Reg.	not all ingredients are listed		
JP	CSCL-ENCS	not all ingredients are listed		
KR	KECI	all ingredients are listed		
MX	INSQ	all ingredients are listed		
NZ	NZIoC	not all ingredients are listed		
PH	PICCS	all ingredients are listed		
TR	CICR	not all ingredients are listed		

United Kingdom (en) Page 16 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCB 15 ROTI®Star 100 μg/ml in isooctane

article number: 1X14



Country	Inventory	Status	
TW	TCSI	all ingredients are listed	
US	TSCA	all ingredients are listed	

Legend

AIIC
Australian Inventory of Industrial Chemicals
CICR
CSCL-ENCS
Chemical Inventory and Control Regulation
List of Existing and New Chemical Substances (CSCL-ENCS)
DSL
Domestic Substances List (DSL)
ECSI
ECSI
ECSU
Inventory of Existing Chemical Substances Produced or Imported in China
INSO
National Inventory of Chemical Substances
Korea Existing Chemicals Inventory NATION Inventory of Chemicals Substances

KECI Korea Existing Chemicals Inventory

NZIOC New Zealand Inventory of Chemicals

PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)

REACH Reg. REACH registered substances

TCSI Taiwan Chemical Substance Inventory

Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de naviga- tion intérieures (European Agreement concerning the International Carriage of Dangerous Goods by In- land Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)
EINECS	European Inventory of Existing Commercial Chemical Substances

United Kingdom (en) Page 17 / 19

Safety data sheet Safety data sheet acc. to Regulation (EC) No. 1907/2006 (REACH)

PCB 15 ROTI®Star 100 μg/ml in isooctane

article number: 1X14



Abbr.	Descriptions of used abbreviations
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Flam. Liq.	Flammable liquid
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Page 18 / 19 United Kingdom (en)

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCB 15 ROTI®Star 100 μg/ml in isooctane

article number: 1X14



Abbr.	Descriptions of used abbreviations
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United Kingdom (en) Page 19 / 19