acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid isobutyl ester ROTICHROM® GC

date of compilation: 2022-12-19 article number: 1YH4 Version: 1.0 en



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance Acetic acid isobutyl ester ROTICHROM® GC

Article number 1YH4

EC number 203-745-1 CAS number 110-19-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes

(household).

Details of the supplier of the safety data sheet 1.3

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

e-mail (competent person): sicherheit@carlroth.de

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

SECTION 2: Hazards identification

Classification of the substance or mixture 2.1

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

United Kingdom (en) Page 1 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid isobutyl ester ROTICHROM® GC

article number: 1YH4



Supplemental hazard information

Code	Supplemental hazard information
EUH066	repeated exposure may cause skin dryness or cracking

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS02, GHS07



Hazard statements

H225 Highly flammable liquid and vapour H336 May cause drowsiness or dizziness

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking

P261 Avoid breathing mist/vapours

Precautionary statements - response

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance Acetic acid isobutyl ester

Molecular formula $C_6H_{12}O_2$ Molar mass $116,2\,^g/_{mol}$ CAS No 110-19-0

EC No 203-745-1

United Kingdom (en) Page 2 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid isobutyl ester ROTICHROM® GC

article number: 1YH4



SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Dizziness, Drowsiness, Narcosis

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

United Kingdom (en) Page 3 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid isobutyl ester ROTICHROM® GC

article number: 1YH4



5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

United Kingdom (en) Page 4 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid isobutyl ester ROTICHROM® GC

article number: 1YH4



7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
EU	isobutyl acetate	110-19-0	IOELV	50	241	150	723				2019/ 1831/EU
GB	isobutyl acetate	110-19-0	WEL	150	724	187	903				EH40/ 2005

Notation

Ceiling-C

TWA

Ceiling value is a limit value above which exposure should not occur

STEL

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Human health values

Relevant DNELs and other threshold levels

Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	300 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	600 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
DNEL	300 mg/m³	human, inhalatory	worker (industry)	chronic - local effects
DNEL	600 mg/m³	human, inhalatory	worker (industry)	acute - local effects
DNEL	10 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic effects
DNEL	10 mg/kg bw/ day	human, dermal	worker (industry)	acute - systemic effects

United Kingdom (en) Page 5 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid isobutyl ester ROTICHROM® GC

article number: 1YH4



Environmental values

Relevant PNECs and other threshold levels

End- point	Threshold level	Organism	Environmental com- partment	Exposure time
PNEC	0,17 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0,017 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)
PNEC	200 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	0,877 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	0,088 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
PNEC	0,075 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

PE: polyethylene

material thickness

0.5 mm

breakthrough times of the glove material

>480 minutes (permeation: level 6)

Splash protection - Protective gloves

• type of material: NBR (Nitrile rubber)

• material thickness: 0,4 mm

• breakthrough times of the glove material: >30 minutes (permeation: level 2)

United Kingdom (en) Page 6 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid isobutyl ester ROTICHROM® GC

article number: 1YH4



Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour colourless

Odour fruity

Odour threshold 4,05 ppm

Melting point/freezing point -90 °C (ECHA)

Boiling point or initial boiling point and boiling

range

117 °C at 1.013 hPa (ECHA)

Flammability flammable liquid in accordance with GHS criteria

60 g/m³ (LEL) - 510 g/m³ (UEL) / 1,3 vol% (LEL) - 10,5 vol% (UEL) Lower and upper explosion limit

Flash point 22 °C at 1.013 hPa (ECHA)

430 °C at 1.019 hPa (ECHA) Auto-ignition temperature

Decomposition temperature not relevant

pH (value) 5 (in aqueous solution: 4 ^g/_l, 20 °C)

0,8025 mm²/_s at 20 °C Kinematic viscosity

0,699 mPa s at 20 °C Dynamic viscosity

Solubility(ies)

 $5,6 \, ^{9}/_{1} \, at \, 20 \, ^{\circ}C \, (ECHA)$ Water solubility

Partition coefficient

Partition coefficient n-octanol/water (log value): 2,3 (pH value: 7, 25 °C) (ECHA)

21 hPa at 20 °C Vapour pressure

United Kingdom (en) Page 7 / 16



acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid isobutyl ester ROTICHROM® GC

article number: 1YH4

Density and/or relative density

Density $0.871 \, \text{g/}_{\text{cm}^3}$ at 20 °C (ECHA)

Relative vapour density 4,01 at 20 °C (air = 1)

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

Other safety characteristics:

Surface tension $62,5^{\text{mN}}/_{\text{m}}$ (20 °C) (ECHA)

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

There is no additional information.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Bases

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Rubber articles, different plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

United Kingdom (en) Page 8 / 16



acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid isobutyl ester ROTICHROM® GC

article number: 1YH4



Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	13.413 ^{mg} / _{kg}	rat		ECHA
dermal	LD50	>17.400 ^{mg} / _{kg}	rabbit		ECHA

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

Data are not available.

• If in eyes

Data are not available.

• If inhaled

vertigo, dizziness, fatigue, narcosis

• If on skin

has degreasing effect on the skin, repeated exposure may cause skin dryness or cracking

Other information

none

11.2 Endocrine disrupting properties

Not listed.

11.3 Information on other hazards

There is no additional information.

United Kingdom (en) Page 9 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid isobutyl ester ROTICHROM® GC

article number: 1YH4



SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)

Endpoint	Value	Species	Source	Exposure time
LC50	16,6 ^{mg} / _l	fish	ECHA	96 h
EC50	24,6 ^{mg} / _l	aquatic invertebrates	ECHA	48 h
ErC50	397 ^{mg} / _l	algae	ECHA	72 h

Aquatic toxicity (chronic)

Endpoint	Value	Species	Source	Exposure time
EC50	34,2 ^{mg} / _l	aquatic invertebrates	ECHA	21 d
LC50	43,5 ^{mg} / _l	aquatic invertebrates	ECHA	21 d

12.2 Persistence and degradability

Biodegradation

The substance is readily biodegradable.

Process of degradability

Process	Degradation rate	Time
oxygen depletion	60 %	5 d

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	2,3 (pH value: 7, 25 °C) (ECHA)
---------------------------	---------------------------------

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Not listed.

12.7 Other adverse effects

Data are not available.

United Kingdom (en) Page 10 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid isobutyl ester ROTICHROM® GC

article number: 1YH4



SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Properties of waste which render it hazardous

HP3 flammable

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number or ID number

ADRRID	UN 1213
IMDG-Code	UN 1213
ICAO-TI	UN 1213

14.2 UN proper shipping name

ADRRID	ISOBUTYL ACETATE
IMDG-Code	ISOBUTYL ACETATE
ICAO-TI	Isobutyl acetate

14.3 Transport hazard class(es)

ADRRID	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

...

ADRRID	II
IMDG-Code	II
ICAO-TI	II

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

United Kingdom (en) Page 11 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid isobutyl ester ROTICHROM® GC

article number: 1YH4



Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)Additional information

Proper shipping name ISOBUTYL ACETATE

Particulars in the transport document UN1213, ISOBUTYL ACETATE, 3, II, (D/E)

Classification code F

Danger label(s) 3



Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
Transport category (TC) 2
Tunnel restriction code (TRC) D/E
Hazard identification No 33
Emergency Action Code 3YE

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional

information

Classification code F1

Danger label(s) 3



Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
Transport category (TC) 2
Hazard identification No 33

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name ISOBUTYL ACETATE

Particulars in the shipper's declaration UN1213, ISOBUTYL ACETATE, 3, II, 22°C c.c.

Marine pollutant Danger label(s) 3



Special provisions (SP)

United Kingdom (en) Page 12 / 16



acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid isobutyl ester ROTICHROM® GC

article number: 1YH4

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

EmS F-E, S-D

Stowage category B

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Isobutyl acetate

Particulars in the shipper's declaration UN1213, Isobutyl acetate, 3, II

Danger label(s) 3



Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	
P5c	flammable liquids (cat. 2, 3)	5.000 50.000	51)

Notation

Deco-Paint Directive

VOC c	ontent	100 % 871 ^g / _l

Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	871 ^g / _l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Water Framework Directive (WFD)

not listed

United Kingdom (en) Page 13 / 16



⁵¹⁾ Flammable liquids, categories 2 or 3 not covered by P5a and P5b

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid isobutyl ester ROTICHROM® GC

article number: 1YH4



Regulation on the marketing and use of explosives precursors

not listed

Regulation on drug precursors

not listed

Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list

not listed

Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)

Name of substance	Name acc. to inventory	CAS No	No
Acetic acid isobutyl ester	this product meets the criteria for classi- fication in accordance with Regulation No 1272/2008/EC		3
Acetic acid isobutyl ester	flammable / pyrophoric		40

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
JP	ISHA-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed

United Kingdom (en) Page 14 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid isobutyl ester ROTICHROM® GC

article number: 1YH4



Country	Inventory	Status
US	TSCA	substance is listed as "ACTIVE"

Legend

AIIC
CICR
CSCL-ENCS
DSL
ECSI
IECSC
INSQ
ISHA-ENCS Australian Inventory of Industrial Chemicals Chemical Inventory and Control Regulation List of Existing and New Chemical Substances (CSCL-ENCS)

List of Existing and New Chemical Substances (CSCL-ENCS)
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances
Inventory of Existing and New Chemical Substances (ISHA-ENCS)
Korea Existing Chemicals Inventory
New Zealand Inventory of Chemicals
Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH registered substances

KECI NZIoC PICCS

REACH Reg. REACH registered substances

Taiwan Chemical Substance Inventory Toxic Substance Control Act

TCSI TSCA

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2019/1831/EU	Commission Directive establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization

United Kingdom (en) Page 15 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid isobutyl ester ROTICHROM® GC

article number: 1YH4



Abbr.	Descriptions of used abbreviations
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United Kingdom (en) Page 16 / 16