acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: **1YXT** Version: **1.0 en**

date of compilation: 2023-02-28

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Identification of the substance

Article number

1YXT

isooctane, 10 µg/ml

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Uses advised against:

Laboratory and analytical use Laboratory chemical

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

PCBs Standard Solution ROTI®Star 7 PCBs in

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment sheet:

e-mail (competent person):

sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
3.9	Specific target organ toxicity - repeated exposure		STOT RE 2	H373
3.10	Aspiration hazard	1	Asp. Tox. 1	H304

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCBs Standard Solution ROTI $\ensuremath{\mathbb{R}}$ Star 7 PCBs in isooctane, 10 $\ensuremath{\mu g}\xspace$ ml



article number: **1YXT**

Section	Hazard class		Hazard class and category	Hazard statement
4.1A	Hazardous to the aquatic environment - acute hazard	1	Aquatic Acute 1	H400
4.1C	Hazardous to the aquatic environment - chronic hazard	1	Aquatic Chronic 1	H410

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling

Signal word Danger

Pictograms



Hazard statements

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure
H410	Very toxic to aquatic life with long lasting effects

Precautionary statements

Precautionary statements - prevention

P280 Wear protective gloves/protective clothing/eye protection/face protection

Hazardous ingredients for labelling:

Isooctane, Polychlorobiphenyls (PCB)

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\ge 0,1\%$.

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml



article number: **1YXT**

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Isooctane	CAS No 540-84-1 EC No 208-759-1 Index No 601-009-00-8	99 - < 100	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410		C(a) GHS-HC
Polychlorobiphenyls (PCB)	CAS No 1336-36-3 EC No 215-648-1 Index No 602-039-00-4	< 0,01	STOT RE 2 / H373 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410		C GHS-HC

Notes

C(a): Mixture of isomers

C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers. GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC, Annex VI)

Name of sub- stance	Identifier	Specific Conc. Limits	M-Factors	ATE	Exposure route
Polychlorobi- phenyls (PCB)	CAS No 1336-36-3	STOT RE 2; H373: C ≥ 0,005 %	-	-	
	EC No 215-648-1				

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: **1YXT**

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Rinse mouth. Do not induce vomiting. Observe aspiration hazard if vomiting occurs. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Following inhalation: Drowsiness, Dizziness, Narcosis, Following skin contact: Irritation, After eye contact: Irritant effects, Following ingestion: Aspiration hazard

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapourair mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO $_2$), May produce toxic fumes of carbon monoxide if burning.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml



article number: **1YXT**

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Measures to protect the environment

Avoid release to the environment.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: 1YXT

7.2 Conditions for safe storage, including any incompatibilities Keep in a cool place.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 2 - 8 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
GB	polychlorinated bi- phenyls (PCB)	1336-36- 3	WEL		0,1						EH40/ 2005

Notation

Ceiling-C STEL

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8

TWA hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture								
Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time		
Isooctane	540-84-1	DNEL	2.035 mg/ m ³	human, inhalat- ory	worker (industry)	chronic - systemic effects		
Isooctane	540-84-1	DNEL	773 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects		

8.2 **Exposure controls**

Individual protection measures (personal protective equipment)

Eye/face protection





acc. to Regulation (EC) No. 1907/2006 (REACH)

PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: 1YXT

Use safety goggle with side protection.

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

NBR (Nitrile rubber)

material thickness

>0,3 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	like: - Gasoline
Melting point/freezing point	-107 °C
Boiling point or initial boiling point and boiling range	99,2 °C at 1.013 hPa
Flammability	flammable liquid in accordance with GHS criteria



acc. to Regulation (EC) No. 1907/2006 (REACH)

PCBs Standard Solution ROTI $\ensuremath{\mathbb{R}}$ Star 7 PCBs in isooctane, 10 $\ensuremath{\mu g}\xspace$ ml

article number: 1YXT

Lower and upper explosion limit	45 g/m³ (LEL) - 290 g/m³ (UEL) / 1 vol% (LEL) - 6 vol% (UEL)
Flash point	-12 °C
Auto-ignition temperature	418 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not determined
Dynamic viscosity	0,5 mPa s at 20 °C
Solubility(ies)	
Water solubility	(poorly soluble (1 till < 10 mg/l))
Partition coefficient	
Partition coefficient n-octanol/water (log value):	this information is not available
Vapour pressure	28 hPa at 20 °C
Density and/or relative density	
Density	0,69 ^g / _{cm³} at 15 °C
Relative vapour density	3,9 (air = 1)
Particle characteristics	not relevant (liquid)
Other safety parameters	
Oxidising properties	none
Other information	
Information with regard to physical hazard classes:	There is no additional information.
Other safety characteristics:	
Maximum explosion pressure	9 bar

SECTION 10: Stability and reactivity

10.1 Reactivity

9.2

The mixture contains reactive substance(s). Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.



acc. to Regulation (EC) No. 1907/2006 (REACH)

PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 μ g/ml

article number: **1YXT**

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- **10.5 Incompatible materials** different plastics
- **10.6** Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful in contact with skin or if inhaled.

cute toxicity of components of the mixture									
Name of substance	CAS No	Exposure route	Endpoint	Value	Species				
Isooctane	540-84-1	oral	LD50	>5.000 ^{mg} / _{kg}	rat				
Isooctane	540-84-1	inhalation: va- pour	LC50	>33,52 ^{mg} / _l / 4h	rat				
Isooctane	540-84-1	dermal	LD50	>2.000 ^{mg} / _{kg}	rabbit				

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.



acc. to Regulation (EC) No. 1907/2006 (REACH)

PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: 1YXT

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

vomiting, aspiration hazard

• If in eyes

causes slight to moderate irritation

If inhaled

drowsiness, dizziness, fatigue, narcosis

• If on skin

causes skin irritation

Other information

none

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\ge 0,1\%$.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

quatic toxicity (acute) of components of the mixture									
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time				
Isooctane	540-84-1	LL50	18,4 ^{mg} / _l	fish	96 h				
Isooctane	540-84-1	LC50	0,11 ^{mg} / _l	fish	96 h				
Isooctane	540-84-1	EC50	0,4 ^{mg} / _l	aquatic invertebrates	48 h				
Isooctane	540-84-1	EL50	2,4 ^{mg} / _l	aquatic invertebrates	48 h				

Aquatic toxicity (chronic) of components of the mixture

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Isooctane	540-84-1	EL50	1,6 ^{mg} / _l	aquatic invertebrates	21 d
Isooctane	540-84-1	EC50	0,23 ^{mg} /l	aquatic invertebrates	21 d

Page 10 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: **1YXT**

12.2	Persistence a	Persistence and degradability						
	Degradabilit	y of compone	nts of the mix	ture				
	Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source	
	Isooctane	540-84-1	oxygen deple- tion	61,81 %	70 d		ECHA	

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potentia	Bioaccumulative potential of components of the mixture				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD	
Isooctane	540-84-1	231	4,08		

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment Data are not available.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\ge 0,1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Properties of waste which render it hazardous

- **HP 3** flammable
- HP 5 specific target organ toxicity (STOT)/aspiration toxicity
- HP 14 ecotoxic

acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: **1YXT**

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1	UN number or ID number	
	ADRRID	UN 1262
	IMDG-Code	UN 1262
	ICAO-TI	UN 1262
14.2	UN proper shipping name	
	ADRRID	OCTANES
	IMDG-Code	OCTANES
	ICAO-TI	Octanes
14.3	Transport hazard class(es)	
	ADRRID	3
	IMDG-Code	3
	ICAO-TI	3
14.4	Packing group	
	ADRRID	II
	IMDG-Code	II
	ICAO-TI	II
14.5	Environmental hazards	hazardous to the aquatic environment
	Environmentally hazardous substance (aquatic environment):	Isooctane

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)Additional information

Proper shipping name	OCTANES
Particulars in the transport document	UN1262, OCTANES, 3, II, (D/E), environmentally hazardous
Classification code	F1
Danger label(s)	3, "Fish and tree"

Safety data sheet Safety data sheet acc. to Regulation (EC) No. 1907/2006 (REACH)

PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml



Environmental hazards	Yes (hazardous to the aquatic environment)
Excepted quantities (EQ)	E2
Limited quantities (LQ)	 1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D/E
Hazard identification No	33
Emergency Action Code	3YE
	Carriage of Dangerous Goods by Rail (RID)Addition
Classification code	F1
Danger label(s)	3 Fish and tree
Environmental hazards	Yes Hazardous to water
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
Transport category (TC)	2
Hazard identification No	33
International Maritime Dangerous Goods (Code (IMDG) - Additional information
Proper shipping name	OCTANES
Particulars in the shipper's declaration	UN1262, OCTANES, 3, II, -12°C c.c., MARINE PC LUTANT
Marine pollutant	yes (P) (hazardous to the aquatic environment)
Danger label(s)	3, "Fish and tree"
Special provisions (SP)	-
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-E, S-E
Stowage category	В
International Civil Aviation Organization (I	ICAO-IATA/DGR) - Additional information
Proper shipping name	Octanes
Particulars in the shipper's declaration	UN1262, Octanes, 3, II
Environmental hazards	Yes (hazardous to the aquatic environment)
Danger label(s)	3

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml



article number: **1YXT**

Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Seveso Directive

2012/	18/EU (Seveso III)			
Νο	Dangerous substance/hazard categories	plication of lower	(tonnes) for the ap- and upper-tier re- ments	Notes
E1	environmental hazards (hazardous to the aquatic en- vironment, cat. 1)	100	200	56)

Notation

56) Hazardous to the Aquatic Environment in category Acute 1 or Chronic 1

Deco-Paint Directive

VOC content	99,99 % 690 ^g / _l

Industrial Emissions Directive (IED)

VOC content	99,99 %
VOC content	690 ^g /l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

Pollutant release and transfer registers (PRTR)			
Name of substance	CAS No	Remarks	Threshold for releases to air (kg/year)
Polychlorobiphenyls (PCB)	1336-36-3		0,1

Water Framework Directive (WFD)

acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: **1YXT**

List of pollutants (WFD)

Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Polychlorobiphenyls (PCB)	Organohalogen compounds and substances which may form such compounds in the aquatic envir- onment		a)	
Polychlorobiphenyls (PCB)	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)	
Polychlorobiphenyls (PCB)	Persistent hydrocarbons and per- sistent and bioaccumulable or- ganic toxic substances		a)	

Legend

A) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

none of the ingredients are listed

Regulation on drug precursors

none of the ingredients are listed

Regulation on substances that deplete the ozone layer (ODS)

none of the ingredients are listed

Regulation concerning the export and import of hazardous chemicals (PIC)

chemicals subject to the international prior informed consent (PIC) procedure (the 'PIC procedure').

Name of substance	Name acc. to inventory	CAS No	Wt%	Category / subcat- egory	Use limita- tion
Polychlorobiphenyls (PCB)	polychlorinated biphenyls (PCB)	1336-36- 3	0,007	i	
Polychlorobiphenyls (PCB)	polychlorinated biphenyls (PCB)	1336-36- 3	0,007		

Legend

Category: i - industrial chemical

Regulation on persistent organic pollutants (POP)

Name of substance	CAS No	Wt%	Type of registra- tion	Re- marks	Exemp- tions	Concen- tration limit
Polychlorobiphenyls (PCB)	1336-36-3	0,007	Annex I - A		A1-ex-08	
Polychlorobiphenyls (PCB)	1336-36-3	0,007	Annex III - A			
Polychlorobiphenyls (PCB)	1336-36-3	0,007	Annex IV			50 mg/kg

Legend

Member States shall identify and remove from use equipment (e.g. transformers, capacitors or other receptacles containing liquid stocks) containing more than 0,005 % PCBs and volumes greater than 0,05 dm3, as soon as possible but no later than 31 December 2025.

A1-ex-08 Without prejudice to Directive 96/59/EC, articles already in use at the time of the entry into force of this Regulation are allowed to be used.

acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: **1YXT**

Legend

annex I - A Part A - Substances listed in the Convention and in the Protocol as well as substances listed only in the Convention annex III - A List of substances subject to release reduction provisions annex IV List of substances subject to waste management provisions set out in Article 7

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list

none of the ingredients are listed

Restrictions according to GB REACH, Annex 17

angerous substances with restrictions (GB REACH, Annex 17)			
Name of substance	Name acc. to inventory	CAS No	Νο
PCBs Standard Solution	this product meets the criteria for classi- fication in accordance with Regulation No 1272/2008/EC		3
Isooctane	flammable / pyrophoric		40

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed as "ACTIVE"

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 μ g/ml

article number: **1YXT**

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations		
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concern- ing the International Carriage of Dangerous Goods by Road)		
Aquatic Acute	Hazardous to the aquatic environment - acute hazard		
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard		
Asp. Tox.	Aspiration hazard		
ATE	Acute Toxicity Estimate		
BCF	Bioconcentration factor		
BOD	Biochemical Oxygen Demand		
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)		
Ceiling-C	Ceiling value		
COD	Chemical oxygen demand		
DGR	Dangerous Goods Regulations (see IATA/DGR)		
DNEL	Derived No-Effect Level		
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval		
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identi fier of substances commercially available within the EU (European Union)		
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)		
EINECS	European Inventory of Existing Commercial Chemical Substances		
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms		
ELINCS	European List of Notified Chemical Substances		
EmS	Emergency Schedule		
Flam. Liq.	Flammable liquid		
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)		
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions		
IATA	International Air Transport Association		
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)		
ICAO	International Civil Aviation Organization		
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air		
IMDG	International Maritime Dangerous Goods Code		
IMDG-Code	International Maritime Dangerous Goods Code		



acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI $\ensuremath{\mathbb{R}}$ Star 7 PCBs in isooctane, 10 µg/ml

article number: **1YXT**

Abbr.	Descriptions of used abbreviations
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCBs Standard Solution ROTI $\ensuremath{\mathbb{R}}$ Star 7 PCBs in isooctane, 10 $\ensuremath{\mu g}\xspace/ml$

® Roth

article number: **1YXT**

Code	Text
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.