acc. to Regulation (EC) No. 1907/2006 (REACH)

#### n-Hexane ROTISOLV® ≥96 %, UV/IR-Grade

article number: **216L** date of compilation: 2023-04-05 Version: **1.0 en** 

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Identification of the substance n-Hexane ROTISOLV® ≥96 %, UV/IR-Grade

Article number 216L

 Index No (GB CLP)
 601-037-00-0

 EC number
 203-777-6

 CAS number
 110-54-3

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes (household). Food, drink and animal feeding-

stuffs.

#### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

**Telephone:**+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

e-mail (competent person): sicherheit@carlroth.de

#### 1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification acc. to GHS

United Kingdom (en) Page 1 / 17



acc. to Regulation (EC) No. 1907/2006 (REACH)

#### n-Hexane ROTISOLV® ≥96 %, UV/IR-Grade

article number: 216L



Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.2	.2 Skin corrosion/irritation		Skin Irrit. 2	H315
3.7	Reproductive toxicity	2	Repr. 2	H361f
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
3.9	Specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
3.10	Aspiration hazard	1	Asp. Tox. 1	H304
4.1C	Hazardous to the aquatic environment - chronic hazard	2	Aquatic Chronic 2	H411

For full text of abbreviations: see SECTION 16

#### The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

#### 2.2 Label elements

#### Labelling

Signal word Danger

#### **Pictograms**

GHS02, GHS07, GHS08, GHS09









## **Hazard statements**

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361f	Suspected of damaging fertility
H373	May cause damage to organs (nervous system) through prolonged or repeated
	exposure (if inhaled)
H411	Toxic to aquatic life with long lasting effects

## **Precautionary statements**

#### **Precautionary statements - prevention**

P202 Do not handle until all safety precautions have been read and understood

P280 Wear protective gloves/eye protection

#### **Precautionary statements - response**

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower]

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing

P308+P313 IF exposed or concerned: Get medical advice/attention

United Kingdom (en) Page 2 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### n-Hexane ROTISOLV® ≥96 %, UV/IR-Grade

article number: 216L



For professional users only

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

## **Endocrine disrupting properties**

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq$  0,1%.

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Name of substance n-Hexane Molecular formula  $C_6H_{14}$  Molar mass  $86,18~^g/_{mol}$  CAS No 110-54-3 EC No 203-777-6 Index No (GB CLP) 601-037-00-0

#### Substance, Specific Conc. Limits, M-factors, ATE

Specific Conc. Limits	M-Factors	ATE	Exposure route
STOT RE 2; H373: C ≥ 5 %	-	-	

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures



#### **General notes**

Take off contaminated clothing.

#### **Following inhalation**

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

#### Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following ingestion

Call a physician immediately. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Observe aspiration hazard if vomiting occurs.

United Kingdom (en) Page 3 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### n-Hexane ROTISOLV® ≥96 %, UV/IR-Grade

article number: 216L



#### 4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard, Irritation, Dizziness, Drowsiness, Narcosis

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media



#### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

water jet

#### 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

#### **Hazardous combustion products**

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

## **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

## **6.2** Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. Danger of explosion.

#### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

United Kingdom (en) Page 4 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### n-Hexane ROTISOLV® ≥96 %, UV/IR-Grade

article number: 216L



#### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

#### Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

#### Measures to protect the environment

Avoid release to the environment.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed.

#### **Incompatible substances or mixtures**

Observe hints for combined storage.

#### Consideration of other advice:

Ground/bond container and receiving equipment.

#### **Ventilation requirements**

Use local and general ventilation.

#### Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

#### 7.3 Specific end use(s)

No information available.

United Kingdom (en) Page 5 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### n-Hexane ROTISOLV® ≥96 %, UV/IR-Grade

article number: 216L



## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **National limit values**

#### **Occupational exposure limit values (Workplace Exposure Limits)**

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
EU	n-hexane	110-54-3	IOELV	20	72						2006/15/ EC
GB	n-hexane	110-54-3	WEL	20	72						EH40/ 2005

Notation

Ceiling-C

Ceiling value is a limit value above which exposure should not occur

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-

minute period (unless otherwise specified)
TWA Time-weighted average (long-term exposur

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8

hours time-weighted average (unless otherwise specified)

#### **Human health values**

#### Relevant DNELs and other threshold levels

Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	75 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	11 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic effects

#### 8.2 Exposure controls

#### Individual protection measures (personal protective equipment)

## **Eye/face protection**





Use safety goggle with side protection.

#### Skin protection



#### hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply

United Kingdom (en) Page 6 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### n-Hexane ROTISOLV® ≥96 %, UV/IR-Grade

article number: 216L



only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

#### type of material

NBR (Nitrile rubber)

#### material thickness

≥0,4 mm

#### · breakthrough times of the glove material

>480 minutes (permeation: level 6)

#### other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

#### **Respiratory protection**





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

#### **Environmental exposure controls**

Keep away from drains, surface and ground water.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state liquid

Colour colourless

Odour like: - Gasoline

Melting point/freezing point -95 °C at 1.013 hPa (ECHA)

Boiling point or initial boiling point and boiling 68 – 69 °C at 1.013 hPa

range

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 1,1 vol% (LEL) - 7,5 vol% (UEL)

Flash point -22 °C at 1.013 hPa (ECHA)

Auto-ignition temperature 225 °C (ECHA)

Decomposition temperature not relevant

pH (value) not determined Kinematic viscosity  $0.5 \, ^{\text{mm}^2}/_{\text{s}}$  at 20 °C

Dynamic viscosity 0,33 mPa s at 20 °C

Solubility(ies)

Water solubility <0,1  $^{g}/_{l}$  at 20  $^{\circ}$ C

United Kingdom (en) Page 7 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### n-Hexane ROTISOLV® ≥96 %, UV/IR-Grade

article number: 216L

ROTH

Partition coefficient

Partition coefficient n-octanol/water (log value): 4 (pH value: 7, 20 °C) (ECHA)

Soil organic carbon/water (log KOC) 3,34 (ECHA)

Vapour pressure 160 hPa at 20 °C

Density and/or relative density

Density  $0.66 \, ^{9}/_{cm^3}$  at 20  $^{\circ}$ C

Relative vapour density 2,79 (air = 1)

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

Other safety characteristics: There is no additional information.

## **SECTION** 10: Stability and reactivity

#### 10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air.

#### If heated

Risk of ignition.

#### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

There is no additional information.

#### 10.3 Possibility of hazardous reactions

**Violent reaction with:** strong oxidiser, Chlorine, Iodine, Peroxides, Nitrogen oxides (NOx), => Explosive properties

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### 10.5 Incompatible materials

Rubber articles, different plastics

## 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

United Kingdom (en) Page 8 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### n-Hexane ROTISOLV® ≥96 %, UV/IR-Grade

article number: 216L



## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### Classification acc. to GHS

#### **Acute toxicity**

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful in contact with skin.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
inhalation: vapour	LC50	185 <sup>mg</sup> / <sub>l</sub> /4h	rat		TOXNET
oral	LD50	25.000 <sup>mg</sup> / <sub>kg</sub>	rat		TOXNET
dermal	LD50	>2.000 <sup>mg</sup> / <sub>kg</sub>	rabbit		ECHA

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

#### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

#### **Germ cell mutagenicity**

Shall not be classified as germ cell mutagenic.

#### Carcinogenicity

Shall not be classified as carcinogenic.

#### Reproductive toxicity

Suspected of damaging fertility.

#### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

## Specific target organ toxicity - repeated exposure

May cause damage to organs (nervous system) through prolonged or repeated exposure (if inhaled).

Hazard category	Target organ	Exposure route
2	nervous system	if inhaled

#### **Aspiration hazard**

May be fatal if swallowed and enters airways.

#### Symptoms related to the physical, chemical and toxicological characteristics

#### • If swallowed

nausea, vomiting, aspiration hazard

#### • If in eyes

slightly irritant but not relevant for classification

United Kingdom (en) Page 9 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### n-Hexane ROTISOLV® ≥96 %, UV/IR-Grade

article number: 216L



irritant effects, headache, vertigo, fatigue, dizziness, narcosis

• If on skin

causes skin irritation

Other information

none

#### 11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq$  0,1%.

#### 11.3 Information on other hazards

There is no additional information.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (ac	Aquatic toxicity (acute)						
Endpoint	Value	Species	Source	Exposure time			
LL50	12,51 <sup>mg</sup> / <sub>l</sub>	fish	ECHA	96 h			
EL50	21,85 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	ECHA	48 h			

## 12.2 Persistence and degradability

#### **Biodegradation**

The substance is readily biodegradable.

Process of degradability					
Process	Degradation rate	Time			
oxygen depletion	83 %	10 d			

#### 12.3 Bioaccumulative potential

The substance fulfils the very bioaccumulative criterion.

n-octanol/water (log KOW)	4 (pH value: 7, 20 °C) (ECHA)
BCF	501,2 (ECHA)

#### 12.4 Mobility in soil

The Organic Carbon normalised adsorption coefficient 3,34	34 (ECHA)
---	-----------

#### 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq$  0,1%.

United Kingdom (en) Page 10 / 17



acc. to Regulation (EC) No. 1907/2006 (REACH)

#### n-Hexane ROTISOLV® ≥96 %, UV/IR-Grade

article number: 216L

#### 12.7 Other adverse effects

Data are not available.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### **Sewage disposal-relevant information**

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

#### 13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

#### Properties of waste which render it hazardous

**HP3** flammable

**HP 4** irritant - skin irritation and eye damage

**HP 5** specific target organ toxicity (STOT)/aspiration toxicity

**HP 10** toxic for reproduction

HP 14 ecotoxic

#### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

## **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADRRID	UN 1208
IMDG-Code	UN 1208
ICAO-TI	UN 1208

## 14.2 UN proper shipping name

ADRRID	HEXANES
IMDG-Code	HEXANES
ICAO-TI	Hexanes

#### 14.3 Transport hazard class(es)

ADRRID	3
IMDG-Code	3

United Kingdom (en) Page 11 / 17



acc. to Regulation (EC) No. 1907/2006 (REACH)

#### n-Hexane ROTISOLV® ≥96 %, UV/IR-Grade

article number: 216L

ICAO-TI 3

14.4 Packing group

ADRRID II
IMDG-Code II
ICAO-TI II

**14.5 Environmental hazards** hazardous to the aquatic environment

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

#### 14.8 Information for each of the UN Model Regulations

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)Additional information

Proper shipping name HEXANES

Particulars in the transport document UN1208, HEXANES, 3, II, (D/E), environmentally

hazardous

Classification code F1

Danger label(s) 3, "Fish and tree"

**№ №** 

Environmental hazards yes (hazardous to the aquatic environment)

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
Transport category (TC) 2
Tunnel restriction code (TRC) D/E
Hazard identification No 33
Emergency Action Code 3YE

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional information

F1

Classification code

Danger label(s) 3

Fish and tree



Environmental hazards Yes

Hazardous to water

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

United Kingdom (en) Page 12 / 17



acc. to Regulation (EC) No. 1907/2006 (REACH)

#### n-Hexane ROTISOLV® ≥96 %, UV/IR-Grade

article number: 216L

Transport category (TC) 2
Hazard identification No 33

#### International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name HEXANES

Particulars in the shipper's declaration UN1208, HEXANES, 3, II, -22°C c.c., MARINE POL-

**LUTANT** 

Marine pollutant yes (P) (hazardous to the aquatic environment)

Danger label(s) 3, "Fish and tree"





Special provisions (SP)

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

EmS F-E, S-D

Stowage category E

## International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Hexanes

Particulars in the shipper's declaration UN1208, Hexanes, 3, II

Environmental hazards yes (hazardous to the aquatic environment)

Danger label(s) 3



Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

## **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

#### **Seveso Directive**

2012/	2012/18/EU (Seveso III)		
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	
E2	environmental hazards (hazardous to the aquatic environment, cat. 2)	200 500	57)

#### Notation

57) Hazardous to the Aquatic Environment in category Chronic 2

United Kingdom (en) Page 13 / 17



acc. to Regulation (EC) No. 1907/2006 (REACH)

#### n-Hexane ROTISOLV® ≥96 %, UV/IR-Grade

article number: 216L



#### **Deco-Paint Directive**

VOC content	100 %
VOC content	660 <sup>g</sup> / <sub>l</sub>

#### **Industrial Emissions Directive (IED)**

VOC content	100 %
VOC content	660 <sup>g</sup> / <sub>l</sub>

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

#### Water Framework Directive (WFD)

#### List of pollutants (WFD)

Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
n-Hexane	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)	

#### Legend

A) Indicative list of the main pollutants

## Regulation on the marketing and use of explosives precursors

not listed

## **Regulation on drug precursors**

not listed

Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list

not listed

United Kingdom (en) Page 14 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### n-Hexane ROTISOLV® ≥96 %, UV/IR-Grade

article number: 216L



#### Restrictions according to GB REACH, Annex 17

Name of substance	Name acc. to inventory	CAS No	No
n-Hexane	this product meets the criteria for classi- fication in accordance with Regulation No 1272/2008/EC		3
n-Hexane	flammable / pyrophoric		40

#### Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

#### **National inventories**

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
JP	ISHA-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed as "ACTIVE"

Legend

Australian Inventory of Industrial Chemicals Chemical Inventory and Control Regulation List of Existing and New Chemical Substances (CSCL-ENCS) AIIC CICR

CSCL-ENCS DSL ECSI IECSC INSQ CSCL-ENCS
DSL
Domestic Substances List (DSL)
ECSI
ECSI
Inventory of Existing Chemical Substances Produced or Imported in China
INSQ
INSQ
ISHA-ENCS
INVENTORY OF Existing and New Chemical Substances (ISHA-ENCS)
KECI
NZIOC
NECS
PICCS
PICCS
REACH Reg.
REACH registered substances
Toxic Substances
Toxic Substances
Provinces
Provin

TCSI TSCA Toxic Substance Control Act

#### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

United Kingdom (en) Page 15 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

## n-Hexane ROTISOLV® ≥96 %, UV/IR-Grade

article number: 216L



## **SECTION 16: Other information**

## **Abbreviations and acronyms**

Abbr.	Descriptions of used abbreviations
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
GB CLP	The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended)
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)

United Kingdom (en) Page 16 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### n-Hexane ROTISOLV® ≥96 %, UV/IR-Grade

article number: 216L



Abbr.	Descriptions of used abbreviations
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

#### Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

#### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs (nervous system) through prolonged or repeated exposure (if inhaled).
H411	Toxic to aquatic life with long lasting effects.

#### **Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United Kingdom (en) Page 17 / 17