

# Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Epoxy systems Araldit® G 2 cast resin

article number: **2545**  
Version: **3.0 en**  
Replaces version of: 2020-12-11  
Version: (2)

date of compilation: 2017-02-07  
Revision: 2022-05-04

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Identification of the substance **Epoxy systems Araldit® G 2 cast resin**  
Article number 2545  
Alternative name(s) epoxy resin, liquid

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical  
Laboratory and analytical use  
Adhesive  
Uses advised against: Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG  
Schoemperlenstr. 3-5  
D-76185 Karlsruhe  
Germany

**Telephone:**+49 (0) 721 - 56 06 0  
**Telefax:** +49 (0) 721 - 56 06 149  
**e-mail:** sicherheit@carlroth.de  
**Website:** www.carlroth.de

Competent person responsible for the safety data sheet: :Department Health, Safety and Environment

**e-mail (competent person):** **sicherheit@carlroth.de**

### 1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.4S	Skin sensitisation	1	Skin Sens. 1	H317
4.1C	Hazardous to the aquatic environment - chronic hazard	2	Aquatic Chronic 2	H411

# Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Epoxy systems Araldit® G 2 cast resin

article number: 2545

### Supplemental hazard information

Code	Supplemental hazard information
EUH205	contains epoxy constituents. May produce an allergic reaction

For full text of abbreviations: see SECTION 16

### The most important adverse physicochemical, human health and environmental effects

Spillage and fire water can cause pollution of watercourses.

## 2.2 Label elements

### Labelling

#### Signal word

Warning

#### Pictograms

GHS07, GHS09



#### Hazard statements

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H411	Toxic to aquatic life with long lasting effects

#### Precautionary statements

##### Precautionary statements - prevention

P273	Avoid release to the environment
P280	Wear protective gloves/eye protection

##### Precautionary statements - response

P302+P352	IF ON SKIN: Wash with plenty of soap and water
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312	Call a POISON CENTRE/doctor if you feel unwell

#### Supplemental hazard information

EUH205 Contains epoxy constituents. May produce an allergic reaction.

#### Hazardous ingredients for labelling:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxy-methylene)]bisoxirane

## 2.3 Other hazards

### Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

# Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Epoxy systems Araldit® G 2 cast resin

article number: 2545

### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

not relevant (mixture)

#### 3.2 Mixtures

##### Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	CAS No 1675-54-3  EC No 216-823-5	≥ 60	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Skin Sens. 1 / H317 Aquatic Chronic 2 / H411		GHS-HC

##### Notes

GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC, Annex VI)

Name of substance	Identifier	Specific Conc. Limits	M-Factors	ATE	Exposure route
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	CAS No 1675-54-3  EC No 216-823-5	Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	-	-	

For full text of abbreviations: see SECTION 16

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures



##### General notes

Take off contaminated clothing.

##### Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

##### Following skin contact

Rinse skin with water/shower. After contact with skin, wash immediately with plenty of water. In case of skin reactions, consult a physician. In case of skin irritation, consult a physician.

##### Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

##### Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

#### 4.2 Most important symptoms and effects, both acute and delayed

Irritation, Allergic reactions

# Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Epoxy systems Araldit® G 2 cast resin

article number: 2545

### 4.3 Indication of any immediate medical attention and special treatment needed

none

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media



#### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings  
water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

water jet

### 5.2 Special hazards arising from the substance or mixture

Combustible.

#### Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), May produce toxic fumes of carbon monoxide if burning.

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

# Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Epoxy systems Araldit® G 2 cast resin

article number: 2545

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Provision of sufficient ventilation.

#### Measures to protect the environment

Avoid release to the environment.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

#### Incompatible substances or mixtures

Observe hints for combined storage.

#### Consideration of other advice:

#### Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

### 7.3 Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### National limit values

#### Occupational exposure limit values (Workplace Exposure Limits)

This information is not available.

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxy-methylene)]bisoxirane	1675-54-3	DNEL	4,93 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxy-methylene)]bisoxirane	1675-54-3	DNEL	0,75 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

# Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Epoxy systems Araldit® G 2 cast resin

article number: 2545

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	PNEC	0,006 mg/l	aquatic organisms	freshwater	short-term (single instance)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	PNEC	0,001 mg/l	aquatic organisms	marine water	short-term (single instance)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	PNEC	0,341 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	PNEC	0,034 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	PNEC	0,065 mg/kg	terrestrial organisms	soil	short-term (single instance)

## 8.2 Exposure controls

### Individual protection measures (personal protective equipment)

#### Eye/face protection



Use safety goggle with side protection.

#### Skin protection



#### • hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 °C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply

# Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Epoxy systems Araldit® G 2 cast resin

article number: 2545

only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

- **type of material**

Butyl caoutchouc (butyl rubber)

- **material thickness**

≥0,5 mm


- **breakthrough times of the glove material**

>480 minutes (permeation: level 6)

- **other protection measures**

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

### Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

### Environmental exposure controls

Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	clear - light yellow
Odour	faintly perceptible
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	>200 °C
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	not determined
Flash point	160 °C (c.c.)
Auto-ignition temperature	not determined
Decomposition temperature	>200 °C
pH (value)	7 (20 °C)
Kinematic viscosity	1.500 mm <sup>2</sup> /s at 25 °C
Dynamic viscosity	1.300 – 1.800 mPa s at 25 °C
<u>Solubility(ies)</u>	
Water solubility	(practically insoluble)

# Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Epoxy systems Araldit® G 2 cast resin

article number: 2545

### Partition coefficient

Partition coefficient n-octanol/water (log value): this information is not available

Vapour pressure <0,0001 hPa at 25 °C

### Density and/or relative density

Density 1,1 – 1,2 g/cm<sup>3</sup> at 25 °C

Relative vapour density information on this property is not available

Particle characteristics not relevant (liquid)

### Other safety parameters

Oxidising properties none

## 9.2 Other information

Information with regard to physical hazard classes: hazard classes acc. to GHS (physical hazards): not relevant

Other safety characteristics: There is no additional information.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is not reactive under normal ambient conditions.

#### **If heated**

Vapours may form explosive mixtures with air.

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### 10.3 Possibility of hazardous reactions

**Violent reaction with:** strong oxidiser

### 10.4 Conditions to avoid

Keep away from heat. Decomposition takes place from temperatures above: >200 °C.

### 10.5 Incompatible materials

Strong alkali, Strong acid

### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.



# Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Epoxy systems Araldit® G 2 cast resin

article number: 2545

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

##### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

##### Classification acc. to GHS

##### Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity of components of the mixture					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
2,2'-[[1-methylethylidene]bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	oral	LD50	>2.000 mg/kg	rat
2,2'-[[1-methylethylidene]bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	dermal	LD50	>2.000 mg/kg	rat

##### Skin corrosion/irritation

Causes skin irritation.

##### Serious eye damage/eye irritation

Causes serious eye irritation.

##### Respiratory or skin sensitisation

May cause an allergic skin reaction.

##### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

##### Carcinogenicity

Shall not be classified as carcinogenic.

##### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

##### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

##### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

##### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

#### Symptoms related to the physical, chemical and toxicological characteristics

##### • If swallowed

Data are not available.

##### • If in eyes

Causes serious eye irritation

# Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Epoxy systems Araldit® G 2 cast resin

article number: 2545

- **If inhaled**

Data are not available.

- **If on skin**

causes skin irritation, May produce an allergic reaction, pruritis, localised redness

- **Other information**

none

### 11.2 Endocrine disrupting properties

Information on this property is not available.

### 11.3 Information on other hazards

There is no additional information.

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	LC50	1,75 mg/l	fish	96 h
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	EC50	1,7 mg/l	aquatic invertebrates	48 h
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	ErC50	>11 mg/l	algae	72 h

### Biodegradation

Data are not available.

### 12.2 Process of degradability

Degradability of components of the mixture						
Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	oxygen depletion	5 %	28 d		ECHA

### 12.3 Bioaccumulative potential

Data are not available.

# Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Epoxy systems Araldit® G 2 cast resin

article number: 2545

### Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
2,2'-[[1-methylethylidene]bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	31	≥2,64 – ≤3,78 (pH value: ~7, 25 °C)	

#### 12.4 Mobility in soil

Data are not available.

#### 12.5 Results of PBT and vPvB assessment

Data are not available.

#### 12.6 Endocrine disrupting properties

Information on this property is not available.

#### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

### 13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste catalogue ordinance (Germany).

### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADRRID	UN 3082
IMDG-Code	UN 3082
ICAO-TI	UN 3082

### 14.2 UN proper shipping name

ADRRID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
--------	---



# Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Epoxy systems Araldit® G 2 cast resin

article number: 2545

IMDG-Code	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
ICAO-TI	Environmentally hazardous substance, liquid, n.o.s.
Technical name (hazardous ingredients)	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane
<b>14.3 Transport hazard class(es)</b>	
ADRRID	9
IMDG-Code	9
ICAO-TI	9
<b>14.4 Packing group</b>	
ADRRID	III
IMDG-Code	III
ICAO-TI	III
<b>14.5 Environmental hazards</b>	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment):	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane
<b>14.6 Special precautions for user</b>	
Provisions for dangerous goods (ADR) should be complied within the premises.	
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	
The cargo is not intended to be carried in bulk.	
<b>14.8 Information for each of the UN Model Regulations</b>	
<b>Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information</b>	
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Particulars in the transport document	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (contains: 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane), 9, III, (-)
Classification code	M6
Danger label(s)	9, "Fish and tree"
 	
Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	274, 335, 375, 601
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	3
Tunnel restriction code (TRC)	-

# Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Epoxy systems Araldit® G 2 cast resin

article number: 2545

Hazard identification No 90

**Emergency Action Code** 3Z

### Regulations concerning the International Carriage of Dangerous Goods by Rail (RID) Additional information

**Classification code** 9

**Danger label(s)** 9  
Fish and tree



**Environmental hazards** Yes  
Hazardous to water

**Special provisions (SP)** 274, 335, 375, 601

**Excepted quantities (EQ)** E1

**Limited quantities (LQ)** 5 L

**Transport category (TC)** 3

**Hazard identification No** 90

### International Maritime Dangerous Goods Code (IMDG) - Additional information

**Proper shipping name** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

**Particulars in the shipper's declaration** UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (contains: 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane), 9, III

**Marine pollutant** YES (hazardous to the aquatic environment), (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane)

**Danger label(s)** 9, "Fish and tree"



**Special provisions (SP)** 274, 335, 969

**Excepted quantities (EQ)** E1

**Limited quantities (LQ)** 5 L

**EmS** F-A, S-F

**Stowage category** A

### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

**Proper shipping name** Environmentally hazardous substance, liquid, n.o.s.

**Particulars in the shipper's declaration** UN3082, Environmentally hazardous substance, liquid, n.o.s., (contains: 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane), 9, III

**Environmental hazards** YES (hazardous to the aquatic environment)

**Danger label(s)** 9, "Fish and tree"

# Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Epoxy systems Araldit® G 2 cast resin

article number: 2545



Special provisions (SP)	A97, A158, A197, A215
Exempted quantities (EQ)	E1
Limited quantities (LQ)	30 kg

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Relevant provisions of the European Union (EU)

##### Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
E2	environmental hazards (hazardous to the aquatic environment, cat. 2)	200                      500	57)

##### Notation

57) Hazardous to the Aquatic Environment in category Chronic 2

##### Deco-Paint Directive

VOC content	>70 % 840 g/l
-------------	------------------

##### Industrial Emissions Directive (IED)

VOC content	>70 %
VOC content	840 g/l

##### Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

##### Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

##### Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
2,2'-[[1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-related functions in or via the aquatic environment		a)	

# Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Epoxy systems Araldit® G 2 cast resin

article number: 2545

### Legend

A) Indicative list of the main pollutants

### Regulation on the marketing and use of explosives precursors

none of the ingredients are listed

### Regulation on drug precursors

none of the ingredients are listed

### Regulation on substances that deplete the ozone layer (ODS)

none of the ingredients are listed

### Regulation concerning the export and import of hazardous chemicals (PIC)

none of the ingredients are listed

### Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

### Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

### National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
KR	KECI	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

### Legend

AIIC Australian Inventory of Industrial Chemicals  
CICR Chemical Inventory and Control Regulation  
CSCL-ENCS List of Existing and New Chemical Substances (CSCL-ENCS)  
DSL Domestic Substances List (DSL)  
ECSI EC Substance Inventory (EINECS, ELINCS, NLP)  
IECSC Inventory of Existing Chemical Substances Produced or Imported in China  
KECI Korea Existing Chemicals Inventory  
NZIoC New Zealand Inventory of Chemicals  
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)  
REACH Reg. REACH registered substances  
TCSI Taiwan Chemical Substance Inventory  
TSCA Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

# Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Epoxy systems Araldit® G 2 cast resin

article number: 2545

### SECTION 16: Other information

#### Indication of changes (revised safety data sheet)

Alignment to regulation:

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1		Supplemental hazard information: change in the listing (table)	yes
2.1		The most important adverse physicochemical, human health and environmental effects: Spillage and fire water can cause pollution of watercourses.	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Warning		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2	contains: 2,2'-[[1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane		yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

#### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand



# Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Epoxy systems Araldit® G 2 cast resin

article number: 2545

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitisation
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

# Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Epoxy systems Araldit® G 2 cast resin

article number: 2545

### Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.