acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2%

article number: 25AL Version: 1.0 en

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance

Article number

Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses:

Uses advised against:

Laboratory and analytical use Laboratory chemical

Etchant Nital 2%

25AL

Do not use for private purposes (household). Food, drink and animal feedingstuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 Telefax: +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data Department Health, Safety and Environment sheet:

e-mail (competent person):

sicherheit@carlroth.de

Emergency telephone number 1.4

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
2.16	Substance or mixture corrosive to metals	1	Met. Corr. 1	H290
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects The product is combustible and can be ignited by potential ignition sources.



date of compilation: 2023-11-22

acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2 %

article number: 25AL

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS02, GHS05



Hazard statements

H225	Highly flammable liquid and vapour
H290	May be corrosive to metals
H315	Causes skin irritation
H319	Causes serious eye irritation

Precautionary statements

Precautionary statements - prevention

P280 Wear protective gloves/eye protection

Precautionary statements - response

P302+P352	IF ON SKIN: Wash with plenty of water
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

2.3 Other hazards

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of \ge 0,1%.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\ge 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Ethanol	CAS No 64-17-5 EC No 200-578-6 Index No 603-002-00-5	70 - 90	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319		GHS-HC



acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2%

article number: 25AL



Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
2-Propanol	CAS No 67-63-0 EC No 200-661-7 Index No 603-117-00-0	5 – 10	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336		GHS-HC
Nitric acid% [C ≤ 70 %]	CAS No 7697-37-2 EC No 231-714-2 Index No 007-030-00-3	1-<3	Ox. Liq. 3 / H272 Met. Corr. 1 / H290 Acute Tox. 3 / H331 Skin Corr. 1A / H314 Eye Dam. 1 / H318		B(a) GHS-HC IOELV

Notes

B(a): The classification refers to an aqueous solution GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/ 2008/EC, Annex VI)

IOELV: Substance with a community indicative occupational exposure limit value

Name of sub- stance	Identifier	Specific Conc. Limits	M-Factors	ΑΤΕ	Exposure route
Nitric acid% [C ≤ 70 %]	CAS No 7697-37-2 EC No 231-714-2	Ox. Liq. 3; H272: C ≥ 65 % Skin Corr. 1A; H314: C ≥ 20 % Skin Corr. 1B; H314: 5 % ≤ C < 20 %	-	2,65 ^{mg} /ı/4h	inhalation: va- pour

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 **Description of first aid measures**



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2%

article number: 25AL

4.2 Most important symptoms and effects, both acute and delayed

Irritation, Nausea, Vomiting, Abdominal pain, Breathing difficulties, Vertigo, Drowsiness, Narcosis, Loss of righting reflex, and ataxia

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapourair mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO₂), May produce toxic fumes of carbon monoxide if burning.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. The product is an acid. Before discharge into sewage plants the product normally needs to be neutralised.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.



acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2%



article number: 25AL

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2%



article number: 25AL

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
EU	nitric acid	7697-37- 2	IOELV			1	2,6				2006/15/ EC
GB	ethanol	64-17-5	WEL	1.00 0	1.920						EH40/ 2005
GB	propan-2-ol	67-63-0	WEL	400	999	500	1.250				EH40/ 2005
GB	nitric acid	7697-37- 2	WEL			1	2,6				EH40/ 2005

Notation

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 Ceiling-C STEL

TWA hours time-weighted average (unless otherwise specified)

Relevant DNELs of components									
Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time			
2-Propanol	67-63-0	DNEL	500 mg/m ³	human, inhalat- ory	worker (industry)	chronic - systemic effects			
2-Propanol	67-63-0	DNEL	1.000 mg/ m³	human, inhalat- ory	worker (industry)	acute - systemic effects			
2-Propanol	67-63-0	DNEL	888 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects			

Relevant PNECs of components									
Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time			
2-Propanol	67-63-0	PNEC	140,9 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)			
2-Propanol	67-63-0	PNEC	140,9 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)			
2-Propanol	67-63-0	PNEC	2.251 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)			
2-Propanol	67-63-0	PNEC	552 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)			
2-Propanol	67-63-0	PNEC	552 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)			

acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2 %



article number: 25AL

Relevant PNECs of components							
Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time	
2-Propanol	67-63-0	PNEC	28 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)	

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

Butyl caoutchouc (butyl rubber)

material thickness

0,7mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2 %

article number: 25AL

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1	Information on basic physical and chemical properties									
	Physical state	liquid								
	Colour	clear - colourless								
	Odour	characteristic								
	Melting point/freezing point	not determined								
	Boiling point or initial boiling point and boiling range	>75 °C								
	Flammability	flammable liquid in accordance with GHS criteria								
	Lower and upper explosion limit	3,1 vol% (LEL) - 27,7 vol% (UEL) (data apply to the main component)								
	Flash point	14 °C								
	Auto-ignition temperature	not determined								
	Decomposition temperature	not relevant								
	pH (value)	<2 (20 °C)								
	Kinematic viscosity	not determined								
	Solubility(ies)									
	Water solubility	miscible in any proportion								
	Partition coefficient									
	Partition coefficient n-octanol/water (log value):	this information is not available								
	Vapour pressure	not determined								
	Density and/or relative density									
	Density	~ 0,8 ^g / _{cm³} at 20 °C								
	Relative vapour density	information on this property is not available								
	Particle characteristics	not relevant (liquid)								
	Other safety parameters									
	Oxidising properties	none								
9.2	Other information									
	Information with regard to physical hazard classes:									
	Corrosive to metals	category 1: corrosive to metals								



acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2%

article number: 25AL

Other safety characteristics:

Miscibility

completely miscible with water

SECTION 10: Stability and reactivity

10.1 Reactivity

The mixture contains reactive substance(s). Risk of ignition. Substance or mixture corrosive to metals. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Alkali metals, Alkaline earth metal, Acetic anhydride, Peroxides, Phosphorus oxides (e.g. P2O5), Nitric acid, Strong alkali, Nitrate, Perchlorates, => Explosive properties

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

different metals

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
Nitric acid% [C ≤ 70 %]	7697-37-2	inhalation: vapour	2,65 ^{mg} /ı/4h



acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2 %



article number: 25AL

Acute toxicity of components					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Ethanol	64-17-5	oral	LD50	10.470 ^{mg} / _{kg}	rat
Ethanol	64-17-5	inhalation: va- pour	LC50	124,7 ^{mg} / _l /4h	rat
2-Propanol	67-63-0	inhalation: va- pour	LC50	37,5 ^{mg} / _l /4h	rat
2-Propanol	67-63-0	oral	LD50	5.045 ^{mg} / _{kg}	rat
2-Propanol	67-63-0	dermal	LD50	12.800 ^{mg} / _{kg}	rabbit
Nitric acid% [C ≤ 70 %]	7697-37-2	inhalation: va- pour	LC50	>2,65 ^{mg} /ı/4h	rat

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

vomiting, abdominal pain, nausea, Causes damage to liver through prolonged or repeated exposure if swallowed, loss of righting reflex, and ataxia

• If in eyes

Causes serious eye irritation

If inhaled

drowsiness, narcosis, vertigo, breathing difficulties, Inebriation

acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2 %



article number: 25AL

• If on skin

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation), causes skin irritation

Other information

none

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\ge 0,1\%$.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute) of components						
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time	
Ethanol	64-17-5	LC50	15.400 ^{mg} / _l	fish	96 h	
Ethanol	64-17-5	EC50	>10.000 ^{mg} / _l	aquatic invertebrates	48 h	
Ethanol	64-17-5	ErC50	22.000 ^{mg} / _l	algae	96 h	
2-Propanol	67-63-0	LC50	10.000 ^{mg} / _l	fish	96 h	

Aquatic toxicity (chronic) of components

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Ethanol	64-17-5	LC50	1.806 ^{mg} / _l	aquatic invertebrates	10 d
Ethanol	64-17-5	ErC50	675 ^{mg} / _l	algae	4 d

12.2 Persistence and degradability

Degradability of components						
Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source
Ethanol	64-17-5	biotic/abiotic	94 %	d		
Ethanol	64-17-5	oxygen deple- tion	69 %	5 d		ECHA
Ethanol	64-17-5	oxygen deple- tion	84 %	10 d		ECHA
Ethanol	64-17-5	oxygen deple- tion	97 %	20 d		ECHA
2-Propanol	67-63-0	biotic/abiotic	95 %	21 d	modifizierter OECD Screen- ing Test	

acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2 %



article number: 25AL

Degradability of components						
Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source
2-Propanol	67-63-0	oxygen deple- tion	53 %	5 d		ECHA

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components					
Name of substance	CAS No	BCF	Log KOW	BOD5/COD	
Ethanol	64-17-5		-0,31	0,6211	
2-Propanol	67-63-0		0,05		

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of \geq 0,1%.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\ge 0,1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Properties of waste which render it hazardous

HP 3 flammable

HP 4 irritant - skin irritation and eye damage

acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2 %

® Roth

article number: 25AL

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1	UN number or ID number	
	ADRRID	UN 2924
	IMDG-Code	UN 2924
	ICAO-TI	UN 2924
14.2	UN proper shipping name	
	ADRRID	FLAMMABLE LIQUID, CORROSIVE, N.O.S.
	IMDG-Code	FLAMMABLE LIQUID, CORROSIVE, N.O.S.
	ICAO-TI	Flammable liquid, corrosive, n.o.s.
	Technical name (hazardous ingredients)	Ethanol, Nitric acid% [C ≤ 70 %]
14.3	Transport hazard class(es)	
	ADRRID	3 (8)
	IMDG-Code	3 (8)
	ICAO-TI	3 (8)
14.4	Packing group	
	ADRRID	II
	IMDG-Code	II
	ICAO-TI	II
14.5	Environmental hazards	non-environmentally hazardous acc. to the dan- gerous goods regulations
440		

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)Additional
information

Proper shipping name	FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Particulars in the transport document	UN2924, FLAMMABLE LIQUID, CORROSIVE, N.O.S., (contains: Ethanol, Nitric acid% [C ≤ 70 %]), 3 (8), II, (D/E)
Classification code	FC
Danger label(s)	3+8

Safety data sheet Safety data sheet acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2 %

article number: 25AL



Special provisions (SP)	274
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D/E
Hazard identification No	338
Emergency Action Code	3WE
Regulations concerning the International C information	arriage of Dangerous Goods by Rail (RID)Additional
Classification code	FC
Danger label(s)	3+8
Special provisions (SP)	274
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
Transport category (TC)	2
Hazard identification No	338
International Maritime Dangerous Goods C	ode (IMDG) - Additional information
Proper shipping name	FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Particulars in the shipper's declaration	UN2924, FLAMMABLE LIQUID, CORROSIVE, N.O.S., (contains: Ethanol, Nitric acid% [C ≤ 70 %]), 3 (8), II, 14°C c.c.
Marine pollutant	-
Danger label(s)	3+8
Special provisions (SP)	274
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-E, S-C
Stowage category	В

acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2 %



article number: 25AL

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information					
Proper shipping name	Flammable liquid, corrosive, n.o.s.				
Particulars in the shipper's declaration	UN2924, Flammable liquid, corrosive, n.o.s., (con- tains: Ethanol, Nitric acid% [C ≤ 70 %]), 3 (8), II				
Danger label(s)	3+8				
Special provisions (SP)	A3				
Excepted quantities (EQ)	E2				
Limited quantities (LQ)	0,5 L				

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Seveso Directive

2012/18/EU (Seveso III)				
Νο	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the ap- plication of lower and upper-tier re- quirements		
P5c	flammable liquids (cat. 2, 3)	5.000 50.000	51)	

Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

Deco-Paint Directive

VOC content	98 %
VOC content	784 ^g /l

Industrial Emissions Directive (IED)

VOC content	98 %
VOC content	784 ^g /l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2 %

article number: 25AL

Water Framework Directive (WFD)

Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Ethanol	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)	
2-Propanol	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)	

Legend

a) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

xplosives precursors which are subject to restrictions						
Name of substance	CAS No	Wt%	Type of registration	Re- marks	Limit value	Upper limit value for the pur- pose of licens- ing un- der Art icle 5(3
Nitric acid% [C ≤ 70 %]	7697-37-2	2	Annex I		3 % w/w	10 % w/v

Legend Annex I

Substances which shall not be made available to members of the general public on their own, or in mixtures or substances including them, except if the concentration is equal to or lower than the limit values set out below

Additional statements

If the product is passed on to third parties, in accordance with Article 7 "Notification of the supply chain" of Regulation EU 2019/1148, the information obligation is subject to the entire supply chain and all other provisions mentioned in Article 7 on restricted and regulated raw materials.

Regulation on drug precursors

none of the ingredients are listed

Regulation on substances that deplete the ozone layer (ODS)

none of the ingredients are listed

Regulation concerning the export and import of hazardous chemicals (PIC)

none of the ingredients are listed

Regulation on persistent organic pollutants (POP)

none of the ingredients are listed



acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2 %



article number: 25AL

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list none of the ingredients are listed

Restrictions according to GB REACH, Annex 17

angerous substances with restrictions (GB REACH, Annex 17)			
Name of substance	Name acc. to inventory	CAS No	No
Etchant Nital	this product meets the criteria for classi- fication in accordance with Regulation No 1272/2008/EC		3
Ethanol	flammable / pyrophoric		40
2-Propanol	flammable / pyrophoric		40

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2 %



article number: 25AL

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations	
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in imple- mentation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC	
Acute Tox.	Acute toxicity	
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concern- ing the International Carriage of Dangerous Goods by Road)	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BOD	Biochemical Oxygen Demand	
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)	
Ceiling-C	Ceiling value	
COD	Chemical oxygen demand	
DGR	Dangerous Goods Regulations (see IATA/DGR)	
DNEL	Derived No-Effect Level	
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causi 50 % changes in response (e.g. on growth) during a specified time interval	
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identi fier of substances commercially available within the EU (European Union)	
ED	Endocrine disruptor	
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)	
EINECS	European Inventory of Existing Commercial Chemical Substances	
ELINCS	European List of Notified Chemical Substances	
EmS	Emergency Schedule	
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control	
Eye Dam.	Seriously damaging to the eye	
Eye Irrit.	Irritant to the eye	
Flam. Liq.	Flammable liquid	
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)	
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions	
IATA	International Air Transport Association	
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)	
ICAO	International Civil Aviation Organization	
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air	

acc. to Regulation (EC) No. 1907/2006 (REACH)

Etchant Nital 2 %

article number: 25AL



Abbr.	Descriptions of used abbreviations
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
log KOW	n-Octanol/water
Met. Corr.	Substance or mixture corrosive to metals
NLP	No-Longer Polymer
Ox. Liq.	Oxidising liquid
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

acc. to Regulation (EC) No. 1907/2006 (REACH)



Etchant Nital 2 %

article number: 25AL

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.