

# Ethylenediamine ROTIPURAN® ≥99,5 %, p.a., anhydrous

article number: **3049** Version: **3.0 en** Replaces version of: 2020-11-05 Version: (2)

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

# 1.1 Product identifier

Identification of the substance	<b>Ethylenediamine</b> ROTIPURAN® ≥99,5 %, p.a., an- hydrous
Article number	3049
Registration number (REACH)	01-2119480383-37-xxxx
Index number in CLP Annex VI	612-006-00-6
EC number	203-468-6
CAS number	107-15-3
Delevent identified uses of the substance or mi	vture and uses advised against

# **1.2** Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Uses advised against:

Laboratory chemical Laboratory and analytical use

Do not use for squirting or spraying. Do not use for products which come into direct contact with the skin. Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

# **1.3** Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

**Telephone:**+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment sheet:

# e-mail (competent person):

# sicherheit@carlroth.de

# **1.4** Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

according to Regulation (EC) No. 1907/2006 (REACH)



# Ethylenediamine ROTIPURAN® ≥99,5 %, p.a., anhydrous

article number: 3049

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

# Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	3	Flam. Liq. 3	H226
3.10	Acute toxicity (oral)	4	Acute Tox. 4	H302
3.1D	Acute toxicity (dermal)	3	Acute Tox. 3	H311
3.1I	Acute toxicity (inhal.)	4	Acute Tox. 4	H332
3.2	3.2 Skin corrosion/irritation		Skin Corr. 1B	H314
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318
3.4R	Respiratory sensitisation	1	Resp. Sens. 1	H334
3.4S	Skin sensitisation	1	Skin Sens. 1	H317
4.1C	Hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16

# The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

# 2.2 Label elements

# Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word Danger

# **Pictograms**

GHS02, GHS05, GHS06, GHS08



# Hazard statements

H226	Flammable liquid and vapour
H302+H332	Harmful if swallowed or if inhaled
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H412	Harmful to aquatic life with long lasting effects

# **Precautionary statements**

# **Precautionary statements - prevention**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking
P280	Wear protective gloves/protective clothing/eye protection/face protection



article number: 3049

#### Precautionary statements - response

P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]
P304+P340	IF INHALED. Remove person to fresh air and keep comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing
P310	Immediately call a POISON CENTER/doctor

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

#### Symbol(s)



H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H412	Harmful to aquatic life with long lasting effects.
P304+P340	Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

# 2.3 Other hazards

# Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

# **SECTION 3: Composition/information on ingredients**

# 3.1 Substances

Name of substance	Ethylenediamine
Molecular formula	$C_2H_8N_2$
Molar mass	60,1 <sup>g</sup> / <sub>mol</sub>
REACH Reg. No	01-2119480383-37-xxxx
CAS No	107-15-3
EC No	203-468-6
Index No	612-006-00-6

# Substance of Very High Concern (SVHC)

Name of substance	CAS No	EC No	Listed in	Remarks
Ethylenediamine	107-15-3	203-468-6	Candidate list	RSP (57f-hh)

#### Legend

candidate Substances meeting the criteria referred to in Article 57 and for eventual inclusion in Annex XIV list

RSP (57f-hh) Respiratory sensitising properties (article 57(f) - human health)



according to Regulation (EC) No. 1907/2006 (REACH)



# Ethylenediamine ROTIPURAN® ≥99,5 %, p.a., anhydrous

article number: 3049

Substance, Specific Conc. Limits, M-factors, ATE					
Specific Conc. Limits         M-Factors         ATE         Exposure route					
-	-	866 <sup>mg</sup> / <sub>kg</sub> 560 <sup>mg</sup> / <sub>kg</sub> 14,7 <sup>mg</sup> / <sub>l</sub> /4h	oral dermal inhalation: vapour		

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures



#### **General notes**

Take off immediately all contaminated clothing. Self-protection of the first aider.

#### **Following inhalation**

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following skin contact

After contact with skin, wash immediately with plenty of water. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

#### Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

#### **Following ingestion**

Rinse mouth immediately and drink plenty of water. Rinse mouth with water (only if the person is conscious). Call a physician immediately. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

#### 4.2 Most important symptoms and effects, both acute and delayed

Corrosion, Vomiting, Risk of blindness, Gastric perforation, Risk of serious damage to eyes, Allergic reactions, Cough, Dyspnoea

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media



#### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

# Unsuitable extinguishing media

water jet



article number: 3049

# 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapourair mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

# Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

# **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures



# For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. Danger of explosion.

# 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

# Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling


Provision of sufficient ventilation. Handle and open container with care. Clear contaminated areas thoroughly.



according to Regulation (EC) No. 1907/2006 (REACH)

# Ethylenediamine ROTIPURAN® ≥99,5 %, p.a., anhydrous

article number: 3049





Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

#### Advice on general occupational hygiene

Thorough skin-cleansing after handling the product. When using do not smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

#### Incompatible substances or mixtures

Observe hints for combined storage.

#### **Consideration of other advice:**

Store locked up. Ground/bond container and receiving equipment.

#### **Ventilation requirements**

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted. Use local and general ventilation.

# Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

#### 7.3 Specific end use(s)

No information available.

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

#### National limit values

# **Occupational exposure limit values (Workplace Exposure Limits)**

This information is not available.

#### Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	25 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	3,6 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic effects



according to Regulation (EC) No. 1907/2006 (REACH)



# Ethylenediamine ROTIPURAN® ≥99,5 %, p.a., anhydrous

article number: 3049

Environm	nvironmental values					
Relevant	Relevant PNECs and other threshold levels					
End- point	Threshold level	Organism	Environmental com- partment	Exposure time		
PNEC	0,167 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	water	intermittent release		
PNEC	0,016 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single instance)		
PNEC	0,002 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single instance)		
PNEC	0,5 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)		
PNEC	7,68 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	freshwater sediment	short-term (single instance)		
PNEC	0,768 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	marine sediment	short-term (single instance)		
PNEC	4,36 <sup>mg</sup> / <sub>kg</sub>	terrestrial organisms	soil	short-term (single instance)		

# 8.2 Exposure controls

# Individual protection measures (personal protective equipment)

# Eye/face protection



Use safety goggle with side protection. Wear face protection.

# **Skin protection**



#### hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

# • type of material

Butyl caoutchouc (butyl rubber)

material thickness

0,7mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

- Splash protection Protective gloves
- type of material: NBR (Nitrile rubber)

# Ethylenediamine ROTIPURAN® ≥99,5 %, p.a., anhydrous

#### article number: 3049

- material thickness: 0,4 mm
- breakthrough times of the glove material:

>30 minutes (permeation: level 2)

# • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

# **Respiratory protection**



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65  $^{\circ}$ C, colour code: Brown).

#### **Environmental exposure controls**

Keep away from drains, surface and ground water.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	amine
Melting point/freezing point	11,1 °C (ECHA)
Boiling point or initial boiling point and boiling range	117,1 °C at 1.013 hPa (ECHA)
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	2,5 vol% (LEL) - 16,3 vol% (UEL)
Flash point	42 °C at 1.013 hPa (ECHA)
Auto-ignition temperature	405 °C (ECHA) (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	12,2 (in aqueous solution: 100 <sup>g</sup> / <sub>l</sub> , 20 °C)
Kinematic viscosity	not determined
Solubility(ies)	
Water solubility	1.000 <sup>g</sup> / <sub>l</sub> (ECHA)
Partition coefficient	
Partition coefficient n-octanol/water (log value):	-1,62 (pH value: >12, 25 °C) (ECHA)
Soil organic carbon/water (log KOC)	3,679 (ECHA)
Vapour pressure	12 hPa at 20 °C 22 hPa at 30 °C 70 hPa at 50 °C





® ROTH

article number: 3049

	Density and/or relative density	
	Density	0,897 <sup>g</sup> / <sub>cm³</sub> at 20 °C
	Relative vapour density	information on this property is not available
	Particle characteristics	not relevant (liquid)
	Other safety parameters	
	Oxidising properties	none
2	Other information	
	Information with regard to physical hazard classes:	There is no additional information.
	Other safety characteristics:	
	Temperature class (EU, acc. to ATEX)	T2 Maximum permissible surface temperature on the equipment: 300°C

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

9.2

It's a reactive substance. Risk of ignition.

# If heated

Risk of ignition. Vapours may form explosive mixtures with air.

# 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

# **10.3** Possibility of hazardous reactions

**Violent reaction with:** Aldehydes, Alcohols, Halogenated hydrocarbons, Perchlorates, **Exothermic reaction with:** Acrylic acid, Acetic acid, Acetic anhydride, Oxidisers, Acids, Carbon disulfide, Hydrochloric gas

# 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

# **10.5** Incompatible materials

aluminium, iron, copper, bronze, brass, zinc

# **10.6** Hazardous decomposition products

Hazardous combustion products: see section 5.

according to Regulation (EC) No. 1907/2006 (REACH)





# article number: 3049

# **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Classification according to GHS (1272/2008/EC, CLP)

# Acute toxicity

Harmful if swallowed. Toxic in contact with skin. Harmful if inhaled.

# Acute toxicity

Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	866 <sup>mg</sup> / <sub>kg</sub>	rat		ECHA
inhalation: vapour	LC50	14,7 <sup>mg</sup> / <sub>l</sub> /4h	rat		ECHA
dermal	LD50	560 <sup>mg</sup> / <sub>kg</sub>	rabbit		ECHA

# Skin corrosion/irritation

Causes severe skin burns and eye damage.

# Serious eye damage/eye irritation

Causes serious eye damage.

# **Respiratory or skin sensitisation**

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

# Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

# Carcinogenicity

Shall not be classified as carcinogenic.

# **Reproductive toxicity**

Shall not be classified as a reproductive toxicant.

# Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

# Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

# **Aspiration hazard**

Shall not be classified as presenting an aspiration hazard.

# Symptoms related to the physical, chemical and toxicological characteristics

# • If swallowed

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects)

# • If in eyes

causes burns, Causes serious eye damage, risk of blindness

# • If inhaled

May produce an allergic reaction, cough, Dyspnoea





# article number: 3049

# • If on skin

causes severe burns, causes poorly healing wounds, May produce an allergic reaction, pruritis, localised redness

# Other information

Other adverse effects: Liver and kidney damage

# **11.2** Endocrine disrupting properties

Not listed.

# 11.3 Information on other hazards

There is no additional information.

# **SECTION 12: Ecological information**

# 12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
LC50	640 <sup>mg</sup> / <sub>l</sub>	fish	ECHA	96 h
EC50	16,7 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	ECHA	48 h
ErC50	645 <sup>mg</sup> / <sub>l</sub>	algae	ECHA	72 h

# Biodegradation

The substance is readily biodegradable.

# 12.2 Process of degradability

Theoretical Oxygen Demand with nitrification: 2,462  $^{mg}/_{mg}$  Theoretical Oxygen Demand: 1,331  $^{mg}/_{mg}$  Theoretical Carbon Dioxide: 1,465  $^{mg}/_{mg}$ 

#### Process of degradability

Process	Degradation rate	Time
biotic/abiotic	94 %	28 d
oxygen depletion	10 %	5 d

# 12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW) -1,62 (pH value: >12, 25 °C) (ECHA)
---

# 12.4 Mobility in soil

according to Regulation (EC) No. 1907/2006 (REACH)



# Ethylenediamine ROTIPURAN® ≥99,5 %, p.a., anhydrous

article number: 3049

Henry's law constant	0,6 <sup>Pa m³</sup> / <sub>mol</sub> at 25 °C (ECHA)
The Organic Carbon normalised adsorption coefficient	3,679 (ECHA)

# 12.5 Results of PBT and vPvB assessment

Data are not available.

**12.6 Endocrine disrupting properties** Not listed.

# 12.7 Other adverse effects

Data are not available.

# **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

#### 13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste catalogue ordinance (Germany).

#### 13.3 Remarks

14.2

14.3

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

# **SECTION 14: Transport information**

# 14.1 UN number or ID number

ADR/RID/ADN	UN 1604
IMDG-Code	UN 1604
ICAO-TI	UN 1604
UN proper shipping name	
ADR/RID/ADN	ETHYLENEDIAMINE
IMDG-Code	ETHYLENEDIAMINE
ICAO-TI	Ethylenediamine
Transport hazard class(es)	
ADR/RID/ADN	8 (3)

according to Regulation (EC) No. 1907/2006 (REACH)



# Ethylenediamine ROTIPURAN® ≥99,5 %, p.a., anhydrous

article number: 3049

	IMDG-Code	8 (3)
	ICAO-TI	8 (3)
14.4	Packing group	
	ADR/RID/ADN	П
	IMDG-Code	II
	ICAO-TI	П
14.5	Environmental hazards	non-environmentally hazardous acc. to the dan- gerous goods regulations

# 14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

# 14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

# 14.8 Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information
Information

Proper shipping name	ETHYLENEDIAMINE
Particulars in the transport document	UN1604, ETHYLENEDIAMINE, 8 (3), II, (D/E)
Classification code	CF1
Danger label(s)	8+3
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D/E
Hazard identification No	83
Emergency Action Code	2W
International Maritime Dangerous Goods Code	e (IMDG) - Additional information
Proper shipping name	ETHYLENEDIAMINE
Particulars in the shipper's declaration	UN1604, ETHYLENEDIAMINE, 8 (3), II, 42°C c.c.
Marine pollutant	-
Danger label(s)	
	8+3
	8+3
Special provisions (SP)	8+3 -
	8+3 - E2
Special provisions (SP)	_

according to Regulation (EC) No. 1907/2006 (REACH)



# Ethylenediamine ROTIPURAN® ≥99,5 %, p.a., anhydrous

article number: 3049

EmS	F-E, S-C
Stowage category	A
Segregation group	18 - Alkalis
International Civil Aviation Organization (ICAO-I	ATA/DGR) - Additional information
Proper shipping name	Ethylenediamine
Particulars in the shipper's declaration	UN1604, Ethylenediamine, 8 (3), II
Danger label(s)	8+3
Excepted quantities (EQ)	E2
Limited quantities (LQ)	0,5 L

# SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture 15.1 Relevant provisions of the European Union (EU)

**Restrictions according to REACH, Annex XVII** 

Dangerous substances with restrictions (REACH, Annex XVII)				
Name of substance	Name acc. to inventory	CAS No	Restriction	No
Ethylenediamine	this product meets the criteria for classification in accordance with Reg- ulation No 1272/2008/EC		R3	3
Ethylenediamine	flammable / pyrophoric		R40	40
Ethylenediamine	substances in tattoo inks and perman- ent make-up		R75	75

Legend R3

1. Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

tricks and jokes,

games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
Articles not complying with paragraph 1 shall not be placed on the market.
Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they

can be used as fuel in decorative oil lamps for supply to the general public, and

present an aspiration hazard and are labelled with H304.
4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation

(CEN). 5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:

(a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps – may lead to life-threatening lung damage";
(b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage';
(c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black on a containers not exceeding 1 litre by 1 December 2010;

opaque containers not exceeding 1 litre by 1 December 2010.';



# Ethylenediamine ROTIPURAN® ≥99,5 %, p.a., anhydrous

#### article number: 3049

#### Legend R40

- 1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: metallic glitter intended mainly for decoration,
- artificial snow and frost,

- 'whoopee' cushions,
   silly string aerosols,
   imitation excrement,
   horns for parties,
   decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: (For professional users only.

- 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).

4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

Ethylenediamine ROTIPURAN® ≥99,5 %, p.a., anhydrous

#### article number: 3049



8. Mixtures that do not contain the statement "Mixture for use in tattoos or permanent make-up" shall not be used for tattooing purposes.





# Ethylenediamine ROTIPURAN® ≥99,5 %, p.a., anhydrous

#### article number: 3049

#### Legend

9. This entry does not apply to substances that are gases at temperature of 20 °C and pressure of 101,3 kPa, or generate a vapour pressure of more than 300 kPa at temperature of 50 °C, with the exception of formaldehyde (CAS No 50-00-0, EC No 200-001-8).

10. This entry does not apply to the placing on the market of a mixture for use for tattooing purposes, or to the use of a mixture for tattooing purposes, when placed on the market exclusively as a medical device or an accessory to a medical device, within the meaning of Regulation (EU) 2017/745, or when used exclusively as a medical device or an accessory to a medical device, within the same meaning. Where the placing on the market or use may not be exclusively as a medical device or an accessory to a medical device or an accessory to a medical device, the requirements of Regulation (EU) 2017/745 and of this Regulation shall apply cumulatively.

# List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

# Substance of Very High Concern (SVHC)

Name acc. to invent- ory	CAS No	Listed in	Remarks	Latest ap- plication date	Sunset date	Date of in- clusion
ethylenediamine (EDA)	107-15- 3	Candidate list	RSP (57f-hh)			2018-06-27

Legend

candidate list Substances meeting the criteria referred to in Article 57 and for eventual inclusion in Annex XIV RSP (57f-hh) Respiratory sensitising properties (article 57(f) - human health)

# **Seveso Directive**

2012/18/EU (Seveso III)				
Νο	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the ap- plication of lower and upper-tier re- quirements		Notes
P5c	flammable liquids (cat. 2, 3)	5.000	50.000	51)

#### Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

# **Deco-Paint Directive**

#### Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	897 <sup>g</sup> /l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

# Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

according to Regulation (EC) No. 1907/2006 (REACH)



# Ethylenediamine ROTIPURAN® ≥99,5 %, p.a., anhydrous

article number: 3049

Water Framework Directive	Water Framework Directive (WFD)			
List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Ethylenediamine	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		A)	

#### Legend

A) Indicative list of the main pollutants

# Regulation on the marketing and use of explosives precursors

not listed

# **Regulation on drug precursors**

not listed

# Regulation on substances that deplete the ozone layer (ODS)

not listed

#### Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

# **Regulation on persistent organic pollutants (POP)**

not listed

# **Other information**

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

#### **National inventories**

Country	Inventory	Status
AU	AICS	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed

according to Regulation (EC) No. 1907/2006 (REACH)



# Ethylenediamine ROTIPURAN® ≥99,5 %, p.a., anhydrous

#### article number: 3049

Country	Inventory	Status
US	TSCA	substance is listed
DSL ECSI IECSC INSQ KECI NZIOC PICCS	Domestic Substances List EC Substance Inventory (E Inventory of Existing Cher National Inventory of Che Korea Existing Chemicals New Zealand Inventory of	iontrol Regulation hemical Substances (CSCL-ENCS) (DSL) EINECS, ELINCS, NLP) mical Substances Produced or Imported in China mical Substances Inventory f Chemicals nemicals and Chemical Substances (PICCS) nces cce Inventory

# 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

# **SECTION 16: Other information**

# Indication of changes (revised safety data sheet)

Alignment to regulation: Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification according to Regulation (EC) No 1272/2008 (CLP): change in the listing (table)	yes
2.1		The most important adverse physicochemical, human health and environmental effects: Skin corrosion produces an irreversible dam- age to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB.	yes

# Restructuring: section 9, section 14

# Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de naviga- tion intérieures (European Agreement concerning the International Carriage of Dangerous Goods by In- land Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concern- ing the International Carriage of Dangerous Goods by Road)
ADR/RID/ADN	Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN)
ATE	Acute Toxicity Estimate

according to Regulation (EC) No. 1907/2006 (REACH)

# Ethylenediamine ROTIPURAN® ≥99,5 %, p.a., anhydrous



# article number: 3049

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causin 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an iden fier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	= EC50: in this method, that concentration of test substance which results in a 50 % reduction in eithe growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na tions
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)
SVHC	Substance of Very High Concern
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative



# Ethylenediamine ROTIPURAN® ≥99,5 %, p.a., anhydrous

#### article number: 3049

# Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

# List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H412	Harmful to aquatic life with long lasting effects.

# Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.