acc. to Regulation (EC) No. 1907/2006 (REACH)

Refractive index standard ROTI®Calipure 1,53660 (20 °C)

article number: 3143 date of compilation: 2020-05-15 Version: **2.0 en** Revision: 2022-05-06

Replaces version of: 2020-05-15

Version: (1)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance Refractive index standard ROTI®Calipure

1,53660 (20 °C)

3143 Article number

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory and analytical use

Laboratory chemical

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes

(household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

sicherheit@carlroth.de e-mail (competent person):

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.10	Acute toxicity (oral)	4	Acute Tox. 4	H302
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.7	Reproductive toxicity	2	Repr. 2	H361d

United Kingdom (en) Page 1 / 21

acc. to Regulation (EC) No. 1907/2006 (REACH)



Refractive index standard ROTI®Calipure 1,53660 (20 °C)

article number: 3143

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
3.8R	Specific target organ toxicity - single exposure (respirat- ory tract irritation)	3	STOT SE 3	H335
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
3.9	Specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
3.10	Aspiration hazard	1	Asp. Tox. 1	H304
4.1A	Hazardous to the aquatic environment - acute hazard	1	Aquatic Acute 1	H400
4.1C	Hazardous to the aquatic environment - chronic hazard	1	Aquatic Chronic 1	H410

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS02, GHS07, GHS08, GHS09









Hazard statements

H225 H302	Highly flammable liquid and vapour Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H361d	Suspected of damaging the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H410	Very toxic to aquatic life with long lasting effects

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition
. = . s partagrama, s partagrama, spartagrama and salar ignition
sources. No smoking
P273 Avoid release to the environment
P280 Wear protective gloves/protective clothing/eye protection/face protection

United Kingdom (en) Page 2 / 21

acc. to Regulation (EC) No. 1907/2006 (REACH)



Refractive index standard ROTI®Calipure 1,53660 (20 °C)

article number: 3143

Precautionary statements - response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin P303+P361+P353

with water [or shower]

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

For professional users only

Hazardous ingredients for labelling: Toluene, 1,2-Dichlorobenzene

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 **Substances**

not relevant (mixture)

3.2 **Mixtures**

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
1,2-Dichlorobenzene	CAS No 95-50-1 EC No 202-425-9	≥50	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	! \$	GHS-HC IOELV
Toluene	CAS No 108-88-3 EC No 203-625-9	25 – 50	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 Repr. 2 / H361d STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304		GHS-HC IOELV

Notes

GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/

2008/EC, Annex VI)
Substance with a community indicative occupational exposure limit value

Name of sub- stance	Identifier	Specific Conc. Limits	M-Factors	ATE	Exposure route
1,2-Dichloroben- zene	CAS No 95-50-1	-	-	500 ^{mg} / _{kg}	oral
	EC No 202-425-9				

For full text of abbreviations: see SECTION 16

United Kingdom (en) Page 3 / 21

acc. to Regulation (EC) No. 1907/2006 (REACH)

Refractive index standard ROTI®Calipure 1,53660 (20 °C)

article number: 3143



SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

Following ingestion

Rinse mouth with water (only if the person is conscious). In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Observe aspiration hazard if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard, Vomiting, Irritation, Cough, Dyspnoea, Dizziness, Drowsiness, Narcosis

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂), Hydrogen chloride (HCl), May produce toxic fumes of carbon monoxide if burning.

United Kingdom (en) Page 4 / 21

acc. to Regulation (EC) No. 1907/2006 (REACH)

Refractive index standard ROTI®Calipure 1,53660 (20 °C)

article number: 3143



5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Measures to protect the environment

Avoid release to the environment.

United Kingdom (en) Page 5 / 21

acc. to Regulation (EC) No. 1907/2006 (REACH)

Refractive index standard ROTI®Calipure 1,53660 (20 °C)

article number: 3143

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

Conditions for safe storage, including any incompatibilities 7.2

Keep container tightly closed. Keep in a cool place.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 2 – 8 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
EU	toluene	108-88-3	IOELV	50	192	100	384			Н	2006/15/ EC
EU	1,2-dichlorobenzene	95-50-1	IOELV	20	122	50	306			Н	2000/39/ EC
GB	toluene	108-88-3	WEL	50	191	100	384				EH40/ 2005
GB	1,2-dichlorobenzene (o-dichlorobenzene)	95-50-1	WEL	25	153	50	306				EH40/ 2005

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur

Absorbed through the skin
Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15minute period (unless otherwise specified) H STEL

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified) TWA

Relevant DNELs of components of the mixture									
Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time			
1,2-Dichloroben- zene	95-50-1	DNEL	4,2 mg/m ³	human, inhalat- ory	worker (industry)	chronic - systemic effects			

United Kingdom (en) Page 6 / 21

acc. to Regulation (EC) No. 1907/2006 (REACH)

Refractive index standard ROTI®Calipure 1,53660 (20 °C)

article number: 3143



Relevant DNELs of components of the mixture									
Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time			
1,2-Dichloroben- zene	95-50-1	DNEL	21 mg/m³	human, inhalat- ory	worker (industry)	acute - systemic effects			
1,2-Dichloroben- zene	95-50-1	DNEL	1,2 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects			
1,2-Dichloroben- zene	95-50-1	DNEL	6 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects			
Toluene	108-88-3	DNEL	192 mg/m³	human, inhalat- ory	worker (industry)	chronic - systemic effects			
Toluene	108-88-3	DNEL	384 mg/m³	human, inhalat- ory	worker (industry)	acute - systemic effects			
Toluene	108-88-3	DNEL	192 mg/m³	human, inhalat- ory	worker (industry)	chronic - local ef- fects			
Toluene	108-88-3	DNEL	384 mg/m³	human, inhalat- ory	worker (industry)	acute - local ef- fects			
Toluene	108-88-3	DNEL	384 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects			

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
1,2-Dichloroben- zene	95-50-1	PNEC	0,004 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
1,2-Dichloroben- zene	95-50-1	PNEC	0 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
1,2-Dichloroben- zene	95-50-1	PNEC	4,7 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
1,2-Dichloroben- zene	95-50-1	PNEC	0,177 ^{mg} / kg	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
1,2-Dichloroben- zene	95-50-1	PNEC	0,018 ^{mg} / kg	aquatic organ- isms	marine sediment	short-term (single instance)
1,2-Dichloroben- zene	95-50-1	PNEC	0,033 ^{mg} / kg	terrestrial organ- isms	soil	short-term (single instance)
Toluene	108-88-3	PNEC	0,68 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
Toluene	108-88-3	PNEC	0,68 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
Toluene	108-88-3	PNEC	13,61 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
Toluene	108-88-3	PNEC	16,39 ^{mg} / kg	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
Toluene	108-88-3	PNEC	16,39 ^{mg} / kg	aquatic organ- isms		
Toluene	108-88-3	PNEC	2,89 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)

United Kingdom (en) Page 7 / 21

acc. to Regulation (EC) No. 1907/2006 (REACH)

Refractive index standard ROTI®Calipure 1,53660 (20 °C)



article number: 3143

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

FKM (fluoro rubber)

material thickness

≥0,4 mm

· breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

United Kingdom (en) Page 8 / 21

acc. to Regulation (EC) No. 1907/2006 (REACH)

Refractive index standard ROTI®Calipure 1,53660 (20 °C)

article number: 3143



SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour colourless
Odour characteristic
Melting point/freezing point not determined

Boiling point or initial boiling point and boiling

range

110,6 °C at 1.013 hPa

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit

39 g/m³ (LEL) - 735 g/m³ (UEL) /
1,1 vol% (LEL) - 12 vol% (UEL)

1,1 VO170 (EEE) - 12 VO170 (OI

Flash point 4,4 °C at 1.013 hPa

Auto-ignition temperature 480 °C (auto-ignition temperature (liquids and

gases))

Decomposition temperature not relevant pH (value) not determined Kinematic viscosity not determined

Solubility(ies)

Water solubility not determined

Partition coefficient

Partition coefficient n-octanol/water (log value): this information is not available

Vapour pressure not determined

Density and/or relative density

Density $1,306 \, {}^{9}/_{cm^3}$ at 20 ${}^{\circ}\text{C}$

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

There is no additional information.

Other safety characteristics:

Refractive index 1,532 – 1,542 (20 °C)

United Kingdom (en) Page 9 / 21

acc. to Regulation (EC) No. 1907/2006 (REACH)

Refractive index standard ROTI®Calipure 1,53660 (20 °C)

article number: 3143



SECTION 10: Stability and reactivity

10.1 Reactivity

The mixture contains reactive substance(s). Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Danger of explosion: Perchlorates, Nitric acid, Sulphuric acid, Acetic acid,

Violent reaction with: Mineral acids, Strong acid, strong oxidiser

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

different Rubber articles, plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Harmful if swallowed.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
1,2-Dichlorobenzene	95-50-1	oral	500 ^{mg} / _{kg}

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
1,2-Dichlorobenzene	95-50-1	oral	LD50	>2.000 ^{mg} / _{kg}	rat
1,2-Dichlorobenzene	95-50-1	dermal	LD50	10.000 ^{mg} / _{kg}	rabbit
Toluene	108-88-3	oral	LD50	5.580 ^{mg} / _{kg}	rat
Toluene	108-88-3	inhalation: va- pour	LC50	28,1 ^{mg} / _l /4h	rat

United Kingdom (en) Page 10 / 21

acc. to Regulation (EC) No. 1907/2006 (REACH)



Refractive index standard ROTI®Calipure 1,53660 (20 °C)

article number: 3143

Acute toxicity of	components	of the	mixture
--------------------------	------------	--------	---------

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Toluene	108-88-3	dermal	LD50	>5.000 ^{mg} / _{kg}	rabbit

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

aspiration hazard

• If in eyes

Causes serious eye irritation

• If inhaled

Irritation to respiratory tract, cough, Dyspnoea, fatigue, dizziness, narcosis

• If on skin

causes skin irritation

Other information

none

11.2 Endocrine disrupting properties

None of the ingredients are listed.

11.3 Information on other hazards

There is no additional information.

United Kingdom (en) Page 11 / 21

acc. to Regulation (EC) No. 1907/2006 (REACH)

Refractive index standard ROTI®Calipure 1,53660 (20 °C)

article number: 3143



SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
1,2-Dichlorobenzene	95-50-1	LC50	1,58 ^{mg} / _l	fish	96 h
1,2-Dichlorobenzene	95-50-1	EC50	0,66 ^{mg} / _l	aquatic invertebrates	48 h
1,2-Dichlorobenzene	95-50-1	ErC50	2,2 ^{mg} / _l	algae	96 h
Toluene	108-88-3	LC50	5,5 ^{mg} / _l	fish	96 h
Toluene	108-88-3	EC50	84 ^{mg} / _l	microorganisms	24 h

Aquatic toxicity (chronic) of components of the mixture

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
1,2-Dichlorobenzene	95-50-1	EC50	0,55 ^{mg} / _l	aquatic invertebrates	14 d
1,2-Dichlorobenzene	95-50-1	EC50	10 ^{mg} / _l	algae	3 h
Toluene	108-88-3	LC50	3,78 ^{mg} / _l	aquatic invertebrates	2 d
Toluene	108-88-3	EC50	3,23 ^{mg} / _l	aquatic invertebrates	7 d

Biodegradation

Data are not available.

12.2 Process of degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
1,2-Dichlorobenzene	95-50-1	150 - 230	3,433 (25 °C)	
Toluene	108-88-3	90	2,73 (pH value: 7, 20 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

United Kingdom (en) Page 12 / 21

acc. to Regulation (EC) No. 1907/2006 (REACH)

Refractive index standard ROTI®Calipure 1,53660 (20 °C)

article number: 3143



Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste catalogue ordinance (Germany).

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN	number	or ID	number
---------	--------	-------	--------

ADRRID	UN 3295
IMDG-Code	UN 3295
ICAO-TI	UN 3295

14.2 UN proper shipping name

ADRRID	HYDROCARBONS, LIQUID, N.O.S.
IMDG-Code	HYDROCARBONS, LIQUID, N.O.S.
ICAO-TI	Hydrocarbons, liquid, n.o.s.

14.3 Transport hazard class(es)

ADRRID	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

ADRRID	II
IMDG-Code	II
ICAO-TI	II

14.5 Environmental hazards hazardous to the aquatic environment

United Kingdom (en) Page 13 / 21



acc. to Regulation (EC) No. 1907/2006 (REACH)



Refractive index standard ROTI®Calipure 1,53660 (20 °C)

article number: 3143

Environmentally hazardous substance (aquatic environment):

1,2-Dichlorobenzene

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Proper shipping name HYDROCARBONS, LIQUID, N.O.S.

Particulars in the transport document UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II,

(D/E), environmentally hazardous, special provi-

sion 640D

Classification code F

Danger label(s) 3, "Fish and tree"





Emergency Action Code

Environmental hazards yes (hazardous to the aquatic environment)

Special provisions (SP) 640D

Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

Transport category (TC) 2

Tunnel restriction code (TRC) D/E

Hazard identification No 33

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional information

3YE

Classification code F1

Danger label(s) 3
Fish and tree



Environmental hazards Yes

Hazardous to water

Special provisions (SP) 640D

Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

Transport category (TC) 2

Hazard identification No 33

United Kingdom (en) Page 14 / 21

acc. to Regulation (EC) No. 1907/2006 (REACH)

Refractive index standard ROTI®Calipure 1,53660 (20 °C)



article number: 3143

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name HYDROCARBONS, LIQUID, N.O.S.

Particulars in the shipper's declaration UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II,

4,4°C c.ć., MARINE POLLUŤANŤ

Marine pollutant yes (hazardous to the aquatic environment)

Danger label(s) 3, "Fish and tree"





Special provisions (SP)

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

EmS F-E, S-D

Stowage category B

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Hydrocarbons, liquid, n.o.s.

Particulars in the shipper's declaration UN3295, Hydrocarbons, liquid, n.o.s., 3, II

Environmental hazards yes (hazardous to the aquatic environment)

Danger label(s) 3



Special provisions (SP) A3
Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Seveso Directive

2012/	2012/18/EU (Seveso III)						
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes				
E1	environmental hazards (hazardous to the aquatic environment, cat. 1)	100 200	56)				

Notation

56) Hazardous to the Aquatic Environment in category Acute 1 or Chronic 1

Deco-Paint Directive

United Kingdom (en) Page 15 / 21

acc. to Regulation (EC) No. 1907/2006 (REACH)



Refractive index standard ROTI®Calipure 1,53660 (20 °C)

article number: 3143

VOC content	100 % 1.306 ^g / _l

Industrial Emissions Directive (IED)

VOC content	100 %
VOC content (Water content was discounted)	1.306 ^g / _l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

Pollutant release and transfer registers (PRTR)			
Name of substance CAS No Remarks Threshold for releases to air (kg/year)			
Toluene	108-88-3	(11)	

Legend

Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Toluene	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)	
1,2-Dichlorobenzene	Organohalogen compounds and substances which may form such compounds in the aquatic envir- onment		a)	

Legend

A) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

none of the ingredients are listed

Regulation on drug precursors

Name of substance	CAS No	Classification	CN Code	Threshold level
Toluene	108-88-3	Category 3	2902 30 00	

Regulation on substances that deplete the ozone layer (ODS)

none of the ingredients are listed

United Kingdom (en) Page 16 / 21

⁽¹¹⁾ Single pollutants are to be reported if the threshold for BTEX (the sum parameter of benzene, toluene, ethyl benzene, xylenes) is exceeded

acc. to Regulation (EC) No. 1907/2006 (REACH)

Refractive index standard ROTI®Calipure 1,53660 (20 °C)





Regulation concerning the export and import of hazardous chemicals (PIC)

none of the ingredients are listed

Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

National regulations(GB)

Restrictions according to GB REACH, Annex 17

none of the ingredients are listed

Dangerous substances with restrictions (GB REACH, Annex 17)			
Name of substance	Name acc. to inventory	CAS No	No
Refractive index standard	this product meets the criteria for classi- fication in accordance with Regulation No 1272/2008/EC		3

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

UN Convention against Illicit Traffic in Narcotic Drugs and Psychotropic Substances

Name of substance	CAS No	Listed in	HS code
Toluene	108-88-3	Table II	2902.30

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

Australian Inventory of Industrial Chemicals Chemical Inventory and Control Regulation List of Existing and New Chemical Substances (CSCL-ENCS) AIIC CICR CSCL-ENCS DSL ECSI

Domestic Substances List (DSL) EC Substance Inventory (EINECS, ELINCS, NLP)

United Kingdom (en) Page 17 / 21

acc. to Regulation (EC) No. 1907/2006 (REACH)



Refractive index standard ROTI®Calipure 1,53660 (20 °C)

article number: 3143

Legend

IECSC INSQ Inventory of Existing Chemical Substances Produced or Imported in China National Inventory of Chemical Substances Inventory of Existing and New Chemical Substances (ISHA-ENCS)

ISHA-ENCS

KECI Korea Existing Chemicals Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances
TCSI Taiwan Chemical Substance Inventory

Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation:

Restructuring: section 9, section 14


Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1	The most important adverse physicochemical, human health and environmental effects: Narcotic effects.	The most important adverse physicochemical, human health and environmental effects: Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Danger		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2	contains: Toluene, 1,2-Dichlorobenzene		yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

United Kingdom (en) Page 18 / 21

acc. to Regulation (EC) No. 1907/2006 (REACH)

Refractive index standard ROTI®Calipure 1,53660 (20 °C)

article number: 3143





	Descriptions of used abbreviations
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
Acute Tox.	Acute toxicity
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de naviga- tion intérieures (European Agreement concerning the International Carriage of Dangerous Goods by In- land Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CN Code	Combined Nomenclature
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations

United Kingdom (en) Page 19 / 21

acc. to Regulation (EC) No. 1907/2006 (REACH)

ROTH

Refractive index standard ROTI®Calipure 1,53660 (20 °C)

article number: 3143

Abbr.	Descriptions of used abbreviations
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
Repr.	Reproductive toxicity
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

United Kingdom (en) Page 20 / 21

acc. to Regulation (EC) No. 1907/2006 (REACH)

ROTH

Refractive index standard ROTI®Calipure 1,53660 (20 °C)

article number: 3143

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United Kingdom (en) Page 21 / 21