acc. to Regulation (EC) No. 1907/2006 (REACH)

Molybdenum (VI) oxide ROTI®METIC 99,98% (3N8)

article number: **4548**Version: **3.0 en**date of compilation: 2017-07-25
Revision: 2022-10-19

Replaces version of: 2021-12-01

Version: (2)



1.1 Product identifier

Identification of the substance Molybdenum (VI) oxide ROTI®METIC 99,98%

(3N8)

Article number 4548

EC number 215-204-7
CAS number 1313-27-5

Alternative name(s) Molybdenum trioxide

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes

(household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe

Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

United Kingdom (en) Page 1 / 14

acc. to Regulation (EC) No. 1907/2006 (REACH)



Molybdenum (VI) oxide ROTI®METIC 99,98% (3N8)

article number: 4548

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.6	Carcinogenicity		Carc. 2	H351
3.8R	Specific target organ toxicity - single exposure (respirat- ory tract irritation)		STOT SE 3	H335

For full text of abbreviations: see SECTION 16

2.2 Label elements

Labelling

Signal word Warning

Pictograms

GHS07, GHS08





Hazard statements

H319 Causes serious eye irritation H335 May cause respiratory irritation H351 Suspected of causing cancer

Precautionary statements

Precautionary statements - prevention

P260 Do not breathe dust

P280 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary statements - response

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P308+P313 IF exposed or concerned: Get medical advice/attention

For professional users only

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

United Kingdom (en) Page 2 / 14

acc. to Regulation (EC) No. 1907/2006 (REACH)

Molybdenum (VI) oxide ROTI®METIC 99,98% (3N8)

article number: 4548



SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance Molybdenum (VI) oxide

Molecular formula MoO₃

Molar mass 143,9 g/_{mol}
CAS No 1313-27-5

EC No 215-204-7

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

Following ingestion

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

4.2 Most important symptoms and effects, both acute and delayed

Irritation, Cough, Dyspnoea

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water, foam, alcohol resistant foam, dry extinguishing powder, ABC-powder

United Kingdom (en) Page 3 / 14

acc. to Regulation (EC) No. 1907/2006 (REACH)

Molybdenum (VI) oxide ROTI®METIC 99,98% (3N8)

article number: 4548



water jet



Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe dust.

Environmental precautions

Keep away from drains, surface and ground water.

6.3

Covering of drains. Take up mechanically.

Advice on how to clean up a spill

Other information relating to spills and releases

Place in appropriate containers for disposal.

Reference to other sections 6.4

patible materials: see section 10. Disposal considerations: see section 13.

Precautions for safe handling 7.1

Provision of sufficient ventilation. Avoid exposure. Avoid dust formation.

Advice on general occupational hygiene

Conditions for safe storage, including any incompatibilities

Incompatible substances or mixtures

Observe hints for combined storage.

United Kingdom (en) Page 4 / 14



5.2 Special hazards arising from the substance or mixture

Non-combustible.

Advice for firefighters 5.3

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures 6.1



For non-emergency personnel

6.2

Methods and material for containment and cleaning up

Advice on how to contain a spill

Take up mechanically. Control of dust.

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incom-

SECTION 7: Handling and storage

Measures to prevent fire as well as aerosol and dust generation

Removal of dust deposits.

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2

Store in a dry place.

acc. to Regulation (EC) No. 1907/2006 (REACH)

Molybdenum (VI) oxide ROTI®METIC 99,98% (3N8)

article number: 4548

Consideration of other advice:

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Identifi- er	TWA [mg/ m³]	STEL [mg/ m³]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
GB	dust		WEL	10			i	EH40/2005
GB	dust		WEL	4			r	EH40/2005

Notation Ceiling-C

Ceiling value is a limit value above which exposure should not occur Inhalable fraction

Respirable fraction

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-

minute period (unless otherwise specified)

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified) TWA

Human health values

Relevant DNELs and other threshold levels **Threshold Endpoint** Protection goal, **Used in Exposure time** level route of exposure DNFI 16,76 mg/m³ human, inhalatory worker (industry) chronic - systemic effects DNEL 3 mg/m³ human, inhalatory chronic - local effects worker (industry)

8.2 **Exposure controls**

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



United Kingdom (en) Page 5 / 14



acc. to Regulation (EC) No. 1907/2006 (REACH)

Molybdenum (VI) oxide ROTI®METIC 99,98% (3N8)

article number: 4548



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 °C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

NBR (Nitrile rubber)

material thickness

>0,11 mm

breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection





Respiratory protection necessary at: Dust formation. Particulate filter device (EN 143). P2 (filters at least 94 % of airborne particles, colour code: White).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state solid
Form powder

Colour white - light green

Odour odourless

Melting point/freezing point 802 °C (ECHA)

Boiling point or initial boiling point and boiling 1.155 °C at 1.013 hPa (ECHA)

range

Flammability non-combustible
Lower and upper explosion limit not determined
Flash point not applicable
Auto-ignition temperature not determined
Decomposition temperature not relevant
pH (value) not applicable

United Kingdom (en) Page 6 / 14

acc. to Regulation (EC) No. 1907/2006 (REACH)

Molybdenum (VI) oxide ROTI®METIC 99,98% (3N8)

article number: 4548

Kinematic viscosity not relevant

Solubility(ies)

Water solubility $1 \, {\rm g/_l}$ at 20 °C (ECHA)

Partition coefficient

Partition coefficient n-octanol/water (log value): not relevant (inorganic)

Vapour pressure not determined

Density and/or relative density

Density 4,7 $^{9}/_{cm^{3}}$ at 25 $^{\circ}$ C

Relative vapour density information on this property is not available

Particle characteristics No data available.

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard hazard classes acc. to GHS (physical hazards): not relevant

Other safety characteristics: There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is not reactive under normal ambient conditions.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: Potassium, Magnesium, Sodium, Lithium, Chlorine trifluoride (CIF3)., Reducing agents

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

United Kingdom (en) Page 7 / 14



acc. to Regulation (EC) No. 1907/2006 (REACH)

Molybdenum (VI) oxide ROTI®METIC 99,98% (3N8)

article number: 4548



ECHA

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	4.233 ^{mg} / _{kg}	rat		ECHA
inhalation: dust/ mist	LC50	>5,1 ^{mg} / _l /4h	rat		ECHA

>2.000 ^{mg}/_{kg}

Skin corrosion/irritation

dermal

Shall not be classified as corrosive/irritant to skin.

LD50

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

Data are not available.

• If in eyes

Causes serious eye irritation

• If inhaled

Irritation to respiratory tract, cough, Dyspnoea

• If on skin

United Kingdom (en) Page 8 / 14

acc. to Regulation (EC) No. 1907/2006 (REACH)

Molybdenum (VI) oxide ROTI®METIC 99,98% (3N8)

article number: 4548

Data are not available.

Other information

none

11.2 Endocrine disrupting properties

Not listed.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)					
Endpoint	Value	Species	Source	Exposure time	
LC50	577 ^{mg} / _l	fish	ECHA	96 h	

Aquatic toxicity (chronic)				
Endpoint	Value	Species	Source	Exposure time
EC50	1.100 ^{mg} / _l	microorganisms	ECHA	30 min

Biodegradation

The methods for determining the biological degradability are not applicable to inorganic substances.

12.2 Process of degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Not listed.

12.7 Other adverse effects

Data are not available.

United Kingdom (en) Page 9 / 14



acc. to Regulation (EC) No. 1907/2006 (REACH)

Molybdenum (VI) oxide ROTI®METIC 99,98% (3N8)

article number: 4548



SECTION 13: Disposal considerations

Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Properties of waste which render it hazardous

HP 4 irritant - skin irritation and eye damage

HP 5 HP 7 specific target organ toxicity (STOT)/aspiration toxicity

carcinogenic

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

	14.1	UN number or ID number	not subject to transport regulations
--	------	------------------------	--------------------------------------

14.2 UN proper shipping name not assigned

14.3 Transport hazard class(es) none

14.4 Packing group not assigned

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Not subject to ADR, RID and ADN.

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

United Kingdom (en) Page 10 / 14

acc. to Regulation (EC) No. 1907/2006 (REACH)

Molybdenum (VI) oxide ROTI®METIC 99,98% (3N8)

article number: 4548



SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Seveso Directive

2012/	2012/18/EU (Seveso III)				
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes		
	not assigned				

Deco-Paint Directive

VOC content	0 % 0 ^g / _l

Industrial Emissions Directive (IED)

VOC content	0 %
VOC content	0 ^g / _l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Molybdenum (VI) oxide	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)	
Molybdenum (VI) oxide	Metals and their compounds		a)	

Legend

A) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

not listed

Regulation on drug precursors

not listed

United Kingdom (en) Page 11 / 14

acc. to Regulation (EC) No. 1907/2006 (REACH)

Molybdenum (VI) oxide ROTI®METIC 99,98% (3N8)

article number: 4548



Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list

not listed

Restrictions according to GB REACH, Annex 17

not listed

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed

Legend

Australian Inventory of Industrial Chemicals Chemical Inventory and Control Regulation List of Existing and New Chemical Substances (CSCL-ENCS) AIIC CICR CSCL-ENCS DSL ECSI IECSC

DSL Domestic Substances List (DSL)
ECSI EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC Inventory of Existing Chemical Substances Produced or Imported in China INSQ National Inventory of Chemical Substances
KECI Korea Existing Chemicals Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances
TCSI Taiwan Chemical Substances Inventory

Taiwan Chemical Substance Inventory TCSI TSCA

Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

United Kingdom (en) Page 12 / 14

acc. to Regulation (EC) No. 1907/2006 (REACH)

Molybdenum (VI) oxide ROTI®METIC 99,98% (3N8)

article number: 4548



SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation:

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Warning		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navig tion intérieures (European Agreement concerning the International Carriage of Dangerous Goods by land Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concer ing the International Carriage of Dangerous Goods by Road)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substance
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causin 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an ide fier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)

United Kingdom (en) Page 13 / 14

acc. to Regulation (EC) No. 1907/2006 (REACH)

Molybdenum (VI) oxide ROTI®METIC 99,98% (3N8)

article number: 4548



Abbr.	Descriptions of used abbreviations
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United Kingdom (en) Page 14 / 14