acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid ethyl ester ROTIPURAN® ≥99,5 %, p.a., ACS, ISO



Replaces version of: 2022-12-16

Version: (4)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance Acetic acid ethyl ester ROTIPURAN® ≥99,5 %,

p.a., ACS, ISO

Article number 6784

Index No (GB CLP) 607-022-00-5
EC number 205-500-4
CAS number 141-78-6
Alternative name(s) Ethyl acetate

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for private purposes (household).

Food, drink and animal feedingstuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

sheet:

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

| Name | Street | Postal code/city | Telephone | Website |
|--|-----------|----------------------|--------------|---------|
| National Poisons Information Service City Hospital | Dudley Rd | B187QH Birmingham | 844 892 0111 | |

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

United Kingdom (en) Page 1 / 18

acc. to Regulation (EC) No. 1907/2006 (REACH)



Acetic acid ethyl ester ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 6784

Classification acc. to GHS

| Section | Hazard class | Cat- egory | Hazard class and category | Hazard statement |
|---------|---|---------------|---------------------------|---------------------|
| 2.6 | Flammable liquid | 2 | Flam. Liq. 2 | H225 |
| 3.3 | Serious eye damage/eye irritation | 2 | Eye Irrit. 2 | H319 |
| 3.8D | Specific target organ toxicity - single exposure (narcotic effects, drowsiness) | 3 | STOT SE 3 | H336 |

Supplemental hazard information

| Code | Supplemental hazard information |
|--------|--|
| EUH066 | repeated exposure may cause skin dryness or cracking |

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS02, GHS07



Hazard statements

| H225 | Highly flammable liquid and vapour |
|------|------------------------------------|
| H319 | Causes serious eye irritation |
| H336 | May cause drowsiness or dizziness |

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking

P243 Take action to prevent static discharges

Precautionary statements - response

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

United Kingdom (en) Page 2 / 18

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid ethyl ester ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 6784

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of \geq 0,1%.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance Acetic acid ethyl ester

Molecular formula $C_4H_8O_2$ Molar mass $88,11~^g/_{mol}$ CAS No 141-78-6 EC No 205-500-4 Index No (GB CLP) 607-022-00-5

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Following inhalation: Headaches and dizziness may occur, Breathing difficulties, Dizziness, Drowsiness, Narcosis,

Following skin contact: Has degreasing effect on the skin, Irritant effects,

After eye contact: Irritation,

Following ingestion: Nausea, Aspiration hazard, Vomiting

4.3 Indication of any immediate medical attention and special treatment needed

none

United Kingdom (en) Page 3 / 18

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid ethyl ester ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 6784



SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

United Kingdom (en) Page 4 / 18

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid ethyl ester ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 6784



Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store in a dry place. Protect against: Direct light irradiation. May cause decomposition by long-term light influence.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

United Kingdom (en) Page 5 / 18



6.4 Reference to other sections

acc. to Regulation (EC) No. 1907/2006 (REACH)



Acetic acid ethyl ester ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 6784

Occupational exposure limit values (Workplace Exposure Limits)

| Cou ntr y | Name of agent | CAS No | Identi- fier | TW A [pp m] | TWA [mg/ m³] | STE L [pp m] | STEL [mg/ m³] | Ceil ing- C [pp m] | Ceil- ing-C [mg/ m³] | Nota- tion | Source |
|-----------------|---------------|----------|-----------------|----------------------|--------------------|-----------------------|---------------------|--------------------------------|-------------------------------|---------------|-----------------|
| EU | ethyl acetate | 141-78-6 | IOELV | 200 | 734 | 400 | 1.468 | | | | 2017/ 164/EU |
| GB | ethyl acetate | 141-78-6 | WEL | 200 | 734 | 400 | 1.468 | | | | EH40/ 2005 |

Notation

Ceiling-C STEL

TWA

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Human health values

Relevant DNELs and other threshold levels

| Endpoint | Threshold level | Protection goal, route of exposure | Used in | Exposure time |
|----------|---------------------|------------------------------------|-------------------|----------------------------|
| DNEL | 734 mg/m³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| DNEL | 1.468 mg/m³ | human, inhalatory | worker (industry) | acute - systemic effects |
| DNEL | 734 mg/m³ | human, inhalatory | worker (industry) | chronic - local effects |
| DNEL | 1.468 mg/m³ | human, inhalatory | worker (industry) | acute - local effects |
| DNEL | 63 mg/kg bw/ day | human, dermal | worker (industry) | chronic - systemic effects |

Environmental values

Relevant PNECs and other threshold levels

| End- point | Threshold level | Organism | Environmental com- partment | Exposure time |
|---------------|-------------------------------------|-----------------------|---------------------------------|------------------------------|
| PNEC | 1,65 ^{mg} / _l | aquatic organisms | water | intermittent release |
| PNEC | 0,24 ^{mg} / _l | aquatic organisms | freshwater | short-term (single instance) |
| PNEC | 0,024 ^{mg} / _l | aquatic organisms | marine water | short-term (single instance) |
| PNEC | 650 ^{mg} / _l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |
| PNEC | 1,15 ^{mg} / _{kg} | aquatic organisms | freshwater sediment | short-term (single instance) |
| PNEC | 0,115 ^{mg} / _{kg} | aquatic organisms | marine sediment | short-term (single instance) |
| PNEC | 0,148 ^{mg} / _{kg} | terrestrial organisms | soil | short-term (single instance) |

8.2 **Exposure controls**

United Kingdom (en) Page 6 / 18

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid ethyl ester ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: **6784**



Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 °C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

Butyl caoutchouc (butyl rubber)

material thickness

0,7mm

breakthrough times of the glove material

>120 minutes (permeation: level 4)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

United Kingdom (en) Page 7 / 18

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid ethyl ester ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 6784



SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour colourless

Odour fruity

Odour threshold 50 ppm

Melting point/freezing point -83,6 °C at 1.013 hPa (ECHA)

Boiling point or initial boiling point and boiling

range

77,1 °C at 1.013 hPa (ECHA)

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 73 g/m³ (LEL) - 470 g/m³ (UEL) /

2,2 vol% (LEL) - 11,5 vol% (UEL)

Flash point -4 °C at 1.013 hPa (ECHA)

Auto-ignition temperature 427 °C at 1.013 hPa (ECHA) (auto-ignition temper-

ature (liquids and gases))

Decomposition temperature not relevant

pH (value) not determined

Kinematic viscosity 0,501 mm²/s at 20 °C

Dynamic viscosity 0,451 mPa s at 20 °C

Solubility(ies)

Water solubility 80 g/1 at 25 °C (ECHA)

Partition coefficient

Partition coefficient n-octanol/water (log value): 0,68 (pH value: 7, 25 °C) (ECHA)

Vapour pressure 97 hPa at 20 °C

Density and/or relative density

Density $0,9003 \, {}^{\rm g}/{}_{\rm cm^3}$ at 20 °C (ECHA)

Relative vapour density 3,04 (air = 1)

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

classes:

United Kingdom (en) Page 8 / 18

acc. to Regulation (EC) No. 1907/2006 (REACH)



Acetic acid ethyl ester ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 6784

Other safety characteristics:

Gas group (explosion group) IIA

Maximum Experimental Safe Gap value; MESG >

0,9 mm

Maximum explosion pressure 9,5 bar

Refractive index 1,372

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Exothermic reaction with: Fluorine, strong oxidiser, **Danger of explosion:** Alkali metals, Alkaline earth metal,

Violent reaction with: Strong alkali, Strong acid

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Direct light irradiation. Protect from moisture.

10.5 Incompatible materials

different plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity

| Exposure route | Endpoint | Value | Species | Method | Source |
|----------------|----------|---------------------------------------|---------|--------|--------|
| oral | LD50 | 5.620 ^{mg} / _{kg} | rat | | TOXNET |
| dermal | LD50 | >20.000 ^{mg} / _{kg} | rabbit | | ECHA |

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

United Kingdom (en) Page 9 / 18

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid ethyl ester ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: **6784**



Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

nausea, vomiting, aspiration hazard

If in eyes

Causes serious eye irritation, Irritating to eyes

If inhaled

fatigue, narcosis, headache, vertigo, breathing difficulties, dizziness, drowsiness, narcosis

• If on skir

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation)

Other information

none

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

United Kingdom (en) Page 10 / 18

acc. to Regulation (EC) No. 1907/2006 (REACH)



Acetic acid ethyl ester ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 6784

Aquatic toxicity (acute)

| Endpoint | Value | Species | Source | Exposure time |
|----------|----------------------------------|---------|--------|------------------|
| LC50 | 230 ^{mg} / _l | fish | ECHA | 96 h |
| EC50 | 220 ^{mg} / _l | fish | ECHA | 96 h |

12.2 Persistence and degradability

Theoretical Oxygen Demand: 1,816 $^{\rm mg}/_{\rm mg}$ Theoretical Carbon Dioxide: 1,998 $^{\rm mg}/_{\rm mg}$

Biodegradation

The substance is readily biodegradable.

Process of degradability

| Process | Degradation rate | Time |
|------------------|------------------|------|
| biotic/abiotic | 100 % | 28 d |
| oxygen depletion | 62 % | 5 d |

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

| n-octanol/water (log KOW) | 0,68 (pH value: 7, 25 °C) (ECHA) |
|---------------------------|----------------------------------|
| BCF | 30 (ECHA) |

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of \geq 0,1%.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

United Kingdom (en) Page 11 / 18

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid ethyl ester ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: **6784**



Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Properties of waste which render it hazardous

HP3 flammable

HP 4 irritant - skin irritation and eye damage

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number or ID number

| ADRRID | UN 1173 |
|-----------|---------|
| IMDG-Code | UN 1173 |
| ICAO-TI | UN 1173 |

14.2 UN proper shipping name

| ADRRID | ETHYL ACETATE |
|-----------|---------------|
| IMDG-Code | ETHYL ACETATE |
| ICAO-TI | Ethyl acetate |

14.3 Transport hazard class(es)

| ADRRID | 3 |
|-----------|---|
| IMDG-Code | 3 |
| ICAO-TI | 3 |

14.4 Packing group

| ADRRID | II |
|-----------|----|
| IMDG-Code | II |
| ICAO-TI | II |

14.5 Environmental hazards non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

United Kingdom (en) Page 12 / 18

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid ethyl ester ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 6784



Proper shipping name ETHYL ACETATE

Particulars in the transport document UN1173, ETHYL ACETATE, 3, II, (D/E)

Classification code F1
Danger label(s) 3



Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
Transport category (TC) 2
Tunnel restriction code (TRC) D/E
Hazard identification No 33
Emergency Action Code 3YE

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional information

Classification code F1

Danger label(s) 3



Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
Transport category (TC) 2
Hazard identification No 33

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name ETHYL ACETATE

Particulars in the shipper's declaration UN1173, ETHYL ACETATE, 3, II, -4°C c.c.

Marine pollutant Danger label(s) 3



Special provisions (SP)
Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

EmS F-E, S-D

Stowage category B

United Kingdom (en) Page 13 / 18



acc. to Regulation (EC) No. 1907/2006 (REACH)



Acetic acid ethyl ester ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 6784

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Ethyl acetate

Particulars in the shipper's declaration UN1173, Ethyl acetate, 3, II

Danger label(s) 3



Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Seveso Directive

| 2012/18/EU (Seveso III) | | | | |
|-------------------------|--|-------|--------|-----|
| No | No Dangerous substance/hazard categories Qualifying quantity (tonnes) for the application of lower and upper-tier requirements | | Notes | |
| P5c | flammable liquids (cat. 2, 3) | 5.000 | 50.000 | 51) |

Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

Deco-Paint Directive

| VOC content | 100 % |
|--|-----------------------------------|
| VOC content (Water content was discounted) | 900,3 ^g / _l |

Industrial Emissions Directive (IED)

| VOC content | 100 % |
|--|-----------------------------------|
| VOC content (Water content was discounted) | 900,3 ^g / _l |

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Water Framework Directive (WFD)

not listed

Regulation on the marketing and use of explosives precursors

not listed

Regulation on drug precursors

not listed

United Kingdom (en) Page 14 / 18

acc. to Regulation (EC) No. 1907/2006 (REACH)



Acetic acid ethyl ester ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 6784

Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list not listed

Restrictions according to GB REACH, Annex 17

| Dangerous substances with restrictions (GB REACH, Annex 17) | | | |
|---|--|--------|----|
| Name of substance | Name acc. to inventory | CAS No | No |
| Acetic acid ethyl ester | this product meets the criteria for classi- fication in accordance with Regulation No 1272/2008/EC | | 3 |
| Acetic acid ethyl ester | flammable / pyrophoric | | 40 |

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

| Country | Inventory | Status |
|---------|------------|------------------------------|
| AU | AIIC | substance is listed |
| CA | DSL | substance is listed |
| CN | IECSC | substance is listed |
| EU | ECSI | substance is listed |
| EU | REACH Reg. | substance is listed |
| JP | CSCL-ENCS | substance is listed |
| KR | KECI | substance is listed |
| MX | INSQ | substance is listed |
| NZ | NZIoC | substance is listed |
| PH | PICCS | substance is listed |
| TR | CICR | substance is listed |
| TW | TCSI | substance is listed |
| US | TSCA | substance is listed (ACTIVE) |
| VN | NCI | substance is listed |

Legend

AIIC Australian Inventory of Industrial Chemicals CICR

Chemical Inventory and Control Regulation
List of Existing and New Chemical Substances (CSCL-ENCS)
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP) CSCL-ENCS DSL ECSI

United Kingdom (en) Page 15 / 18

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid ethyl ester ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 6784

Legend

IECSC INSQ Inventory of Existing Chemical Substances Produced or Imported in China National Inventory of Chemical Substances Korea Existing Chemicals Inventory

NCI National Chemical Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances
TCSI Taiwan Chemical Substance Inventory

Toxic Substance Control Act

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

| Section | Former entry (text/value) | Actual entry (text/value) | Safety- relev- ant |
|---------|--|--|--------------------------|
| 2.3 | | Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of ≥ 0,1%. | yes |
| 15.1 | VOC content: 100 % 900,3 ⁹ / _I | VOC content: 100 % | yes |
| 15.1 | | VOC content (Water content was discounted): 900,3 ⁹ / _I | yes |
| 15.1 | | National inventories: change in the listing (table) | yes |

Abbreviations and acronyms

| Abbr. | Descriptions of used abbreviations |
|-------------|--|
| 2017/164/EU | Commission Directive establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU |
| ADR | Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road) |
| BCF | Bioconcentration factor |
| CAS | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances) |
| Ceiling-C | Ceiling value |
| DGR | Dangerous Goods Regulations (see IATA/DGR) |
| DNEL | Derived No-Effect Level |
| EC50 | Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval |
| EC No | The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union) |
| EH40/2005 | EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/) |
| EINECS | European Inventory of Existing Commercial Chemical Substances |
| ELINCS | European List of Notified Chemical Substances |

United Kingdom (en) Page 16 / 18

acc. to Regulation (EC) No. 1907/2006 (REACH)

Acetic acid ethyl ester ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 6784



| Abbr. | Descriptions of used abbreviations |
|-----------|--|
| EmS | Emergency Schedule |
| GB CLP | The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended) |
| GB REACH | The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended) |
| GHS | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations |
| IATA | International Air Transport Association |
| IATA/DGR | Dangerous Goods Regulations (DGR) for the air transport (IATA) |
| ICAO | International Civil Aviation Organization |
| ICAO-TI | Technical instructions for the safe transport of dangerous goods by air |
| IMDG | International Maritime Dangerous Goods Code |
| IMDG-Code | International Maritime Dangerous Goods Code |
| index No | The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 |
| IOELV | Indicative occupational exposure limit value |
| LC50 | Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval |
| LD50 | Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval |
| LEL | Lower explosion limit (LEL) |
| NLP | No-Longer Polymer |
| PBT | Persistent, Bioaccumulative and Toxic |
| PNEC | Predicted No-Effect Concentration |
| ppm | Parts per million |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals |
| RID | Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail) |
| STEL | Short-term exposure limit |
| TWA | Time-weighted average |
| UEL | Upper explosion limit (UEL) |
| VOC | Volatile Organic Compounds |
| vPvB | Very Persistent and very Bioaccumulative |
| WEL | Workplace exposure limit |

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

United Kingdom (en) Page 17 / 18

acc. to Regulation (EC) No. 1907/2006 (REACH)



Acetic acid ethyl ester ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 6784

List of relevant phrases (code and full text as stated in section 2 and 3)

| Code | Text |
|------|-------------------------------------|
| H225 | Highly flammable liquid and vapour. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United Kingdom (en) Page 18 / 18