acc. to Regulation (EC) No. 1907/2006 (REACH)

Diisobutyl ketone ≥94 % pure

article number: 7653 Version: **3.0 en** Revision: 2022-08-01

Replaces version of: 2019-06-21

Version: (2)



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance **Diisobutyl ketone** ≥94 % pure

Article number 7653

EC number 203-620-1 CAS number 108-83-8

Alternative name(s) 2,6-dimethylheptan-4-one

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Industrial uses Professional uses

Formulation [mixing] of preparations and/or re-

packaging (excluding alloys)

Feedstock use Intermediate

Use in cleaning agents

sicherheit@carlroth.de

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes

(household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr, 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

e-mail (competent person):

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

United Kingdom (en) Page 1 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Diisobutyl ketone ≥94 % pure

article number: 7653



SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class		Hazard class and category	Hazard statement
2.6	Flammable liquid	3	Flam. Liq. 3	H226
3.8R	3.8R Specific target organ toxicity - single exposure (respiratory tract irritation)		STOT SE 3	H335

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

Signal word Warning

Pictograms

GHS02, GHS07



Hazard statements

H226 Flammable liquid and vapour H335 May cause respiratory irritation

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking

P261 Avoid breathing mist/vapours

P280 Wear protective gloves/eye protection/face protection

Precautionary statements - response

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing

P312 Call a POISON CENTRE/doctor if you feel unwell

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

United Kingdom (en) Page 2 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Diisobutyl ketone ≥94 % pure

article number: 7653



SECTION 3: Composition/information on ingredients

3.1 Substances

EC No

Name of substance Diisobutyl ketone

Substance, Specific Conc. Limits, M-factors, ATE

Specific Conc. Limits	M-Factors	ATE	Exposure route
STOT SE 3; H335: C ≥ 10 %	-	-	

203-620-1

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In all cases of doubt, or when symptoms persist, seek medical advice.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Irritation, Cough, Dyspnoea, Narcosis

4.3 Indication of any immediate medical attention and special treatment needed

none

United Kingdom (en) Page 3 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Diisobutyl ketone ≥94 % pure

article number: 7653



SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

United Kingdom (en) Page 4 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Diisobutyl ketone ≥94 % pure

article number: 7653



6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
GB	2,6-dimethylheptan- 4-one	108-83-8	WEL	25	148						EH40/ 2005

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur

United Kingdom (en) Page 5 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Diisobutyl ketone ≥94 % pure

article number: 7653



Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) **STEL**

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 **TWA**

hours time-weighted average (unless otherwise specified)

Human health values

Relevant DNE	Relevant DNELs and other threshold levels						
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time			
DNEL	53 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects			
DNEL	7,7 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic effects			

Environmental values

Relevant	Relevant PNECs and other threshold levels						
End- point	Threshold level	Organism	Environmental compartment	Exposure time			
PNEC	0,03 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)			
PNEC	0,003 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)			
PNEC	2,55 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)			
PNEC	0,46 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)			
PNEC	0,046 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)			
PNEC	0,075 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)			

8.2 **Exposure controls**

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection.

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply

United Kingdom (en) Page 6 / 17



acc. to Regulation (EC) No. 1907/2006 (REACH)

Diisobutyl ketone ≥94 % pure

article number: 7653



only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

NBR (Nitrile rubber)

material thickness

>0,3 mm

breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid
Colour colourless
Odour like esters

Melting point/freezing point -46 °C at 1.013 hPa (ECHA) Boiling point or initial boiling point and boiling range -46 °C at 1.013 hPa (ECHA)

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 47 g/m³ (LEL) - 365 g/m³ (UEL) / 0,8 vol% (LEL) - 6,2 vol% (UEL)

Flash point 49 °C at 1.013 hPa (c.c.) (ECHA)

Auto-ignition temperature 345 °C at 1.013 hPa (ECHA)

Solubility(ies)

Water solubility $0.5 \, {}^{9}/_{1}$ at 20 ${}^{\circ}$ C

United Kingdom (en) Page 7 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Diisobutyl ketone ≥94 % pure

article number: 7653

Partition coefficient

Partition coefficient n-octanol/water (log value): 3,71 (25 °C) (ECHA)

Soil organic carbon/water (log KOC) 2,07 (ECHA)

Vapour pressure 1,6 hPa at 20 °C

9,8 hPa at 50 °C

Density and/or relative density

Density $0.804 - 0.813 \, ^{9}/_{cm^{3}}$

Relative vapour density 4,91 (air = 1)

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

There is no additional information.

Other safety characteristics:

Surface tension 22,8 ^{dyn}/_{cm} (25 °C) (ECHA)

Refractive index 1,414

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition.

If heated

Risk of ignition. Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

aluminium, plastics, rubber, natural, Butyl caoutchouc (butyl rubber)

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

United Kingdom (en) Page 8 / 17



acc. to Regulation (EC) No. 1907/2006 (REACH)

Diisobutyl ketone ≥94 % pure

article number: 7653



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute	toxicity	

Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	>2.000 ^{mg} / _{kg}	rat		ECHA
inhalation: vapour	LC50	>14,5 ^{mg} / _I /4h	rat		ECHA
dermal	LD50	>2.000 ^{mg} / _{kg}	rat		ECHA

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

vomiting, nausea

• If in eyes

slightly irritant

• If inhaled

Irritation to respiratory tract, cough, Dyspnoea

• If on skin

has degreasing effect on the skin

United Kingdom (en) Page 9 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Diisobutyl ketone ≥94 % pure

article number: 7653



Liver and kidney damage, Headache, Abdominal pain, Narcosis, Nausea, Vertigo, Dizziness, Drowsiness, Vomiting

11.2 Endocrine disrupting properties

Not listed.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)

Endpoint	Value	Species	Source	Exposure time
LC50	30 ^{mg} / _l	fish	ECHA	24 h
EC50	55,6 ^{mg} / _l	aquatic invertebrates	ECHA	24 h
ErC50	46,9 ^{mg} / _l	algae	ECHA	72 h

Biodegradation

The substance is readily biodegradable.

12.2 Process of degradability

Theoretical Oxygen Demand: 2,924 ^{mg}/_{mg} Theoretical Carbon Dioxide: 2,785 ^{mg}/_{mg}

Process of degradability

Process	Degradation rate	Time
biotic/abiotic	88 %	20 d
oxygen depletion	4 %	5 d

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	3,71 (25 °C) (ECHA)
BCF	130 (ECHA)

12.4 Mobility in soil

The Organic Carbon normalised adsorption coefficient	2,07 (ECHA)
--	-------------

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Not listed.

United Kingdom (en) Page 10 / 17



acc. to Regulation (EC) No. 1907/2006 (REACH)

Diisobutyl ketone ≥94 % pure

article number: 7653

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste catalogue ordinance (Germany).

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1	UN	number	or ID	number

ADRRID	UN 1157
IMDG-Code	UN 1157
ICAO-TI	UN 1157

14.2 UN proper shipping name

ADRRID	DIISOBUTYL KETONE
IMDG-Code	DIISOBUTYL KETONE
ICAO-TI	Diisobutyl ketone

14.3 Transport hazard class(es)

ADRRID	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

ADRRID	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

United Kingdom (en) Page 11 / 17



acc. to Regulation (EC) No. 1907/2006 (REACH)

Diisobutyl ketone ≥94 % pure

article number: 7653



14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Proper shipping name DIISOBUTYL KETONE

Particulars in the transport document UN1157, DIISOBUTYL KETONE, 3, III, (D/E)

Classification code F1
Danger label(s) 3



Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional information

Classification code F1

Danger label(s) 3



Excepted quantities (EQ) E1
Limited quantities (LQ) 5 L
Transport category (TC) 3
Hazard identification No 30

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name DIISOBUTYL KETONE

Particulars in the shipper's declaration UN1157, DIISOBUTYL KETONE, 3, III, 49°C c.c.

Marine pollutant Danger label(s) 3



Special provisions (SP)

United Kingdom (en) Page 12 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Diisobutyl ketone ≥94 % pure

article number: 7653

Excepted quantities (EQ) E1
Limited quantities (LQ) 5 L

EmS F-E, S-D

Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Diisobutyl ketone

Particulars in the shipper's declaration UN1157, Diisobutyl ketone, 3, III

Danger label(s) 3



Excepted quantities (EQ) E1
Limited quantities (LQ) 10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Seveso Directive

2012/18/EU (Seveso III)				
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements		Notes
P5c	flammable liquids (cat. 2, 3)	5.000	50.000	51)

Notation

Deco-Paint Directive

VOC content	100 %
VOC content	100 70

Industrial Emissions Directive (IED)

VOC content	100 %
-------------	-------

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Water Framework Directive (WFD)

not listed

Regulation on the marketing and use of explosives precursors

not listed

United Kingdom (en) Page 13 / 17



⁵¹⁾ Flammable liquids, categories 2 or 3 not covered by P5a and P5b

acc. to Regulation (EC) No. 1907/2006 (REACH)

Diisobutyl ketone ≥94 % pure

article number: 7653



Regulation on drug precursors

not listed

Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list

not listed

Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)			
Name of substance Name acc. to inventory CAS No No			
Diisobutyl ketone	this product meets the criteria for classi- fication in accordance with Regulation No 1272/2008/EC		3
Diisobutyl ketone	flammable / pyrophoric		40

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
JP	ISHA-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed

United Kingdom (en) Page 14 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Diisobutyl ketone ≥94 % pure

article number: 7653

Legend

AIIC CICR CSCL-ENCS Australian Inventory of Industrial Chemicals

Chemical Inventory and Control Regulation
List of Existing and New Chemical Substances (CSCL-ENCS)

Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China National Inventory of Chemical Substances
Inventory of Existing and New Chemical Substances (ISHA-ENCS)
Korea Existing Chemicals Inventory
New Zoaland Inventory of Chemicals DSL ECSI IECSC

INSQ

ISHA-ENCS

KECI NZIOC New Zealand Inventory of Chemicals PICCS Philippine Inventory of Chemicals and REACH Reg.
TCSI Taiwan Chemical Substance Inventory Toxic Substance Control Act

New Zealand Inventory of Chemicals
Philippine Inventory of Chemicals and Chemical Substances (PICCS)

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation:

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1		The most important adverse physicochemical, human health and environmental effects: The product is combustible and can be ignited by potential ignition sources.	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Warning		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de naviga- tion intérieures (European Agreement concerning the International Carriage of Dangerous Goods by In- land Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor

United Kingdom (en) Page 15 / 17



acc. to Regulation (EC) No. 1907/2006 (REACH)

Diisobutyl ketone ≥94 % pure

article number: 7653



Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)

United Kingdom (en) Page 16 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Diisobutyl ketone ≥94 % pure

article number: 7653



Abbr.	Descriptions of used abbreviations
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H335	May cause respiratory irritation.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United Kingdom (en) Page 17 / 17