acc. to Regulation (EC) No. 1907/2006 (REACH)

Benzene D6 99,8 Atom%D

article number: **7912**Version: **5.0 en**date of compilation: 2019-06-26
Revision: 2022-12-05

Replaces version of: 2022-08-03

Version: (4)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance Benzene D6 99,8 Atom%D

Article number 7912

EC number 214-061-8 CAS number 1076-43-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes

(household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319

United Kingdom (en) Page 1 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)



Benzene D6 99,8 Atom%D

article number: 7912

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
3.5	Germ cell mutagenicity	1B	Muta. 1B	H340
3.6	Carcinogenicity	1A	Carc. 1A	H350
3.9	Specific target organ toxicity - repeated exposure	1	STOT RE 1	H372
3.10	Aspiration hazard	1	Asp. Tox. 1	H304
4.1C	Hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS02, GHS07, GHS08







Hazard statements

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H340	May cause genetic defects (if exposed)
H350	May cause cancer (if exposed)
H372	Causes damage to organs (haematopoietic system) through prolonged or re-
	peated exposure
H412	Harmful to aquatic life with long lasting effects

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking

P280 Wear protective gloves/eye protection

Precautionary statements - response

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting P302+P352 IF ON SKIN: Wash with plenty of soap and water

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P308+P313 IF exposed or concerned: Get medical advice/attention

For professional users only

United Kingdom (en) Page 2 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

ROTH

Benzene D6 99,8 Atom%D

article number: 7912

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance Benzene D6

Molecular formula C₆D₆

Molar mass 84,16 ^g/_{mol}
CAS No 1076-43-3
EC No 214-061-8

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

Following ingestion

Call a physician immediately. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Observe aspiration hazard if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard, Irritation, Headache, Vertigo, Nausea, Fatigue

4.3 Indication of any immediate medical attention and special treatment needed

none

United Kingdom (en) Page 3 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Benzene D6 99,8 Atom%D

article number: 7912



SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

United Kingdom (en) Page 4 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Benzene D6 99,8 Atom%D

article number: 7912



6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

This information is not available.

United Kingdom (en) Page 5 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Benzene D6 99,8 Atom%D

article number: 7912



Environmental values

Relevant PNECs and other threshold levels

End- point	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	1,9 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)
PNEC	1,9 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)
PNEC	39 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	33 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	33 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
PNEC	4,8 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

FKM (fluoro rubber)

material thickness

0.4 mm

breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

United Kingdom (en) Page 6 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Benzene D6 99,8 Atom%D

article number: 7912

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour colourless

Odour characteristic

Melting point/freezing point 6,8 °C at 1.013 hPa

Boiling point or initial boiling point and boiling 79,1 °C at 1.013 hPa

range

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 1,3 vol% (LEL) - 8 vol% (UEL)

Flash point -11 °C at 1.013 hPa Auto-ignition temperature 498 °C at 1.013 hPa

Decomposition temperature not relevant

pH (value) not determined
Kinematic viscosity not determined

Solubility(ies)

Water solubility ~2 ^g/_l at 25 °C

Partition coefficient

Partition coefficient n-octanol/water (log value): 2,13 (pH value: 7, 25 °C) (ECHA)

Vapour pressure 99,5 hPa at 20 °C

Density and/or relative density

Density $0.95 \, ^{9}/_{\text{cm}^3}$ at 25 $^{\circ}\text{C}$

Relative vapour density 2,91 (air = 1)

Particle characteristics not relevant (liquid)

United Kingdom (en) Page 7 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Benzene D6 99,8 Atom%D

article number: 7912

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

There is no additional information.

Other safety characteristics: There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Mineral acids, Sulphur,

Exothermic reaction with: Halogenated hydrocarbons,

Danger of explosion: Halogens, Nitric acid, Perchlorates, Peroxides

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Rubber articles, different plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity

Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	>2.000 ^{mg} / _{kg}	rat		ECHA
inhalation: vapour	LC50	43.767 ^{mg} / _{m³} /4h	rat		ECHA

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

United Kingdom (en) Page 8 / 17



acc. to Regulation (EC) No. 1907/2006 (REACH)

Benzene D6 99,8 Atom%D

article number: 7912



Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

May cause genetic defects (if exposed).

Carcinogenicity

May cause cancer (if exposed).

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Causes damage to organs (haematopoietic system) through prolonged or repeated exposure.

Hazard category	Target organ	Exposure route
1	haematopoietic system	if exposed

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

vomiting, nausea, aspiration hazard

• If in eyes

Causes serious eye irritation

• If inhaled

cough, pain, choking, and breathing difficulties, deficits in perception and coordination, reaction time, or sleepiness, poisoning effect on central nervous system can cause convulsions, laboured breathing and loss of consciousness

• If on skin

pruritis, causes skin irritation

Other information

none

11.2 Endocrine disrupting properties

Not listed.

11.3 Information on other hazards

There is no additional information.

United Kingdom (en) Page 9 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Benzene D6 99,8 Atom%D

article number: 7912



SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute)

Endpoint	Value	Species	Source	Exposure time
LC50	5,3 ^{mg} / _l	fish	ECHA	96 h
EC50	10 ^{mg} / _l	aquatic invertebrates	ECHA	48 h
ErC50	100 ^{mg} / _l	algae	ECHA	72 h

Biodegradation

The substance is readily biodegradable.

12.2 Process of degradability

Theoretical Carbon Dioxide: 3,138 mg/mg

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	2,13 (pH value: 7, 25 °C) (ECHA)
---------------------------	----------------------------------

12.4 Mobility in soil

Henry's law constant	415 Pa m³/ _{mol} (ECHA)

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Not listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

United Kingdom (en) Page 10 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Benzene D6 99,8 Atom%D

article number: 7912



13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Properties of waste which render it hazardous

HP3 flammable

HP 4 irritant - skin irritation and eye damage

HP 5 specific target organ toxicity (STOT)/aspiration toxicity

HP 5 specific targe HP 7 carcinogenic HP 11 mutagenic

HP 14 ecotoxic

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number or ID number

ADRRID	UN 1114
IMDG-Code	UN 1114
ICAO-TI	UN 1114

14.2 UN proper shipping name

ADRRID	BENZENE
IMDG-Code	BENZENE
ICAO-TI	Renzene

14.3 Transport hazard class(es)

ADRRID	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

ADRRID	II
IMDG-Code	II
ICAO-TI	II

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

United Kingdom (en) Page 11 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

ROTH

Benzene D6 99,8 Atom%D

article number: 7912

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Proper shipping name BENZENE

Particulars in the transport document UN1114, BENZENE, 3, II, (D/E)

Classification code F1
Danger label(s) 3



Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
Transport category (TC) 2
Tunnel restriction code (TRC) D/E
Hazard identification No 33
Emergency Action Code 3WE

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional information

Classification code F1

Danger label(s) 3



Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
Transport category (TC) 2
Hazard identification No 33

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name BENZENE

Particulars in the shipper's declaration UN1114, BENZENE, 3, II, -11°C c.c.

Marine pollutant Danger label(s) 3



Special provisions (SP)
Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

EmS F-E, S-D

Stowage category B

United Kingdom (en) Page 12 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)



Benzene D6 99,8 Atom%D

article number: 7912

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Benzene

Particulars in the shipper's declaration UN1114, Benzene, 3, II

Danger label(s) 3



Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Seveso Directive

2012/18/EU (Seveso III)				
No	Dangerous substance/hazard categories	ance/hazard categories Qualifying quantity (tonnes) for the application of lower and upper-tier requirements		Notes
P5c	flammable liquids (cat. 2, 3)	5.000	50.000	51)

Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

Deco-Paint Directive

C content	100 % 950 ^g / _I
-----------	--

Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	950 ^g / _l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Water Framework Directive (WFD)

United Kingdom (en) Page 13 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)





Benzene D6 99,8 Atom%D

article number: 7912

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Benzene D6	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-		a)	

related functions in or via the aquatic environment

Legend

A)

Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

not listed

Regulation on drug precursors

not listed

Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list not listed

Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)			
Name of substance	Name acc. to inventory	CAS No	No
Benzene D6	this product meets the criteria for classi- fication in accordance with Regulation No 1272/2008/EC		3
Benzene D6	flammable / pyrophoric		40

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

United Kingdom (en) Page 14 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Benzene D6 99,8 Atom%D

article number: 7912



Country	Inventory	Status
CA	NDSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
JP	CSCL-ENCS	substance is listed
NZ	NZIoC	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed

Legend

CSCL-ENCS ECSI IECSC

List of Existing and New Chemical Substances (CSCL-ENCS) EC Substance Inventory (EINECS, ELINCS, NLP) Inventory of Existing Chemical Substances Produced or Imported in China Non-domestic Substances List (NDSL)

NDSL NZIoC TCSI TSCA New Zealand Inventory of Chemicals Taiwan Chemical Substance Inventory Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1	The most important adverse physicochemical, human health and environmental effects: Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.	The most important adverse physicochemical, human health and environmental effects: Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.	yes
2.2		Hazard statements: change in the listing (table)	yes
15.1	VOC content: 100 % 876 ⁹ / _I	VOC content: 100 % 950 ^g / _l	yes
15.1	VOC content: 876 ^g / _l	VOC content: 950 ^g / _l	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de naviga- tion intérieures (European Agreement concerning the International Carriage of Dangerous Goods by In- land Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)

United Kingdom (en) Page 15 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)

Benzene D6 99,8 Atom%D

article number: 7912



Abbr.	Descriptions of used abbreviations
DGR	Dangerous Goods Regulations (see IATA/DGR)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

United Kingdom (en) Page 16 / 17

acc. to Regulation (EC) No. 1907/2006 (REACH)



Benzene D6 99,8 Atom%D

article number: 7912

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H340	May cause genetic defects (if exposed).
H350	May cause cancer (if exposed).
H372	Causes damage to organs (haematopoietic system) through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United Kingdom (en) Page 17 / 17