

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Acetone ≥99,5 %, VLSI Grade

article number: **9780**  
Version: **7.0 en**  
Replaces version of: 2022-05-18  
Version: (6)

date of compilation: 2016-04-28  
Revision: 2023-07-10

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Identification of the substance	<b>Acetone</b> ≥99,5 %, VLSI Grade
Article number	9780
Index No (GB CLP)	606-001-00-8
EC number	200-662-2
CAS number	67-64-1
Alternative name(s)	2-Propanone

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Laboratory chemical Laboratory and analytical use
Uses advised against:	Do not use for private purposes (household). Food, drink and animal feedingstuffs.

### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG  
Schoemperlenstr. 3-5  
D-76185 Karlsruhe  
Germany

**Telephone:**+49 (0) 721 - 56 06 0

**Telefax:** +49 (0) 721 - 56 06 149

**e-mail:** [sicherheit@carlroth.de](mailto:sicherheit@carlroth.de)

**Website:** [www.carlroth.de](http://www.carlroth.de)

Competent person responsible for the safety data sheet: :Department Health, Safety and Environment

**e-mail (competent person):** [sicherheit@carlroth.de](mailto:sicherheit@carlroth.de)

### 1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Acetone ≥99,5 %, VLSI Grade

article number: 9780

## Classification acc. to GHS

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

## Supplemental hazard information

Code	Supplemental hazard information
EUH066	repeated exposure may cause skin dryness or cracking

For full text of abbreviations: see SECTION 16

## The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

## 2.2 Label elements

### Labelling

#### Signal word

**Danger**

#### Pictograms

GHS02, GHS07



#### Hazard statements

H225 Highly flammable liquid and vapour  
H319 Causes serious eye irritation  
H336 May cause drowsiness or dizziness

#### Precautionary statements

##### Precautionary statements - prevention

P210 Keep away from heat, sparks, open flames, hot surfaces. No smoking

##### Precautionary statements - response

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

##### Precautionary statements - storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed

#### Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Acetone $\geq 99,5\%$ , VLSI Grade

article number: 9780

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

#### Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq 0,1\%$ .

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Name of substance	Acetone
Molecular formula	$C_3H_6O$
Molar mass	58,08 g/mol
CAS No	67-64-1
EC No	200-662-2
Index No (GB CLP)	606-001-00-8

## SECTION 4: First aid measures

### 4.1 Description of first aid measures



#### General notes

Take off contaminated clothing.

#### Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following skin contact

Rinse skin with water/shower.

#### Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

#### Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

### 4.2 Most important symptoms and effects, both acute and delayed

Irritation, Nausea, Vomiting, Gastrointestinal complaints, Headache, Vertigo, Dizziness, Drowsiness, Narcosis

### 4.3 Indication of any immediate medical attention and special treatment needed

none

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Acetone  $\geq 99,5$  %, VLSI Grade

article number: 9780

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media



#### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings  
water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

water jet

### 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

#### Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



**Acetone  $\geq$ 99,5 %, VLSI Grade**

article number: **9780**

## 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Provision of sufficient ventilation. When not in use, keep containers tightly closed.

#### Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed.

#### Incompatible substances or mixtures

Observe hints for combined storage.

#### Consideration of other advice:

Ground/bond container and receiving equipment.

#### Ventilation requirements

Use local and general ventilation.

#### Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

### 7.3 Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### National limit values

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Acetone ≥99,5 %, VLSI Grade

article number: 9780

### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
EU	acetone	67-64-1	IOELV	500	1.210						2000/39/EC
GB	acetone	67-64-1	WEL	500	1.210	1.500	3.620				EH40/2005

#### Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

### Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	1.210 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	2.420 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
DNEL	186 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

### Environmental values

Relevant PNECs and other threshold levels				
Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	10,6 mg/l	aquatic organisms	freshwater	short-term (single instance)
PNEC	1,06 mg/l	aquatic organisms	marine water	short-term (single instance)
PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	30,4 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	3,04 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
PNEC	29,5 mg/kg	terrestrial organisms	soil	short-term (single instance)

## 8.2 Exposure controls

### Individual protection measures (personal protective equipment)

#### Eye/face protection



Use safety goggle with side protection.

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Acetone $\geq 99,5$ %, VLSI Grade

article number: 9780

### Skin protection



#### • hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

#### • type of material

Butyl caoutchouc (butyl rubber)

#### • material thickness

0,7mm

#### • breakthrough times of the glove material

>480 minutes (permeation: level 6)

#### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

### Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: AX (gas filters and combined filters against low-boiling point organic compounds, colour code: Brown).

### Environmental exposure controls

Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	mild sweet - fruity
Melting point/freezing point	-94,8 °C (ECHA)
Boiling point or initial boiling point and boiling range	56,05 °C (ECHA)
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	2,6 vol% (LEL) - 12,8 vol% (UEL)

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Acetone ≥99,5 %, VLSI Grade

article number: 9780

Flash point	-17 °C (ECHA)
Auto-ignition temperature	465 °C (ECHA)
Decomposition temperature	not relevant
pH (value)	5 – 6 (in aqueous solution: 395 g/l, 20 °C)
Kinematic viscosity	0,4051 mm <sup>2</sup> /s at 20 °C
Dynamic viscosity	0,32 mPa s at 20 °C

### Solubility(ies)

Water solubility miscible in any proportion

### Partition coefficient

Partition coefficient n-octanol/water (log value): -0,23 (ECHA)

Vapour pressure 240 hPa at 20 °C

### Density and/or relative density

Density 0,79 g/cm<sup>3</sup> at 20 °C

Relative vapour density 2,01 (air = 1)

Particle characteristics not relevant (liquid)

### Other safety parameters

Oxidising properties none

## 9.2 Other information

Information with regard to physical hazard classes: There is no additional information.

Other safety characteristics:

Miscibility completely miscible with water

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air.

#### **If heated**

Risk of ignition.

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.



# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Acetone ≥99,5 %, VLSI Grade

article number: 9780

### 10.3 Possibility of hazardous reactions

**Risk of ignition:** strong oxidiser, Reducing agents, Nitric acid, Chromium(VI) oxide,  
**Exothermic reaction with:** Alkali metals, Alkali hydroxide (caustic alkali), Bromine, Halogenated hydrocarbons,  
**Danger of explosion:** Chloroform, Hydrogen peroxide

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5 Incompatible materials

Rubber articles, different plastics

### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Classification acc. to GHS

#### Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	5.800 mg/kg	rat		ECHA

#### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

#### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

#### Carcinogenicity

Shall not be classified as carcinogenic.

#### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

#### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

#### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

#### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.



Acetone ≥99,5 %, VLSI Grade

article number: 9780

**Symptoms related to the physical, chemical and toxicological characteristics**

• **If swallowed**

vomiting, nausea, gastrointestinal complaints

• **If in eyes**

Causes serious eye irritation, corneal opacity

• **If inhaled**

irritant effects, headache, vertigo, fatigue, dizziness, narcosis

• **If on skin**

repeated exposure may cause skin dryness or cracking

• **Other information**

none

**11.2 Endocrine disrupting properties**

Does not contain an endocrine disruptor (EDC) in a concentration of ≥ 0,1%.

**11.3 Information on other hazards**

There is no additional information.

**SECTION 12: Ecological information**

**12.1 Toxicity**

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
LC50	5.540 mg/l	fish	ECHA	96 h

Aquatic toxicity (chronic)				
Endpoint	Value	Species	Source	Exposure time
EC50	61,15 g/l	microorganisms	ECHA	30 min

**12.2 Persistence and degradability**

Process of degradability		
Process	Degradation rate	Time
carbon dioxide generation	90,9 %	28 d

**12.3 Bioaccumulative potential**

Does not significantly accumulate in organisms.

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Acetone ≥99,5 %, VLSI Grade

article number: 9780

n-octanol/water (log KOW)	-0,23 (ECHA)
BOD5/COD	963,54166667

### 12.4 Mobility in soil

Henry's law constant	2,929 Pa m <sup>3</sup> /mol at 25 °C (ECHA)
----------------------	--

### 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of ≥ 0,1%.

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Sewage disposal-relevant information

Do not empty into drains.

#### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

### 13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

#### Properties of waste which render it hazardous

**HP 3** flammable

**HP 4** irritant - skin irritation and eye damage

### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Acetone ≥99,5 %, VLSI Grade

article number: 9780

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADRRID	UN 1090
IMDG-Code	UN 1090
ICAO-TI	UN 1090

### 14.2 UN proper shipping name

ADRRID	ACETONE
IMDG-Code	ACETONE
ICAO-TI	Acetone

### 14.3 Transport hazard class(es)

ADRRID	3
IMDG-Code	3
ICAO-TI	3

### 14.4 Packing group

ADRRID	II
IMDG-Code	II
ICAO-TI	II

### 14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

### 14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

### 14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

### 14.8 Information for each of the UN Model Regulations

#### Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) Additional information

Proper shipping name	ACETONE
Particulars in the transport document	UN1090, ACETONE, 3, II, (D/E)
Classification code	F1
Danger label(s)	3



Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D/E

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Acetone ≥99,5 %, VLSI Grade

article number: 9780

Hazard identification No 33

**Emergency Action Code** 2YE

### Regulations concerning the International Carriage of Dangerous Goods by Rail (RID) Additional information

**Classification code** F1

**Danger label(s)** 3



**Excepted quantities (EQ)** E2

**Limited quantities (LQ)** 1 L

**Transport category (TC)** 2

**Hazard identification No** 33

### International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name ACETONE

Particulars in the shipper's declaration UN1090, ACETONE, 3, II, -17°C c.c.

Marine pollutant -

**Danger label(s)** 3



Special provisions (SP) -

Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

EmS F-E, S-D

Stowage category E

### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Acetone

Particulars in the shipper's declaration UN1090, Acetone, 3, II

**Danger label(s)** 3



Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Acetone ≥99,5 %, VLSI Grade

article number: 9780

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Relevant provisions of the European Union (EU)

##### Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
P5c	flammable liquids (cat. 2, 3)	5.000 50.000	51)

##### Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

##### Deco-Paint Directive

VOC content	100 %
VOC content	790 g/l

##### Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	790 g/l

##### Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

##### Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

##### Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Acetone	Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-related functions in or via the aquatic environment		a)	

##### Legend

A) Indicative list of the main pollutants

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Acetone ≥99,5 %, VLSI Grade

article number: 9780

## Regulation on the marketing and use of explosives precursors

Explosives precursors which are subject to restrictions						
Name of substance	CAS No	Wt%	Type of registration	Re- marks	Limit value	Upper limit value for the pur- pose of licens- ing un- der Ar- ticle 5(3)
Acetone	67-64-1	100	Annex II			

### Legend

annex II Substances on their own or in mixtures or in substances for which suspicious transactions shall be reported

### Additional statements

If the product is passed on to third parties, in accordance with Article 7 "Notification of the supply chain" of Regulation EU 2019/1148, the information obligation is subject to the entire supply chain and all other provisions mentioned in Article 7 on restricted and regulated raw materials.

## Regulation on drug precursors

Name of substance	CAS No	Wt%	Classification	CN Code	Threshold level
Acetone	67-64-1	100	Category 3	2914 11 00	

## Regulation on substances that deplete the ozone layer (ODS)

not listed

## Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

## Regulation on persistent organic pollutants (POP)

not listed

## National regulations(GB)

### List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list

not listed

### Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)			
Name of substance	Name acc. to inventory	CAS No	No
Acetone	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		3
Acetone	flammable / pyrophoric		40

### Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Acetone ≥99,5 %, VLSI Grade

article number: 9780

## UN Convention against Illicit Traffic in Narcotic Drugs and Psychotropic Substances

Name of substance	CAS No	Listed in	HS code
Acetone	67-64-1	Table II	2914.11

## National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)

### Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

## 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance.

## SECTION 16: Other information

### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of ≥ 0,1%.	yes
15.1	VOC content: 100 % 790 g/l	VOC content: 100 %	yes



# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Acetone ≥99,5 %, VLSI Grade

article number: 9780

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
15.1		VOC content: 790 g/l	yes
15.1		Explosives precursors which are subject to restrictions: change in the listing (table)	yes
15.1		Regulation on drug precursors: change in the listing (table)	yes
15.1		National inventories: change in the listing (table)	yes

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CN Code	Combined Nomenclature
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits ( <a href="http://www.nationalarchives.gov.uk/doc/open-government-licence/">http://www.nationalarchives.gov.uk/doc/open-government-licence/</a> )
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
GB CLP	The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended)
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Acetone ≥99,5 %, VLSI Grade

article number: 9780

Abbr.	Descriptions of used abbreviations
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

### Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.