

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: **9921**  
Version: **3.1 en**  
Replaces version of: 2022-01-21  
Version: (3)

date of compilation: 2016-08-30  
Revision: 2022-01-21

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

Identification of the substance	<b>Styrene D8 99Atom%D, stabilized</b>
Article number	9921
Registration number (REACH)	It is not required to list the identified uses because the substance is not subject to registration according to REACH (< 1 t/a).
EC number	242-995-6
CAS number	19361-62-7

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Laboratory chemical Laboratory and analytical use
Uses advised against:	Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG  
Schoemperlenstr. 3-5  
D-76185 Karlsruhe  
Germany

**Telephone:** +49 (0) 721 - 56 06 0

**Telefax:** +49 (0) 721 - 56 06 149

**e-mail:** [sicherheit@carlroth.de](mailto:sicherheit@carlroth.de)

**Website:** [www.carlroth.de](http://www.carlroth.de)

Competent person responsible for the safety data sheet: Department Health, Safety and Environment

**e-mail (competent person):** [sicherheit@carlroth.de](mailto:sicherheit@carlroth.de)

### 1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	3	Flam. Liq. 3	H226
3.1I	Acute toxicity (inhal.)	4	Acute Tox. 4	H332
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.7	Reproductive toxicity	2	Repr. 2	H361d
3.9	Specific target organ toxicity - repeated exposure	1	STOT RE 1	H372
3.10	Aspiration hazard	1	Asp. Tox. 1	H304
4.1C	Hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16

##### The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008 (CLP)

##### Signal word

**Danger**

##### Pictograms

GHS02, GHS07,  
GHS08



##### Hazard statements

H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H361d	Suspected of damaging the unborn child
H372	Causes damage to organs (hearing organs) through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects

##### Precautionary statements

##### Precautionary statements - prevention

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P280	Wear protective clothing/eye protection

### Precautionary statements - response

P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention

For professional users only

### Labelling of packages where the contents do not exceed 125 ml

Signal word: **Danger**

Symbol(s)



H304	May be fatal if swallowed and enters airways.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs (hearing organs) through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
P280	Wear protective clothing/eye protection.
P308+P313	IF exposed or concerned: Get medical advice/attention.

## 2.3 Other hazards

### Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Name of substance	Styrene D8
Molecular formula	C <sub>8</sub> D <sub>8</sub>
Molar mass	112,2 g/mol
CAS No	19361-62-7
EC No	242-995-6

#### To stabilise:

Name of substance	Identifier	Wt%
4-tert-butylpyrocatechol	CAS No 98-29-3  EC No 202-653-9	0,5

#### Substance, Specific Conc. Limits, M-factors, ATE

Specific Conc. Limits	M-Factors	ATE	Exposure route
-	-	11 mg/4h	inhalation: vapour

For full text of abbreviations: see SECTION 16

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures



##### General notes

Take off contaminated clothing.

##### Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

##### Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

##### Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

##### Following ingestion

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Observe aspiration hazard if vomiting occurs.

#### 4.2 Most important symptoms and effects, both acute and delayed

Irritation, Localised redness, Pruritis, Malaise, Headache, Nausea, Vomiting, Aspiration hazard

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media



##### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings  
water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

##### Unsuitable extinguishing media

water jet

#### 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

##### Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. Danger of explosion.

### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

#### Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep in a cool place.

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

### Incompatible substances or mixtures

Observe hints for combined storage.

### Protect against external exposure, such as

high temperatures, direct light irradiation, UV-radiation/sunlight, contact with air/oxygen

### Consideration of other advice:

Ground/bond container and receiving equipment.

### Ventilation requirements

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted. Use local and general ventilation.

### Specific designs for storage rooms or vessels

Recommended storage temperature: 2 – 8 °C

### 7.3 Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### National limit values

#### Occupational exposure limit values (Workplace Exposure Limits)

This information is not available.

#### Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	85 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	289 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
DNEL	306 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
DNEL	406 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
4-tert-butylpyrocatechol	98-29-3	DNEL	1,6 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects

#### Environmental values

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

Relevant PNECs and other threshold levels				
End-point	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	0,028 mg/l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0,014 mg/l	aquatic organisms	marine water	short-term (single instance)
PNEC	5 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	0,614 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	0,307 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
PNEC	0,2 mg/kg	terrestrial organisms	soil	short-term (single instance)

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
4-tert-butylpyrocatechol	98-29-3	PNEC	1,2 µg/l	aquatic organisms	freshwater	short-term (single instance)
4-tert-butylpyrocatechol	98-29-3	PNEC	0,12 µg/l	aquatic organisms	marine water	short-term (single instance)
4-tert-butylpyrocatechol	98-29-3	PNEC	1,2 µg/l	aquatic organisms	water	intermittent release
4-tert-butylpyrocatechol	98-29-3	PNEC	0,16 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
4-tert-butylpyrocatechol	98-29-3	PNEC	6,9 µg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
4-tert-butylpyrocatechol	98-29-3	PNEC	0,68 µg/kg	terrestrial organisms	soil	short-term (single instance)
4-tert-butylpyrocatechol	98-29-3	PNEC	0,69 µg/kg	aquatic organisms	marine sediment	short-term (single instance)

## 8.2 Exposure controls

### Individual protection measures (personal protective equipment)

#### Eye/face protection



Use safety goggle with side protection.

#### Skin protection



# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

### • hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

### • type of material

FKM (fluoro rubber)

### • material thickness

>0,4 mm

### • breakthrough times of the glove material

>480 minutes (permeation: level 6)

### • Splash protection - Protective gloves

• type of material: NBR (Nitrile rubber)


• material thickness: 0,4 mm

• breakthrough times of the glove material: >30 minutes (permeation: level 2)

### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

### Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown).

### Environmental exposure controls

Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	mild sweet
Melting point/freezing point	-31 °C (ECHA)
Boiling point or initial boiling point and boiling range	145 °C at 1.013 hPa (ECHA)
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	45 g/m <sup>3</sup> (LEL) - 350 g/m <sup>3</sup> (UEL) / 1,2 vol% (LEL) - 8,9 vol% (UEL)
Flash point	31 °C at 1.013 hPa (ECHA)



# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

Auto-ignition temperature	490 °C at 1.013 hPa (ECHA) (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	0,77 mm <sup>2</sup> /s at 25 °C
<u>Solubility(ies)</u>	
Water solubility	0,32 g/l at 25 °C (ECHA)
<u>Partition coefficient</u>	
Partition coefficient n-octanol/water (log value):	2,96 (25 °C) (ECHA)
Soil organic carbon/water (log KOC)	2,55 (ECHA)
Vapour pressure	6,67 hPa at 20 °C
<u>Density and/or relative density</u>	
Density	0,98 g/cm <sup>3</sup> at 20 °C
Relative vapour density	3,6 (air = 1)
Particle characteristics	not relevant (liquid)
<u>Other safety parameters</u>	
Oxidising properties	none

### 9.2 Other information

Information with regard to physical hazard classes:	There is no additional information.
Other safety characteristics:	
Maximum explosion pressure	6,6 bar
Temperature class (EU, acc. to ATEX)	T1 Maximum permissible surface temperature on the equipment: 450°C

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

It's a reactive substance. Risk of ignition. Can polymerise exothermically if heated, exposed to air, sunlight or by addition of free radical initiators. May form explosive peroxides.

#### If heated

Risk of ignition. Vapours may form explosive mixtures with air.

### 10.2 Chemical stability

Reactivity if exposed to air => May form explosive peroxides  
Reactivity if exposed to light, Reactivity if heated => Danger of polymerisation

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

### 10.3 Possibility of hazardous reactions

**Danger of explosion:** Peroxides, Strong acid, Peroxide formation possible with air oxygen,  
**Violent reaction with:** strong oxidiser

### 10.4 Conditions to avoid

Direct light irradiation. UV-radiation/sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5 Incompatible materials

copper

### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5. Release of: Peroxides.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Classification according to GHS (1272/2008/EC, CLP)**

#### Acute toxicity

Harmful if inhaled.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
dermal	LD50	>2.000 mg/kg	rat		ECHA

#### Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
4-tert-butylpyrocatechol	98-29-3	oral	LD50	815 mg/kg	rat
4-tert-butylpyrocatechol	98-29-3	dermal	LD50	1.331 mg/kg	rat

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

#### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

#### Carcinogenicity

Shall not be classified as carcinogenic.

#### Reproductive toxicity

Suspected of damaging the unborn child.

#### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

### Specific target organ toxicity - repeated exposure

Causes damage to organs (hearing organs) through prolonged or repeated exposure.

Hazard category	Target organ	Exposure route
1	hearing organs	if exposed

### Aspiration hazard

May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

#### • If swallowed

vomiting, aspiration hazard

#### • If in eyes

Causes serious eye irritation

#### • If inhaled

vertigo, headache

#### • If on skin

causes skin irritation, pruritis, localised redness

#### • Other information

none

### 11.2 Endocrine disrupting properties

Not listed.

### 11.3 Information on other hazards

There is no additional information.

## SECTION 12: Ecological information

### 12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
LC50	4,02 mg/l	fish	ECHA	96 h
EC50	4,7 mg/l	aquatic invertebrates	ECHA	48 h
ErC50	4,9 mg/l	algae	ECHA	72 h

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
4-tert-butylpyrocatechol	98-29-3	LC50	0,12 mg/l	fish	96 h

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
4-tert-butylpyrocatechol	98-29-3	EC50	0,48 mg/l	aquatic invertebrates	48 h
4-tert-butylpyrocatechol	98-29-3	ErC50	10,17 mg/l	algae	72 h

Aquatic toxicity (chronic)				
Endpoint	Value	Species	Source	Exposure time
EC50	1,88 mg/l	aquatic invertebrates	ECHA	21 d
LC50	>3,84 mg/l	aquatic invertebrates	ECHA	21 d

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
4-tert-butylpyrocatechol	98-29-3	EC50	0,94 mg/l	aquatic invertebrates	24 h

### Biodegradation

Data are not available.

### 12.2 Process of degradability

Theoretical Carbon Dioxide: 3,138 mg/mg

Process of degradability		
Process	Degradation rate	Time
biotic/abiotic	80 %	20 d

Degradability of components of the mixture						
Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
4-tert-butylpyrocatechol	98-29-3	DOC removal	91 %	28 d		ECHA
4-tert-butylpyrocatechol	98-29-3	carbon dioxide generation	24,7 %	28 d		ECHA

### 12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

n-octanol/water (log KOW)	2,96 (25 °C) (ECHA)
BCF	74 (ECHA)

### Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
4-tert-butylpyrocatechol	98-29-3		1,98 (pH value: 5,9, 25 °C)	

### 12.4 Mobility in soil

Henry's law constant	231,6 Pa m <sup>3</sup> /mol (ECHA)
The Organic Carbon normalised adsorption coefficient	2,55 (ECHA)

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Endocrine disrupting properties

Not listed.

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

### 13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste catalogue ordinance (Germany).

### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR/RID/ADN	UN 2055
IMDG-Code	UN 2055
ICAO-TI	UN 2055

#### 14.2 UN proper shipping name

ADR/RID/ADN	STYRENE MONOMER, STABILIZED
IMDG-Code	STYRENE MONOMER, STABILIZED
ICAO-TI	Styrene monomer, stabilized

#### 14.3 Transport hazard class(es)

ADR/RID/ADN	3
IMDG-Code	3
ICAO-TI	3

#### 14.4 Packing group

ADR/RID/ADN	III
IMDG-Code	III
ICAO-TI	III

#### 14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

#### 14.6 Special precautions for user


Provisions for dangerous goods (ADR) should be complied within the premises.

#### 14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

#### 14.8 Information for each of the UN Model Regulations

##### Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Proper shipping name	STYRENE MONOMER, STABILIZED
Particulars in the transport document	UN2055, STYRENE MONOMER, STABILIZED, 3, III, (D/E)
Classification code	F1
Danger label(s)	3
	
Special provisions (SP)	386
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	3



# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

Tunnel restriction code (TRC)	D/E
Hazard identification No	39
<b>Emergency Action Code</b>	3Y
<b>International Maritime Dangerous Goods Code (IMDG) - Additional information</b>	
Proper shipping name	STYRENE MONOMER, STABILIZED
Particulars in the shipper's declaration	UN2055, STYRENE MONOMER, STABILIZED, 3, III, 31°C c.c.
Marine pollutant	-
Danger label(s)	3
	
Special provisions (SP)	386
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, S-D
Stowage category	C
<b>International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information</b>	
Proper shipping name	Styrene monomer, stabilized
Particulars in the shipper's declaration	UN2055, Styrene monomer, stabilized, 3, III
Danger label(s)	3
	
Special provisions (SP)	A209
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Relevant provisions of the European Union (EU)

#### Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)				
Name of substance	Name acc. to inventory	CAS No	Restriction	No
Styrene D8	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3
Styrene D8	flammable / pyrophoric		R40	40
Styrene D8	substances in tattoo inks and permanent make-up		R75	75

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

### Legend

- R3
1. Shall not be used in:
    - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
    - tricks and jokes,
    - games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
  2. Articles not complying with paragraph 1 shall not be placed on the market.
  3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
    - can be used as fuel in decorative oil lamps for supply to the general public, and
    - present an aspiration hazard and are labelled with H304.
  4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
  5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
    - (a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps – may lead to life-threatening lung damage";
    - (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter fluid may lead to life threatening lung damage";
    - (c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.;
- R40
1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:
    - metallic glitter intended mainly for decoration,
    - artificial snow and frost,
    - 'whoopie' cushions,
    - silly string aerosols,
    - imitation excrement,
    - horns for parties,
    - decorative flakes and foams,
    - artificial cobwebs,
    - stink bombs.
  2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:  
'For professional users only'.
  3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).
  4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.



## Styrene D8 99Atom%D, stabilized

article number: 9921

### Legend

- R75
1. Shall not be placed on the market in mixtures for use for tattooing purposes, and mixtures containing any such substances shall not be used for tattooing purposes, after 4 January 2022 if the substance or substances in question is or are present in the following circumstances:
    - (a) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight;
    - (b) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as reproductive toxicant category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;
    - (c) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin sensitiser category 1, 1A or 1B, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;
    - (d) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2, or as serious eye damage category 1 or eye irritant category 2, the substance is present in the mixture in a concentration equal to or greater than:
      - (i) 0,1 % by weight, if the substance is used solely as a pH regulator;
      - (ii) 0,01 % by weight, in all other cases;
    - (e) in the case of a substance listed in Annex II to Regulation (EC) No 1223/2009 (\*1), the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight;
    - (f) in the case of a substance for which a condition of one or more of the following kinds is specified in column g (Product type, Body parts) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight:
      - (i) "Rinse-off products";
      - (ii) "Not to be used in products applied on mucous membranes";
      - (iii) "Not to be used in eye products";
    - (g) in the case of a substance for which a condition is specified in column h (Maximum concentration in ready for use preparation) or column i (Other) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration, or in some other way, that does not accord with the condition specified in that column;
    - (h) in the case of a substance listed in Appendix 13 to this Annex, the substance is present in the mixture in a concentration equal to or greater than the concentration limit specified for that substance in that Appendix.
  2. For the purposes of this entry use of a mixture "for tattooing purposes" means injection or introduction of the mixture into a person's skin, mucous membrane or eyeball, by any process or procedure (including procedures commonly referred to as permanent make-up, cosmetic tattooing, micro-blading and micro-pigmentation), with the aim of making a mark or design on his or her body.
  3. If a substance not listed in Appendix 13 falls within more than one of points (a) to (g) of paragraph 1, the strictest concentration limit laid down in the points in question shall apply to that substance. If a substance listed in Appendix 13 also falls within one or more of points (a) to (g) of paragraph 1, the concentration limit laid down in point (h) of paragraph 1 shall apply to that substance.
  4. By way of derogation, paragraph 1 shall not apply to the following substances until 4 January 2023:
    - (a) Pigment Blue 15:3 (CI 74160, EC No 205-685-1, CAS No 147-14-8);
    - (b) Pigment Green 7 (CI 74260, EC No 215-524-7, CAS No 1328-53-6).
  5. If Part 3 of Annex VI to Regulation (EC) No 1272/2008 is amended after 4 January 2021 to classify or re-classify a substance such that the substance then becomes caught by point (a), (b), (c) or (d) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the date of application of that new or revised classification is after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect on the date of application of that new or revised classification.
  6. If Annex II or Annex IV to Regulation (EC) No 1223/2009 is amended after 4 January 2021 to list or change the listing of a substance such that the substance then becomes caught by point (e), (f) or (g) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the amendment takes effect after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect from the date falling 18 months after entry into force of the act by which that amendment was made.
  7. Suppliers placing a mixture on the market for use for tattooing purposes shall ensure that, after 4 January 2022, the mixture is marked with the following information:
    - (a) the statement "Mixture for use in tattoos or permanent make-up";
    - (b) a reference number to uniquely identify the batch;
    - (c) the list of ingredients in accordance with the nomenclature established in the glossary of common ingredient names pursuant to Article 33 of Regulation (EC) No 1223/2009, or in the absence of a common ingredient name, the IUPAC name. In the absence of a common ingredient name or IUPAC name, the CAS and EC number. Ingredients shall be listed in descending order by weight or volume of the ingredients at the time of formulation. "Ingredient" means any substance added during the process of formulation and present in the mixture for use for tattooing purposes. Impurities shall not be regarded as ingredients. If the name of a substance, used as ingredient within the meaning of this entry, is already required to be stated on the label in accordance with Regulation (EC) No 1272/2008, that ingredient does not need to be marked in accordance with this Regulation;
    - (d) the additional statement "pH regulator" for substances falling under point (d)(i) of paragraph 1;
    - (e) the statement "Contains nickel. Can cause allergic reactions." if the mixture contains nickel below the concentration limit specified in Appendix 13;
    - (f) the statement "Contains chromium (VI). Can cause allergic reactions." if the mixture contains chromium (VI) below the concentration limit specified in Appendix 13;
    - (g) safety instructions for use insofar as they are not already required to be stated on the label by Regulation (EC) No 1272/2008.The information shall be clearly visible, easily legible and marked in a way that is indelible. The information shall be written in the official language(s) of the Member State(s) where the mixture is placed on the market, unless the Member State(s) concerned provide(s) otherwise. Where necessary because of the size of the package, the information listed in the first subparagraph, except for point (a), shall be included instead in the instructions for use. Before using a mixture for tattooing purposes, the person using the mixture shall provide the person undergoing the procedure with the information marked on the package or included in the instructions for use pursuant to this paragraph.
  8. Mixtures that do not contain the statement "Mixture for use in tattoos or permanent make-up" shall not be used for tattooing purposes.

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

### Legend

9. This entry does not apply to substances that are gases at temperature of 20 °C and pressure of 101,3 kPa, or generate a vapour pressure of more than 300 kPa at temperature of 50 °C, with the exception of formaldehyde (CAS No 50-00-0, EC No 200-001-8).

10. This entry does not apply to the placing on the market of a mixture for use for tattooing purposes, or to the use of a mixture for tattooing purposes, when placed on the market exclusively as a medical device or an accessory to a medical device, within the meaning of Regulation (EU) 2017/745, or when used exclusively as a medical device or an accessory to a medical device, within the same meaning. Where the placing on the market or use may not be exclusively as a medical device or an accessory to a medical device, the requirements of Regulation (EU) 2017/745 and of this Regulation shall apply cumulatively.

### List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

Not listed.

### Seveso Directive

2012/18/EU (Seveso III)				
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements		Notes
P5c	flammable liquids (cat. 2, 3)	5.000	50.000	51)

#### Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

### Deco-Paint Directive

VOC content	100 % , 980 g/l
-------------	--------------------

### Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	980 g/l

### Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

### Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

### Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Styrene D8	Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-related functions in or via the aquatic environment		A)	

#### Legend

A) Indicative list of the main pollutants

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

### Regulation on the marketing and use of explosives precursors

not listed

### Regulation on drug precursors

not listed

### Regulation on substances that deplete the ozone layer (ODS)

not listed

### Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

### Regulation on persistent organic pollutants (POP)

not listed

### Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

### National inventories

Country	Inventory	Status
CA	NDSL	substance is listed
EU	ECSI	substance is listed
NZ	NZIoC	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed

#### Legend

ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
NDSL	Non-domestic Substances List (NDSL)
NZIoC	New Zealand Inventory of Chemicals
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

## SECTION 16: Other information

### Indication of changes (revised safety data sheet)

Alignment to regulation: Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification according to Regulation (EC) No 1272/2008 (CLP): change in the listing (table)	yes

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1	The most important adverse physicochemical, human health and environmental effects: Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.	The most important adverse physicochemical, human health and environmental effects: Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.	yes
2.2		Hazard statements: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
ADR/RID/ADN	Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN)
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: 9921

Abbr.	Descriptions of used abbreviations
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
SVHC	Substance of Very High Concern
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.  
Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs (hearing organs) through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Styrene D8 99Atom%D, stabilized

article number: **9921**

---

### **Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.