

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Petroleum ether 40-60 °C , DAB, extra pure

article number: **CP44**  
Version: **2.0 en**  
Replaces version of: 2021-05-26  
Version: (1)

date of compilation: 2021-05-25  
Revision: 2023-04-05

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Identification of the substance **Petroleum ether 40-60 °C , DAB, extra pure**  
Article number **CP44**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: **Laboratory chemical  
Laboratory and analytical use**  
Uses advised against: **Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household). Food, drink and animal feeding-stuffs.**

### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG  
Schoemperlenstr. 3-5  
D-76185 Karlsruhe  
Germany

**Telephone:**+49 (0) 721 - 56 06 0  
**Telefax:** +49 (0) 721 - 56 06 149  
**e-mail:** [sicherheit@carlroth.de](mailto:sicherheit@carlroth.de)  
**Website:** [www.carlroth.de](http://www.carlroth.de)

Competent person responsible for the safety data sheet: **Department Health, Safety and Environment**

**e-mail (competent person):** **[sicherheit@carlroth.de](mailto:sicherheit@carlroth.de)**

### 1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
3.10	Aspiration hazard	1	Asp. Tox. 1	H304

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Petroleum ether 40-60 °C , DAB, extra pure

article number: **CP44**

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
4.1C	Hazardous to the aquatic environment - chronic hazard	2	Aquatic Chronic 2	H411

For full text of abbreviations: see SECTION 16

### The most important adverse physicochemical, human health and environmental effects

The product is combustibile and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

## 2.2 Label elements

### Labelling

#### Signal word

**Danger**

#### Pictograms

GHS02, GHS07,  
GHS08, GHS09



#### Hazard statements

H225 Highly flammable liquid and vapour  
H304 May be fatal if swallowed and enters airways  
H315 Causes skin irritation  
H336 May cause drowsiness or dizziness  
H411 Toxic to aquatic life with long lasting effects

#### Precautionary statements

##### Precautionary statements - prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P240 Ground and bond container and receiving equipment  
P273 Avoid release to the environment

##### Precautionary statements - response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor  
P331 Do NOT induce vomiting

##### Precautionary statements - storage

P403+P235 Store in a well-ventilated place. Keep cool

#### Hazardous ingredients for labelling:

Hydrocarbons, C<sub>6</sub>, isoalkanes, <5% n-hexane, n-Pentane

## 2.3 Other hazards

### Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of  $\geq 0,1\%$ .

### Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq 0,1\%$ .

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Petroleum ether 40-60 °C , DAB, extra pure

article number: CP44

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

not relevant (mixture)

### 3.2 Mixtures

#### Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
n-Pentane	CAS No 109-66-0  EC No 203-692-4  Index No 601-006-00-1	≤ 70	Flam. Liq. 2 / H225 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411 EUH066		C GHS-HC IOELV
Hydrocarbons, C <sub>6</sub> , isoalkanes, <5% n-hex- ane	CAS No 64742-49-0  EC No 931-254-9  Index No 649-328-00-1	≤ 70	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411		

#### Notes

C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.  
GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC, Annex VI)  
IOELV: Substance with a community indicative occupational exposure limit value

For full text of abbreviations: see SECTION 16

## SECTION 4: First aid measures

### 4.1 Description of first aid measures



#### General notes

Take off contaminated clothing.

#### Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

#### Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following ingestion

Call a physician immediately. Observe aspiration hazard if vomiting occurs.

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Petroleum ether 40-60 °C , DAB, extra pure

article number: CP44

## 4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard, Irritation, Dizziness, Drowsiness, Narcosis

## 4.3 Indication of any immediate medical attention and special treatment needed

none

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media



#### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings  
water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

water jet

### 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

#### Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), May produce toxic fumes of carbon monoxide if burning.

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. Danger of explosion.

### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



**Petroleum ether 40-60 °C , DAB, extra pure**

article number: **CP44**

## **Advice on how to clean up a spill**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

## **Other information relating to spills and releases**

Place in appropriate containers for disposal. Ventilate affected area.

## **6.4 Reference to other sections**

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## **SECTION 7: Handling and storage**

### **7.1 Precautions for safe handling**

Provision of sufficient ventilation.

### **Measures to prevent fire as well as aerosol and dust generation**



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

### **Measures to protect the environment**

Avoid release to the environment.

### **Advice on general occupational hygiene**

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

### **7.2 Conditions for safe storage, including any incompatibilities**

Store in a well-ventilated place. Keep container tightly closed.

### **Incompatible substances or mixtures**

Observe hints for combined storage.

### **Consideration of other advice:**

Ground/bond container and receiving equipment.

### **Ventilation requirements**

Use local and general ventilation.

### **Specific designs for storage rooms or vessels**

Recommended storage temperature: 15 - 25 °C

### **7.3 Specific end use(s)**

No information available.

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Petroleum ether 40-60 °C , DAB, extra pure

article number: CP44

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### National limit values

#### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
EU	n-pentane	109-66-0	IOELV	1.000	3.000						2006/15/EC
GB	pentane	109-66-0	WEL	600	1.800						EH40/2005

#### Notation

Ceiling-C  
STEL

Ceiling value is a limit value above which exposure should not occur  
Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

#### Relevant DNELs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Hydrocarbons, C <sub>6</sub> , isoalkanes, <5% n-hexane	64742-49-0	DNEL	5.306 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C <sub>6</sub> , isoalkanes, <5% n-hexane	64742-49-0	DNEL	13.964 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
n-Pentane	109-66-0	DNEL	3.000 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
n-Pentane	109-66-0	DNEL	432 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

#### Relevant PNECs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
n-Pentane	109-66-0	PNEC	230 µg/l	aquatic organisms	freshwater	short-term (single instance)
n-Pentane	109-66-0	PNEC	230 µg/l	aquatic organisms	marine water	short-term (single instance)
n-Pentane	109-66-0	PNEC	3.600 µg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
n-Pentane	109-66-0	PNEC	1,2 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
n-Pentane	109-66-0	PNEC	1,2 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
n-Pentane	109-66-0	PNEC	0,55 mg/kg	terrestrial organisms	soil	short-term (single instance)

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Petroleum ether 40-60 °C , DAB, extra pure

article number: CP44

## 8.2 Exposure controls

### Individual protection measures (personal protective equipment)

#### Eye/face protection



Use safety goggle with side protection.

#### Skin protection



- **hand protection**

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

- **type of material**

NBR: acrylonitrile-butadiene rubber

- **material thickness**

>0,4 mm

- **breakthrough times of the glove material**

>480 minutes (permeation: level 6)

- **other protection measures**

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

#### Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: AX (gas filters and combined filters against low-boiling point organic compounds, colour code: Brown).

#### Environmental exposure controls

Keep away from drains, surface and ground water.

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Petroleum ether 40-60 °C , DAB, extra pure

article number: CP44

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	clear - colourless
Odour	like: - Gasoline
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	40 – 60 °C
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	1 vol% (LEL) - 8 vol% (UEL)
Flash point	-40 °C
Auto-ignition temperature	260 °C
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	0,41 mm <sup>2</sup> /s at 25 °C

#### Solubility(ies)

Water solubility (practically insoluble)

#### Partition coefficient

Partition coefficient n-octanol/water (log value): this information is not available

Vapour pressure 350 hPa at 20 °C

#### Density and/or relative density

Density 0,65 g/cm<sup>3</sup> at 20 °C

Relative vapour density 3 (air = 1)

Particle characteristics not relevant (liquid)

#### Other safety parameters

Oxidising properties none

### 9.2 Other information

Information with regard to physical hazard classes: There is no additional information.

Other safety characteristics: There is no additional information.



# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Petroleum ether 40-60 °C , DAB, extra pure

article number: CP44

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The mixture contains reactive substance(s). Risk of ignition. Vapours may form explosive mixtures with air.

#### If heated

Risk of ignition.

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### 10.3 Possibility of hazardous reactions

**Violent reaction with:** strong oxidiser

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5 Incompatible materials

Rubber articles, different plastics

### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to GHS

#### Acute toxicity

Shall not be classified as acutely toxic.

#### Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
n-Pentane	109-66-0	oral	LD50	>5.000 mg/kg	rat
n-Pentane	109-66-0	inhalation: vapour	LC50	>25,3 mg/l/4h	rat

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

#### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Petroleum ether 40-60 °C , DAB, extra pure

article number: CP44

## Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

## Carcinogenicity

Shall not be classified as carcinogenic.

## Reproductive toxicity

Shall not be classified as a reproductive toxicant.

## Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

## Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

## Aspiration hazard

May be fatal if swallowed and enters airways.

## Symptoms related to the physical, chemical and toxicological characteristics

### • If swallowed

vomiting, aspiration hazard

### • If in eyes

causes slight to moderate irritation

### • If inhaled

headache, vertigo, drowsiness, dizziness, narcosis

### • If on skin

has degreasing effect on the skin, causes skin irritation

### • Other information

none

## 11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq 0,1\%$ .

## 11.3 Information on other hazards

There is no additional information.

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
n-Pentane	109-66-0	LC50	4,26 mg/l	rainbow trout (Oncorhynchus mykiss)	96 h
n-Pentane	109-66-0	EC50	2,7 mg/l	daphnia magna	48 h

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Petroleum ether 40-60 °C , DAB, extra pure

article number: CP44

## 12.2 Persistence and degradability

### Biodegradation

The relevant substances of the mixture are readily biodegradable.

Degradability of components of the mixture						
Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
Hydrocarbons, C <sub>6</sub> , isoalkanes, <5% n-hexane	64742-49-0	oxygen depletion	83 %	10 d		ECHA
n-Pentane	109-66-0	oxygen depletion	87 %	28 d		ECHA

## 12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Hydrocarbons, C <sub>6</sub> , isoalkanes, <5% n-hexane	64742-49-0	501,2	3,6 (pH value: 7, 20 °C)	
n-Pentane	109-66-0	171	3,45 (pH value: 7, 25 °C)	

## 12.4 Mobility in soil

Data are not available.

## 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of  $\geq 0,1\%$ .

## 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq 0,1\%$ .

## 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



**Petroleum ether 40-60 °C , DAB, extra pure**

article number: **CP44**

## 13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

### Properties of waste which render it hazardous

**HP 3** flammable

**HP 5** specific target organ toxicity (STOT)/aspiration toxicity

**HP 14** ecotoxic

## 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADRRID	UN 3295
IMDG-Code	UN 3295
ICAO-TI	UN 3295

### 14.2 UN proper shipping name

ADRRID	HYDROCARBONS, LIQUID, N.O.S.
IMDG-Code	HYDROCARBONS, LIQUID, N.O.S.
ICAO-TI	Hydrocarbons, liquid, n.o.s.

### 14.3 Transport hazard class(es)

ADRRID	3
IMDG-Code	3
ICAO-TI	3

### 14.4 Packing group

ADRRID	II
IMDG-Code	II
ICAO-TI	II

### 14.5 Environmental hazards

	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment):	Hydrocarbons, C <sub>6</sub> , isoalkanes, <5% n-hexane

### 14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

### 14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

### 14.8 Information for each of the UN Model Regulations

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Petroleum ether 40-60 °C , DAB, extra pure

article number: **CP44**

### Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) Additional information

Proper shipping name	HYDROCARBONS, LIQUID, N.O.S.
Particulars in the transport document	UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II, (D/E), environmentally hazardous, special provision 640D
Classification code	F1
Danger label(s)	3, "Fish and tree"
Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	640D
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D/E
Hazard identification No	33
<b>Emergency Action Code</b>	3YE

### Regulations concerning the International Carriage of Dangerous Goods by Rail (RID) Additional information

<b>Classification code</b>	F1
<b>Danger label(s)</b>	3 Fish and tree
<b>Environmental hazards</b>	Yes Hazardous to water
<b>Special provisions (SP)</b>	640D
<b>Excepted quantities (EQ)</b>	E2
<b>Limited quantities (LQ)</b>	1 L
<b>Transport category (TC)</b>	2
<b>Hazard identification No</b>	33

### International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name	HYDROCARBONS, LIQUID, N.O.S.
Particulars in the shipper's declaration	UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II, -40°C c.c., MARINE POLLUTANT
Marine pollutant	yes (hazardous to the aquatic environment)
Danger label(s)	3, "Fish and tree"

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Petroleum ether 40-60 °C , DAB, extra pure

article number: **CP44**

Special provisions (SP)	-
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-E, S-D
Stowage category	B

### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name	Hydrocarbons, liquid, n.o.s.
Particulars in the shipper's declaration	UN3295, Hydrocarbons, liquid, n.o.s., 3, II
Environmental hazards	YES (hazardous to the aquatic environment)
Danger label(s)	3



Special provisions (SP)	A3
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Relevant provisions of the European Union (EU)

##### Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
E2	environmental hazards (hazardous to the aquatic environment, cat. 2)	200                      500	57)

##### Notation

57) Hazardous to the Aquatic Environment in category Chronic 2

##### Deco-Paint Directive

VOC content	100 %
VOC content	650 g/l

##### Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	650 g/l

##### Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Petroleum ether 40-60 °C , DAB, extra pure

article number: CP44

## Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

## Water Framework Directive (WFD)

none of the ingredients are listed

## Regulation on the marketing and use of explosives precursors

none of the ingredients are listed

## Regulation on drug precursors

none of the ingredients are listed

## Regulation on substances that deplete the ozone layer (ODS)

none of the ingredients are listed

## Regulation concerning the export and import of hazardous chemicals (PIC)

none of the ingredients are listed

## Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

## National regulations(GB)

## List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list

none of the ingredients are listed

## Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)			
Name of substance	Name acc. to inventory	CAS No	No
Petroleum ether 40-60 °C	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		3
n-Pentane	flammable / pyrophoric		40

## Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

## National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Petroleum ether 40-60 °C , DAB, extra pure

article number: **CP44**

Country	Inventory	Status
PH	PICCS	all ingredients are listed
TR	CICR	all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed as "ACTIVE"

### Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Danger		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2	contains: Hydrocarbons, C <sub>6</sub> , isoalkanes, <5% n-hexane, n-Pentane		yes
2.3	Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance in a concentration of ≥ 0,1%.	yes
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of ≥ 0,1%.	yes
14.8		Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional information	yes
14.8		Classification code: F1	yes



# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Petroleum ether 40-60 °C , DAB, extra pure

article number: **CP44**

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.8		Danger label(s): 3 Fish and tree	yes
14.8		Danger label(s): change in the listing (table)	yes
14.8		Environmental hazards: Yes Hazardous to water	yes
14.8		Special provisions (SP): 640D	yes
14.8		Excepted quantities (EQ): E2	yes
14.8		Limited quantities (LQ): 1 L	yes
14.8		Transport category (TC): 2	yes
14.8		Hazard identification No: 33	yes
14.8	Marine pollutant: yes (hazardous to the aquatic environment), (Hydrocarbons, C <sub>6</sub> , isoalkanes, <5% n-hexane)	Marine pollutant: yes (hazardous to the aquatic environment)	yes
15.1	Restrictions according to REACH, Annex XVII		yes
15.1		Dangerous substances with restrictions (REACH, Annex XVII): change in the listing (table)	yes
15.1	List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list: None of the ingredients are listed. (Or Concentration of the substance in a mixture: <0.1 % Mass concentration)		yes
15.1	VOC content: 100 % 0,65 g/l	VOC content: 100 %	yes
15.1		VOC content: 650 g/l	yes
15.1	VOC content: 0,65 g/l	VOC content: 650 g/l	yes
15.1		Water Framework Directive (WFD): none of the ingredients are listed	yes
15.1		National regulations(GB)	yes
15.1		List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list: none of the ingredients are listed	yes
15.1		Restrictions according to GB REACH, Annex 17	yes
15.1		Dangerous substances with restrictions (GB REACH, Annex 17): change in the listing (table)	yes

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Petroleum ether 40-60 °C , DAB, extra pure

article number: **CP44**

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
15.1		Other information: Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.	yes
15.1		National inventories: change in the listing (table)	yes

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits ( <a href="http://www.nationalarchives.gov.uk/doc/open-government-licence/">http://www.nationalarchives.gov.uk/doc/open-government-licence/</a> )
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Flam. Liq.	Flammable liquid
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Petroleum ether 40-60 °C , DAB, extra pure

article number: **CP44**

Abbr.	Descriptions of used abbreviations
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

### Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties. The classification is based on tested mixture.  
Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



**Petroleum ether 40-60 °C , DAB, extra pure**

article number: **CP44**

## List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

## Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.