



**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name: Sprayflon Plus 3**
- **UFI: P300-P0FT-K00A-G4MG**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Lubricant
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Saint-Gobain Performance Plastics Pampus GmbH  
Am Nordkanal 37  
D-47877 Willich  
Tel.: +49 (0) 2154 60 216  
Fax: +49 (0) 2154 60465  
Email: jan.glaeser@saint-gobain.com
- **1.4 Emergency telephone number:** Tel.: 0049 228 19 240 info centre against poisoning, Universitätsklinikum Bonn

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
  - **Classification according to Regulation (EC) No 1272/2008**  
Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
Eye Irrit. 2 H319 Causes serious eye irritation.
  - **2.2 Label elements**
  - **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
  - **Hazard pictograms**
- 

GHS02



GHS07
- **Signal word** Danger
  - **Hazard statements**  
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.
  - **Precautionary statements**  
P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P280 Wear eye protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of container with content as special waste.
  - **Additional information:**  
Without sufficient ventilation formation of explosive mixtures may be possible.

Lieferant / Supplier:  
 Carl Roth GmbH + Co KG  
 Schoemperlenstr. 3-5  
 76185 Karlsruhe, Germany  
 +49 721 5606 0  
 sicherheit@carlroth.de

**Trade name: Sprayflon Plus 3**

- **2.3 Other hazards** Smoking of contaminated tobacco may cause polymer-smoke-fever
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

#### · 3.2 Chemical characterisation: Mixtures

##### · Description:

Mixture of substances listed below with nonhazardous compounds or compounds with no duty to declare.

##### · Dangerous components:

CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	Butane ( < 0,1 % 1,3-butadiene) ⚠ Flam. Gas 1A, H220; Press. Gas (Liq.), H280	50-100%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Liq.), H280	25-50%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	Propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	≥2.5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	Isobutane ( < 0,1 % 1,3-butadiene) ⚠ Flam. Gas 1A, H220; Press. Gas (Liq.), H280	2.5-10%
CAS: 5593-70-4 EINECS: 227-006-8 Reg.nr.: 01-2119967423-33	titanium tetrabutanolat ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335	≥2.5-<3%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

##### · General information:

Take affected persons out into the fresh air.

Do not leave affected persons unattended.

##### · After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

##### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

##### · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

##### · After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

##### · Information for doctor: Smoking of contaminated tobacco may cause polymer-smoke-fever

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

##### · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Trade name: Sprayflon Plus 3

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** Risk of bursting in case of fire heat
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear fully protective suit.
- **Additional information** Cool endangered receptacles with water spray.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.  
Do not spray onto a naked flame or any incandescent material.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Store away from oxidising agents.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Recommended storage temperature:** 15 - 35°C, max. 50°C
- **Storage class:** German storage class: 2B (Aerosols)
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see item 7.

 · **Ingredients with limit values that require monitoring at the workplace:**
**106-97-8 Butane ( < 0,1 % 1,3-butadiene)**

WEL (Great Britain)	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
---------------------	---

**67-63-0 Propan-2-ol**

WEL (Great Britain)	Short-term value: 1250 mg/m <sup>3</sup> , 500 ppm Long-term value: 999 mg/m <sup>3</sup> , 400 ppm
---------------------	--

**Trade name: Sprayflon Plus 3**

· DNELs		
67-63-0 Propan-2-ol		
Oral	DNEL Endverbraucher/ Consumers / Consommateur	26 mg/kg BW/ day (.) chronische Exposition, Systemische Wirkungen/ chronic Exposition, systemic effects/ Chronique Exposition, Systémique Effets Overall assessment factor (AF): 2
Dermal	DNEL - Endverbraucher/ Consumers / Consommateur	319 mg/kg BW /day (.) chronische Exposition, Systemische Wirkungen/ chronic Exposition, systemic effects/ Chronique Exposition, Systémique Effets Overall assessment factor (AF): 2
	DNEL Arbeiter / Workers/ Travailleur	888 mg/kg BW /day (.) chronische Exposition, Systemische Wirkungen/ chronic Exposition, systemic effects/ Chronique Exposition, Systémique Effets Overall assessment factor (AF): 1
Inhalative	DNEL Endverbraucher/ Consumers / Consommateur	89 mg /m3 (.) chronische Exposition, Systemische Wirkungen/ chronic Exposition, systemic effects/ Chronique Exposition, Systémique Effets Overall assessment factor (AF):2
	DNEL Arbeiter / Workers/ Travailleur	500 mg /m3 (.) chronische Exposition, Systemische Wirkungen/ chronic Exposition, systemic effects/ Chronique Exposition, Systémique Effets Overall assessment factor (AF): 1

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

Not necessary if room is well-ventilated.



Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**



Protective gloves

· **Material of gloves** If contamination is possible, use gloves made of nitrile according EN 374

· **Penetration time of glove material** > 480 min / 0,4 mm thickness

· **Eye protection:**



Tightly sealed goggles

Trade name: Sprayflon Plus 3

 · **Body protection:** Protective work clothing

**SECTION 9: Physical and chemical properties**

 · **9.1 Information on basic physical and chemical properties**

 · **General Information**

 · **Appearance:**

· <b>Form:</b>	Aerosol
· <b>Colour:</b>	Yellowish
· <b>Odour:</b>	Alcohol-like
· <b>Odour threshold:</b>	Not determined.

· <b>pH-value at 20 °C:</b>	6-8
-----------------------------	-----

 · **Change in condition**

· <b>Melting point/freezing point:</b>	Undetermined.
· <b>Initial boiling point and boiling range:</b>	-44.5 °C value concerns to propellant

· <b>Flash point:</b>	-97 °C concerns to propellant
-----------------------	----------------------------------

· <b>Flammability (solid, gas):</b>	Not applicable.
-------------------------------------	-----------------

· <b>Ignition temperature:</b>	365 °C
--------------------------------	--------

· <b>Decomposition temperature:</b>	Not determined.
-------------------------------------	-----------------

· <b>Auto-ignition temperature:</b>	Product is not selfigniting.
-------------------------------------	------------------------------

· <b>Explosive properties:</b>	Risk of bursting at temperatures > 50°C. Damage of the container may lead to the formation of explosive mixtures of gas/vapors with air.
--------------------------------	--

 · **Explosion limits:**

· <b>Lower:</b>	1.5 Vol %
· <b>Upper:</b>	10.9 Vol %

· <b>Vapour pressure:</b>	Not determined.
---------------------------	-----------------

· <b>Pressure (20°C) at 20 °C</b>	3-5 bar
-----------------------------------	---------

· <b>Density at 20 °C:</b>	0.587 g/cm <sup>3</sup>
----------------------------	-------------------------

· <b>Relative density</b>	Not determined.
---------------------------	-----------------

· <b>Vapour density</b>	Not determined.
-------------------------	-----------------

· <b>Evaporation rate</b>	Not applicable.
---------------------------	-----------------

· <b>Solubility in / Miscibility with water:</b>	Fully miscible.
--	-----------------

· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
--	-----------------

 · **Viscosity:**

· <b>Dynamic:</b>	Not determined.
· <b>Kinematic:</b>	Not determined.

 · **Solvent content:**

· <b>Organic solvents:</b>	8.7 %
· <b>VOC (EC)</b>	98.50 % = 0.1735 kg/300ml

 · **9.2 Other information**

· <b>Additional information</b>	Vapors are heavier than air.
---------------------------------	------------------------------

Trade name: Sprayflon Plus 3

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** Risk of bursting at temperatures >50°C.
- **10.3 Possibility of hazardous reactions**  
By use or incidental release the formation of explosive vapor/air mixtures is possible.
- **10.4 Conditions to avoid**  
Temperatures >50°C  
Avoid the use in the near of ignition sources.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.
- **Additional information:** Stable for a storage time of min. 24 months

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

**106-97-8 Butane ( < 0,1 % 1,3-butadiene)**

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

**74-98-6 propane**

Inhalative	LC50/4 h	>20 mg/l (rat)
	LC50 /15 min	1,443 mg/l (rat)

**67-63-0 Propan-2-ol**

Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

**75-28-5 Isobutane ( < 0,1 % 1,3-butadiene)**

Inhalative	LC50/4 h	>20 mg/l (rat)
------------	----------	----------------

**5593-70-4 titanium tetrabutanolate**

Oral	LD50	3,122 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

**Trade name: Sprayflon Plus 3**

- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water



Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation**  
empty cans: material recycling  
filled cans: remove in accordance with local regulations  
Hand over to hazardous waste disposers.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

**SECTION 14: Transport information**

· <b>14.1 UN-Number</b> · <b>ADR, IMDG, IATA</b>	UN1950
· <b>14.2 UN proper shipping name</b> · <b>ADR</b> · <b>IMDG</b> · <b>IATA</b>	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· <b>14.3 Transport hazard class(es)</b> · <b>ADR</b>	
	
· <b>Class</b> · <b>Label</b>	2.5F Gases. 2.1
· <b>IMDG, IATA</b>	
	
· <b>Class</b> · <b>Label</b>	2.1 2.1
· <b>14.4 Packing group</b> · <b>ADR, IMDG, IATA</b>	Void
· <b>14.5 Environmental hazards:</b>	Not applicable.
· <b>14.6 Special precautions for user</b> · <b>Hazard identification number (Kemler code):</b> · <b>EMS Number:</b> · <b>Stowage Code</b>	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre:

**Trade name: Sprayflon Plus 3**

· <b>Segregation Code</b>	<p>Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.</p>
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D
· <b>Remarks:</b>	<p>Transportation as "LIMITED QUANTITIES" according 3.4 ADR is possible. Sole marking: Sign for "Limited Quantities" (rhombus with two black edges) Entry in the transportation document: Transportation according chapter 3.4 ADR Tunnel category "E" in case of a load of 8000 kg (rgross weight) or more.</p>
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1

**SECTION 15: Regulatory information**

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P3a FLAMMABLE AEROSOLS**

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.



**Trade name: Sprayflon Plus 3**

· **National regulations:**

· **Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

Class	Share in %
NK	8.7

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level

(REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and

Toxic vPvB: very Persistent and very

Bioaccumulative Flam. Gas 1A:

Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Liq.): Gases under pressure – Liquefied gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· **\* Data compared to the previous version altered.**