Uses advised against:

1.3

2.1

Germany Telephone:+49 (0) 721 - 56 06 0 Telefax: +49 (0) 721 - 56 06 149

Details of the supplier of the safety data sheet

e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Relevant identified uses:

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe

Competent person responsible for the safety data :Department Health, Safety and Environment sheet:

e-mail (competent person):

SECTION 2: Hazards identification

Classification of the substance or mixture

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

Classification acc. to GHS

Toluene ROTISOLV® ≥99,8 %, Pestilyse®

acc. to Regulation (EC) No. 1907/2006 (REACH)

Safety data sheet Safety data sheet

article number: T166 Version: 6.0 en Replaces version of: 2022-05-06 Version: (5)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance	Toluene ROTISOLV® ≥99,8 %, Pestilyse®				
Article number	T166				
EC number	203-625-9				
CAS number	108-88-3				
Alternative name(s)	Methylbenzene				

1.2 Relevant identified uses of the substance or mixture and uses advised against

Laboratory chemical Laboratory and analytical use

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

sicherheit@carlroth.de



date of compilation: 2015-09-24

Revision: 2022-08-25

acc. to Regulation (EC) No. 1907/2006 (REACH)

Toluene ROTISOLV® ≥99,8 %, Pestilyse®



article number: T166

Section	SectionHazard class2.6Flammable liquid3.2Skin corrosion/irritation3.7Reproductive toxicity3.8DSpecific target organ toxicity - single exposure (narcotic effects, drowsiness)		Hazard class and category	Hazard statement
2.6			Flam. Liq. 2	H225
3.2			Skin Irrit. 2	H315
3.7			Repr. 2	H361d
3.8D			STOT SE 3	H336
3.9	3.9 Specific target organ toxicity - repeated exposure		STOT RE 2	H373
3.10 Aspiration hazard		1	Asp. Tox. 1	H304
4.1C	Hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS02, GHS07, GHS08



Hazard statements

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361d	Suspected of damaging the unborn child
H373	May cause damage to organs (central nervous system) through prolonged or re-
	peated exposure (if inhaled)
H412	Harmful to aquatic life with long lasting effects

Precautionary statements

Precautionary statements - prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking
P280	Wear protective gloves/protective clothing/eye protection/face protection

Precautionary statements - response

P302+P352	IF ON SKIN: Wash with plenty of soap and water
P308+P313	IF exposed or concerned: Get medical advice/attention
P331	Do NOT induce vomiting

acc. to Regulation (EC) No. 1907/2006 (REACH)

Toluene ROTISOLV® ≥99,8 %, Pestilyse®

article number: T166

For professional users only

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	Toluene
Molecular formula	C_7H_8
Molar mass	92,14 ^g / _{mol}
CAS No	108-88-3
EC No	203-625-9

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Call a physician immediately. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Observe aspiration hazard if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard, Irritation, Dizziness, Drowsiness, Narcosis

4.3 Indication of any immediate medical attention and special treatment needed

none



acc. to Regulation (EC) No. 1907/2006 (REACH)

Toluene ROTISOLV® ≥99,8 %, Pestilyse®



article number: T166

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapourair mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

acc. to Regulation (EC) No. 1907/2006 (REACH)

Toluene ROTISOLV® ≥99,8 %, Pestilyse®



article number: T166

6.4 Reference to other sections


Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

Measures to prevent fire as well as aerosol and dust generation



Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Keep in a cool place.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters National limit values

acc. to Regulation (EC) No. 1907/2006 (REACH)



Toluene ROTISOLV® ≥99,8 %, Pestilyse®

article number: T166

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
EU	toluene	108-88-3	IOELV	50	192	100	384			Н	2006/15/ EC
GB	toluene	108-88-3	WEL	50	191	100	384				EH40/ 2005

Notation

Ceiling-C H STEL

Ceiling value is a limit value above which exposure should not occur Absorbed through the skin Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified) TWA

Human health values

Relevant DNI	Relevant DNELs and other threshold levels								
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time					
DNEL	192 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects					
DNEL	384 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects					
DNEL	192 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects					
DNEL	384 mg/m ³	human, inhalatory	worker (industry)	acute - local effects					
DNEL	384 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic effects					

Environmental values

Relevant	t PNECs and ot	her threshold levels		
End- point	Threshold level	Organism	Environmental com- partment	Exposure time
PNEC	0,68 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0,68 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)
PNEC	13,61 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	16,39 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	16,39 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
PNEC	2,89 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)

8.2 **Exposure controls**

acc. to Regulation (EC) No. 1907/2006 (REACH)

Toluene ROTISOLV® ≥99,8 %, Pestilyse®



article number: T166

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

FKM (fluoro rubber)

material thickness

≥0,4 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

acc. to Regulation (EC) No. 1907/2006 (REACH)

Toluene ROTISOLV® ≥99,8 %, Pestilyse®

® ROTH

article number: **T166**

SECTION 9: Physical and chemical properties

9.1	Information on basic physical and chemical pro	perties
	Physical state	liquid
	Colour	colourless
	Odour	characteristic
	Melting point/freezing point	-95 °C at 1.013 hPa (ECHA)
	Boiling point or initial boiling point and boiling range	110,6 °C at 1.013 hPa (ECHA)
	Flammability	flammable liquid in accordance with GHS criteria
	Lower and upper explosion limit	39 g/m³ (LEL) - 300 g/m³ (UEL) / 1,1 vol% (LEL) - 7,1 vol% (UEL)
	Flash point	4,4 °C at 1.013 hPa (ECHA)
	Auto-ignition temperature	480 °C at 1.013 hPa (ECHA) (auto-ignition temper- ature (liquids and gases))
	Decomposition temperature	not relevant
	pH (value)	not determined
	Kinematic viscosity	not determined
	Dynamic viscosity	0,56 mPa s at 25 °C
	Solubility(ies)	
	Water solubility	0,573 ^g / _l at 25 °C (ECHA)
	Partition coefficient	
	Partition coefficient n-octanol/water (log value):	2,73 (pH value: 7, 20 °C) (ECHA)
	Soil organic carbon/water (log KOC)	2,312 (ECHA)
	Vapour pressure	29 hPa at 20 °C
	Density and/or relative density	
	Density	0,87 ^g / _{cm³} at 20 °C (ECHA)
	Relative vapour density	3,18 (air = 1)
	Particle characteristics	not relevant (liquid)
	Other safety parameters	
	Oxidising properties	none
9.2	Other information	
	Information with regard to physical hazard classes:	There is no additional information.

acc. to Regulation (EC) No. 1907/2006 (REACH)

Toluene ROTISOLV® ≥99,8 %, Pestilyse®

® Foth

article number: **T166**

Other safety characteristics:

Gas group (explosion group)

Maximum explosion pressure

Surface tension

Maximum Experimental Safe Gap value; MESG > 0,9 mm

7,7 bar

IIA

27,73 ^{mN}/_m (25 °C) (ECHA)

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Danger of explosion: Perchlorates, Nitric acid, Sulphuric acid, Acetic acid, **Violent reaction with:** Mineral acids, Strong acid, strong oxidiser

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

different Rubber articles, plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity

Exposure route	Endpoint	Value	Species	Method	Source		
oral	LD50	5.580 ^{mg} / _{kg}	rat		ECHA		
inhalation: vapour	LC50	28,1 ^{mg} / _ا /4h	rat		ECHA		
dermal	LD50	>5.000 ^{mg} / _{kg}	rabbit		ECHA		

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

acc. to Regulation (EC) No. 1907/2006 (REACH)

Toluene ROTISOLV® ≥99,8 %, Pestilyse®



article number: T166

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

May cause damage to organs (central nervous system) through prolonged or repeated exposure (if inhaled).

Hazard category	Target organ	Exposure route
2	central nervous system	if inhaled

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

aspiration hazard

• If in eyes

causes slight to moderate irritation

• If inhaled

dizziness, fatigue, narcosis

• If on skin

causes skin irritation

• Other information

none

11.2 Endocrine disrupting properties

Not listed.

11.3 Information on other hazards

There is no additional information.

acc. to Regulation (EC) No. 1907/2006 (REACH)



Toluene ROTISOLV® ≥99,8 %, Pestilyse®

article number: T166

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute)

Endpoint	Value	Species	Source	Exposure time
LC50	5,5 ^{mg} / _l	fish	ECHA	96 h
EC50	84 ^{mg} / _l	microorganisms	ECHA	24 h

Aquatic toxicity (chronic)

Endpoint	Value	Species	Source	Exposure time
LC50	3,78 ^{mg} / _l	aquatic invertebrates	ECHA	2 d
EC50	3,23 ^{mg} / _l	aquatic invertebrates	ECHA	7 d

Biodegradation

The substance is readily biodegradable.

12.2 Process of degradability

Theoretical Oxygen Demand: 3,125 ^{mg}/_{mg} Theoretical Carbon Dioxide: 3,343 ^{mg}/_{mg}

Process of degradability		
Process	Degradation rate	Time
biotic/abiotic	86 %	20 d

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	2,73 (pH value: 7, 20 °C) (ECHA)
BCF	90 (ECHA)

12.4 Mobility in soil

Henry's law constant	485 ^{Pa m³} / _{mol} (ECHA)
The Organic Carbon normalised adsorption coefficient	2,312 (ECHA)

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Not listed.

acc. to Regulation (EC) No. 1907/2006 (REACH)



Toluene ROTISOLV® ≥99,8 %, Pestilyse®

article number: T166

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste catalogue ordinance (Germany).

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number or ID number

	ADRRID	UN 1294
	IMDG-Code	UN 1294
	ICAO-TI	UN 1294
14.2	UN proper shipping name	
	ADRRID	TOLUENE
	IMDG-Code	TOLUENE
	ICAO-TI	Toluene
14.3	Transport hazard class(es)	
	ADRRID	3
	IMDG-Code	3
	ICAO-TI	3
14.4	Packing group	
	ADRRID	II
	IMDG-Code	II
	ICAO-TI	II


acc. to Regulation (EC) No. 1907/2006 (REACH)

® Foth

Toluene ROTISOLV® ≥99,8 %, Pestilyse®

article number: T166

- 14.5 **Environmental hazards** non-environmentally hazardous acc. to the dangerous goods regulations Special precautions for user 14.6 Provisions for dangerous goods (ADR) should be complied within the premises. Maritime transport in bulk according to IMO instruments 14.7 The cargo is not intended to be carried in bulk. 14.8 Information for each of the UN Model Regulations Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information Proper shipping name TOLUENE Particulars in the transport document UN1294, TOLUENE, 3, II, (D/E) Classification code F1 3 Danger label(s) Excepted quantities (EQ) E2 Limited quantities (LQ) 1 L
 - Transport category (TC)2Tunnel restriction code (TRC)D/EHazard identification No33Emergency Action Code3YE
 - Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional information



acc. to Regulation (EC) No. 1907/2006 (REACH)

Toluene	ROTISOLV	≷ ≥99.8 %.	Pestilyse®



article number: **T166**

Special provisions (SP)	-	
Excepted quantities (EQ)	E2	
Limited quantities (LQ)	1 L	
EmS	F-E, S-D	
Stowage category	В	
International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information		
Proper shipping name	Toluene	
Particulars in the shipper's declaration	UN1294, Toluene, 3, II	
Danger label(s)	3	
Excepted quantities (EQ)	E2	
Limited quantities (LQ)	1 L	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Seveso Directive

2012/18/EU (Seveso III)				
Νο	Dangerous substance/hazard categories	Qualifying quantity plication of lower a quiren		Notes
P5c	flammable liquids (cat. 2, 3)	5.000	50.000	51)

Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

Deco-Paint Directive

VOC content	100 % 870 ^g /l

Industrial Emissions Directive (IED)

VOC content	100 %
VOC content (Water content was discounted)	870 ^g /l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

acc. to Regulation (EC) No. 1907/2006 (REACH)



Toluene ROTISOLV® ≥99,8 %, Pestilyse®

article number: **T166**

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

Pollutant release and transfer registers (PRTR)

Name of substance	CAS No	Remarks	Threshold for releases to air (kg/year)
Toluene	108-88-3	(11)	

Legend

(11) Single pollutants are to be reported if the threshold for BTEX (the sum parameter of benzene, toluene, ethyl benzene, xylenes) is exceeded

Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Toluene	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)	

Legend

A) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

not listed

Regulation on drug precursors

Name of substance	CAS No	Wt%	Classification	CN Code	Threshold level
Toluene	108-88-3	100	Category 3	2902 30 00	

Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list not listed

acc. to Regulation (EC) No. 1907/2006 (REACH)

Toluene ROTISOLV® ≥99,8 %, Pestilyse®



article number: T166

Restrictions according to GB REA	Restrictions according to GB REACH, Annex 17			
Dangerous substances with restrictions (GB REACH, Annex 17)				
Name of substance	Name acc. to inventory	CAS No	No	
Toluene	Toluene	108-88-3	48	
Toluene	this product meets the criteria for classi- fication in accordance with Regulation No 1272/2008/EC		3	
Toluene	flammable / pyrophoric		40	

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

UN Convention against Illicit Traffic in Narcotic Drugs and Psychotropic Substances

Name of substance	CAS No	Listed in	HS code
Toluene	108-88-3	Table II	2902.30

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
JP	ISHA-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory

acc. to Regulation (EC) No. 1907/2006 (REACH)

Toluene ROTISOLV® ≥99,8 %, Pestilyse®



article number: T166

Legend

TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1	The most important adverse physicochemical, human health and environmental effects: Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.	The most important adverse physicochemical, human health and environmental effects: Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.	yes
2.2		Hazard statements: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in imple- mentation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de naviga- tion intérieures (European Agreement concerning the International Carriage of Dangerous Goods by In- land Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concern- ing the International Carriage of Dangerous Goods by Road)
BCF	Bioconcentration factor
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CN Code	Combined Nomenclature
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identi- fier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances

acc. to Regulation (EC) No. 1907/2006 (REACH)

Toluene ROTISOLV® ≥99,8 %, Pestilyse®



article number: **T166**

Abbr.	Descriptions of used abbreviations
EmS	Emergency Schedule
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
ΙΑΤΑ	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

acc. to Regulation (EC) No. 1907/2006 (REACH)

Toluene ROTISOLV® ≥99,8 %, Pestilyse®



article number: T166

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs (central nervous system) through prolonged or repeated exposure (if inhaled).
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.